LOCKOUT/TAGOUT SITE SPECIFIC PROCEDURE

| Equipment: | Location: | |
|---|--|-----------------------------|
| Energy Source(s) (shock these | that apply): | |
| Energy Source(s) (check those ☐ Electricity | s triat apply). ☐ Kinetic parts (moving parts) | ☐ Thermal component |
| ☐ Compressor air | ☐ Chemicals | ☐ Hydraulic component |
| □ Water | ☐ Pneumatic components | ☐ Potential source (stored) |
| ☐ Natural gas | ☐ Control power | ☐ Other compressed gas |
| Other: | • | |
| | | 2 0 |
| Lockout and/or Tagout Device(| (s) (check those that apply): | |
| ☐ Lock Box | ☐ Power Cord Plug Box/Cover | ☐ Adjustable Cable Device |
| ☐ Locks w/keys | □ Universal Valve Device | ☐ Fuse Lockout Device |
| ☐ Tagout Tags | ☐ Gate Valve Device | □ Wall Switch Device |
| ☐ Lockout Hasps | ☐ Circuit Breaker Device | ☐ Supervisory Lock w/key |
| ☐ Other: | | |
| Procedures to notify all affected | d employees and inmates: | |
| Troopadios to flothly all allocator | | |
| | | |
| | | |
| | | |
| Description of the shutdown pro | ocedures: | |
| | | |
| | | |
| | | |
| | | |
| Procedures for the isolation of | equipment from all power sources: | |
| | | |
| | | |
| | | |
| | | |
| Procedure for locking out or tag | gging out equipment: | |
| - | | |
| | | |
| | | |
| | | |
| Procedures for the release of s | tored energy (where applicable): | |
| | | |
| - | | |
| | | |
| December 1 | Constitution of the consti | |
| Procedures to ensure that equi | ipment is isolated from all power source | JS: |
| | | |
| | | |
| | | |

Restoring equipment to service:

Affected Employee

| | n the servicing or maintenance is completed and the ormal operating condition, the following steps will be | | |
|----|--|------|--|
| | Check the machine or equipment and the immediate area around the machine or equipment to ensure that nonessential items have been removed and that the machine or equipment components are operationally intact. | | |
| | Check the work area to ensure that all employees and inmates have been safely positioned or removed from the area. | | |
| | Verify that the controls are in neutral. | | |
| | Remove the lockout/tagout devices and reenergize the machine or equipment. | | |
| | □ Notify affected employees that the servicing or maintenance is completed and the machine or equipment is ready for use. | | |
| Pr | imary Authorized Employee | Date | |
| Au | ithorized Employee | Date | |
| Au | ithorized Employee | Date | |
| Au | uthorized Employee | Date | |
| Au | thorized Employee | Date | |
| Au | thorized Employee | Date | |
| Au | ithorized Employee | Date | |
| Af | fected Employee | Date | |

(R 01/22)

Date