



Clean Harbors Lone Mountain, LLC
40355 S. County Road 236
Waynoka, OK 78360-6302
(580) 697-3500

RECEIVED

DEC 23 2025

LAND PROTECTION DIVISION
DEPT. OF ENVIRON. QLTY

December 19, 2025

Ms. Hillary Young, P.E.
Chief Engineer
Land Protection Division
Oklahoma Department of Environmental Quality
707 North Robinson
P.O. Box 1677
Oklahoma City, OK 73101-1677

255723 CD__ #c__ c/o__

RE: Response to Notice of Deficiency
Clean Harbors Lone Mountain, LLC; EPA ID No. OKD065438376

Dear Ms. Young:

Clean Harbors Lone Mountain, LLC ("CHLM" or the "Facility") received Notice of Deficiency (NOD) from the Oklahoma Department of Environmental Quality on November 20, 2025, requesting CHLM to submit drawings that are certified by a qualified Professional Engineer ("PE") in accordance with 40 C.F.R. § 264.14(a). and information clearly demonstrates that secondary containment for the proposed building will sufficiently contain 10% of the volume of the containers or the volume of the largest container, whichever is greater in accordance with 40 CFR §264.175(b)(3). for the Class 3, Tier III Permit Modification Request for Landfill Cell 16 Engineering Report submitted on August 27, 2025.

Please find the attached drawings for the Class 3, Tier III Permit Modification Request to expand CHLM's container management building required by 40 CFR § 270.14 (a) and 40 CFR § 264.175 (b)(3).

If you have any questions regarding this matter, or require any additional information, please feel free to contact me at (580) 697-3500 or meriwether.michael@cleanharbors.com or (580)-430-7219 or sawyer.christine@cleanharbors.com.

Sincerely,

Michael Meriwether
General Manager
Clean Harbors Lone Mountain, LLC

RECEIVED

Attachments: Updated "PE" certified drawings

DEC 22 2025



CC: Roarke Blackwell, ODEQ
Hilary Young, ODEQ
Michael Meriwether, Clean Harbors
Jared Torstenson, Clean Harbors
Jay Adair, Clean Harbors
Michael Crisenberry, Clean Harbors
Earthea Nance, EPA Region 6

CONTAINER MANAGEMENT BUILDING ADDITION

CLEAN HARBORS - LONE MOUNTAIN FACILITY

SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST I.M.
MAJOR COUNTY, OKLAHOMA

36°25'42.17"N, 98°48'20.62"W
36.428381°, -98.805728°




CONTACTS

CLEAN HARBORS - JOHN DINAPOLI - (781) 858-7412
CLEAN HARBORS - DOUG SCHRANTZ P.E. - (781) 556-9608
ENVIROTECH ENGINEERING & CONSULTING - ISAIAH IRBY, EIT (580)-234-8780
(DESIGN ENGINEER)
ENVIROTECH ENGINEERING & CONSULTING - TYLER WILLIAMS, PE (580)-234-8780
(SUPERVISING ENGINEER)



UTILITY CAUTION

THE CONTRACTOR IS CAUTIONED THE LOCATION AND DEPTH OF EXISTING UTILITIES AS SHOWN ON THESE PLANS ARE BASED ON PUBLICLY AVAILABLE RECORDS OF THE VARIOUS UTILITY COMPANIES AND FIELD MEASUREMENTS. THE INFORMATION PROVIDED IS NOT TO BE RELIED ON AS BEING PRECISE OR COMPLETE. THE CONTRACTOR MUST CONTACT THE LOCAL UTILITY LOCATION CENTER AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATIONS OF THE UTILITIES.





INDEX TO DRAWINGS

11X17

SHEET NO. DESCRIPTION

1. COVER SHEET
2. EXISTING SITE AND DEMOLITION PLAN
3. SITE PLAN
4. NOTES
5. ADJOINING STRUCTURE DETAILS
6. ARCHITECTURAL PROFILES
7. ARCHITECTURAL PROFILES



ENVIROTECH

ENGINEERING

2500 N. Eleventh Street Enid, OK 73701 • 580.234.8780 • envirotechconsulting.com
C.A. #1960 - Expiration Date: 6-30-2026



NORTH

0 30 60
Scale 1=50
Bar Scale is intended for 11' x 17' (Full Size)

**ENVIROTECH
ENGINEERING**
2500 North Eleventh Street
Enid, Oklahoma
580.234.8780
envirotechconsulting.com

COPYRIGHT
This document and the information contained may NOT be reproduced or
copied from without the express written
permission of EnviroTech Engineering and
Consulting, Inc. Unauthorized copying,
disclosure or construction use are prohibited
by the copyright law.

	DATE	DESCRIPTION
--	------	-------------

The logo for Clean Harbors Environmental Services, Inc. It features the company name "CleanHarbors" in a stylized, red, wavy font. The "C" and "H" are particularly prominent. To the right of the name, the words "ENVIRONMENTAL SERVICES, INC." are written in a smaller, red, sans-serif font.



**EXISTING SITE AND DEMOLITION PLAN
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY**

SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

TE: NOVEMBER 2025
ALE: 1st = 60'
SIGNED BY: I. IRBY
AWN BY: I. IRBY
ECKED BY: T. WILLIAMS
JECT NO. 024330-00
ET NO. 2 OF 7

2 OF 7

This topographic map shows a construction site with several key features and proposed changes. The site includes an **EXISTING BUILDING** (FF=1434.16'), a **CONCRETE DRIVEWAY**, a **STAIRS**, a **COVERED LOADING DOCK**, a **CONCRETE AREA**, **SCALES**, a **METAL SHED**, and an **ACCESS ROAD**. A **POWER POLE** is located on the left, and a **36" CMP PIPE** (FL=1426.58) is marked with a red arrow. A **MONITORING WELLS** area is also indicated. The map features contour lines with elevations ranging from 1420 to 1450. Red arrows and text callouts highlight proposed changes: **RELOCATE POWER POLE (BY OTHERS)** (multiple locations), **MODIFY CONCRETE STAIRS (REMOVE HANDRAIL AND SAWCUT STAIRS TO MATCH PROPOSED GRADE)**, **RELOCATE POWER POLE (BY OTHERS)**, **REMOVE EXISTING LOADING RAMP (BY OTHERS)**, **RELOCATE POWER POLE (BY OTHERS)**, **REMOVE SHED**, **REMOVE NORTHERN BAY OF MATERIAL STORAGE LEAN-TO (BY OTHERS) (REMOVE 20-FT)**, **POWER POLE PROTECT IN PLACE**, **18" PIPE PROTECT IN PLACE**, **POWER POLE PROTECT IN PLACE**, **MANHOLE PROTECT IN PLACE**, **18" PIPE PROTECT IN PLACE**, and **POWER POLE**. A specific cut is labeled **BM-1 "X" CUT ON CONCRETE** with coordinates **N:11480.59**, **E:8550.34**, and **Z:1425.60**. The **EDGE OF ROAD** is also marked.



**ENVIROTECH
ENGINEERING**
2500 North Eleventh Street
Enid, Oklahoma
580.234.8780
envirotechconsulting.com
P.E. #24553 - Expiration Date: 1-31-2025

COPYRIGHT

NO.	DATE	DESCRIPTION
-----	------	-------------

The logo for Clean Harbors Environmental Services, Inc. It features the company name "Clean Harbors" in a stylized, red, wavy font. To the right of the name, the words "ENVIRONMENTAL SERVICES, INC." are written in a smaller, red, sans-serif font.

SITE PLAN
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

DATE:	NOVEMBER 2025
CALE:	1" = 40'
DESIGNED BY:	I. IRBY
RAWN BY:	I. IRBY
CHECKED BY:	T. WILLIAMS
PROJECT NO.	024330-00
HEET NO.	3 OF 7

3 OF 7

GENERAL NOTES:

1. ANY QUANTITIES SHOWN WITHIN THESE PLANS HAVE BEEN PROVIDED FOR PERMITTING PURPOSES ONLY AND ARE NOT INTENDED FOR USE IN PREPARATION OF CONTRACT DOCUMENTS. QUANTITIES INTENDED FOR, BUT NOT LIMITED TO, THE PREPARATION OF PROPOSALS AND BID DOCUMENTS SHALL BE INDEPENDENTLY EVALUATED BY THE ESTIMATING PARTY BASED UPON THE CONTENTS OF THESE PLANS.
2. RETURN ALL DISTURBED AREAS TO A CONDITION EQUAL TO OR BETTER THAN THE CONDITION PRIOR TO CONSTRUCTION.
3. THE SUBCONTRACTOR SHALL EMPLOY ALL NECESSARY BARRICADES, SIGNS, FENCES, FLASHING LIGHTS, FLAGMEN, ETC. FOR MAINTENANCE AND PROTECTION OF TRAFFIC AS REQUIRED BY CLEAN HARBORS REFER TO THE MANUALS ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), LATEST EDITION, FOR DETAILS OF TRAFFIC CONTROL STANDARDS AND DEVICES.
4. THE SUBCONTRACTOR SHALL PROTECT ALL MONUMENTS, IRON PINS, AND PROPERTY CORNERS DURING CONSTRUCTION.
5. ALL SITE DIMENSIONS ARE REFERENCED TO THE FACE OF BACK OR EDGE OF PAVING UNLESS OTHERWISE NOTED. ALL BUILDING DIMENSIONS ARE REFERENCED TO THE OUTSIDE FACE OF THE STRUCTURE.
6. THE SUBCONTRACTOR SHALL VERIFY ALL DIMENSIONS IN THE FIELD PRIOR TO THE START OF CONSTRUCTION. THE SUBCONTRACTOR SHALL BE RESPONSIBLE FOR ALL FIELD DIMENSIONS AND SHALL REPORT ANY DISCREPANCIES BETWEEN THE PLANS AND ACTUAL FIELD CONDITION TO THE OWNER OR OWNER'S REPRESENTATIVE IMMEDIATELY. SUBCONTRACTOR SHALL WAIT FOR INSTRUCTION PRIOR TO PROCEEDING WITH WORK.
7. THE SUBCONTRACTOR SHALL PROVIDE SMOOTH TRANSITIONS FROM PROPOSED FEATURES TO EXISTING FEATURES AS NECESSARY.
8. THE SUBCONTRACTOR SHALL REPAIR, RESURFACE, RECONSTRUCT OR REFURBISH AT OWNERS DISCRETION ANY AREAS DAMAGED DURING CONSTRUCTION BY THE SUBCONTRACTOR, HIS SUBCONTRACTORS OR SUPPLIERS AT NO ADDITIONAL COST TO THE OWNER.
9. GRASSED AREAS DISTURBED BY CONSTRUCTION ACTIVITIES SHALL BE SEEDED OR SODDED AND

ESTABLISHMENT

1. SUBCONTRACTOR SHALL REFER TO THE CONSTRUCTION DOCUMENTS, INCLUDING BUT NOT LIMITED TO THE WRITTEN SPECIFICATIONS, CONSTRUCTION DRAWINGS, STORMWATER POLLUTION PLAN, AND GEOTECHNICAL REPORT.
2. ALL CONSTRUCTION SHALL BE IN STRICT ACCORDANCE WITH THE OWNERS DESIGN GUIDELINES AND SPECIFICATIONS, AND WHERE APPLICABLE, SHALL MEET THE REQUIREMENTS OF THE GOVERNING/PERMITTING AUTHORITY HAVING JURISDICTION.
3. SUBCONTRACTOR IS RESPONSIBLE FOR THEIR OWN HORIZONTAL AND VERTICAL CONTROL, REFERENCE POINTS, AND CONSTRUCTION STAKING AS INCIDENTAL TO THE PROJECT.
4. THE SUBCONTRACTOR SHALL FIELD VERIFY EXISTING ELEVATIONS/PROPERTY LINES/UTILITIES/DRAINAGE PRIOR TO CONSTRUCTION START.
5. ALL WORK NOT INCLUDED IN THE LUMP SUM SCOPE OF WORK SHALL BE CONSIDERED INCIDENTAL AND THE COST THEREOF SHALL BE INCLUDED IN LUMP SUM PRICING.
6. SUBCONTRACTOR SHALL REFER TO THE ARCHITECTURAL AND MEP PLANS AND SPECIFICATIONS BEING A PART OF THE CONSTRUCTION DOCUMENTS FOR THE EXACT LOCATIONS AND DIMENSIONS OF ENTRY, EXIT PORCHES, PRECISE BUILDING DIMENSIONS, EXACT BUILDING UTILITY ENTRANCE, AND DOWNSPOUT LOCATIONS/SPECIFICATIONS/DETAILS.
7. ALL DIMENSIONS SHOWN ARE TO THE EDGE OF CONCRETE UNLESS OTHERWISE NOTED.
8. BUILDING DIMENSIONS ARE TO OUTSIDE OF STEEL, UNLESS OTHERWISE SHOWN.
9. SUBCONTRACTOR SHALL REFER TO THE ARCHITECTURAL AND STRUCTURAL PLANS AND SPECIFICATIONS PREPARED BY OTHERS FOR ACTUAL LOCATION AND DETAILS OF ALL UTILITY ENTRANCES. SUBCONTRACTOR SHALL COORDINATE INSTALLATION OF UTILITIES IN SUCH AS MANNER AS TO AVOID CONFLICTS AND ASSURE PROPER DEPTHS ARE ACHIEVED, AS WELL AS COORDINATE WITH ANY UTILITY COMPANIES FOR APPROVED LOCATIONS AND SCHEDULING OF TIE-INS/CONNECTIONS TO THEIR FACILITIES.
10. REFER TO ARCHITECTURE PLANS FOR SITE LIGHTING AND ELECTRICAL CONDUIT PLANS. POLE LOCATIONS ARE SHOWN ON THIS SHEET FOR REFERENCE ONLY. IT IS THE SUBCONTRACTORS RESPONSIBILITY TO IDENTIFY AND ADJUST ANY CONSTRUCTED CONFLICTS WITH UNDERGROUND UTILITIES, SIDEWALKS, ETC.
11. CHECK ARCHITECTURAL PLANS FOR EXACT DOWNSPOUT LOCATIONS.

RAVING NOTES:

1. ALL PAVING MATERIALS AND CONSTRUCTION SHALL BE IN ACCORDANCE WITH THESE PLANS, THE FINAL GEOTECHNICAL REPORT, COMMONLY ACCEPTED CONSTRUCTION STANDARDS, OR AT THE SOLE DISCRETION OF THE OWNERS.
2. SUBCONTRACTOR IS RESPONSIBLE FOR ALL PAVING AND PAVING SUBGRADE TESTING AND CERTIFICATION, UNLESS SPECIFIED OTHERWISE BY OWNER. ALL PAVING AND PAVING SUBGRADE TESTING SHALL BE COORDINATED WITH ENVIROTECH.
3. SUBCONTRACTOR SHALL CONSTRUCT PROPOSED PAVEMENT TO MATCH EXISTING PAVEMENT AND BE PINNED WITH A SMOOTH, FLUSH, TRANSITION.
4. SUBCONTRACTOR SHALL FURNISH AND INSTALL ALL PAVEMENT MARKINGS AS DIRECTED BY OWNER.
5. ALL REINFORCING STEEL FOR CONCRETE PAVING SHALL CONFORM TO THE GEOTECHNICAL REPORT, CITY STANDARDS, AND ASTM A-615, GRADE 60, AND SHALL BE SUPPORTED PROPERLY BY REBAR CHAIRS.
6. SUBCONTRACTOR SHALL TAKE FIELD SLOPE MEASUREMENTS ON FINISHED SUBGRADE AND FORM BOARDS PRIOR TO PLACING PAVEMENT TO VERIFY THAT ALL ADA SLOPE REQUIREMENTS ARE PROVIDED. SUBCONTRACTOR SHALL CONTACT PROJECT ENGINEER PRIOR TO PAVING IF ANY EXCESSIVE SLOPES ARE ENCOUNTERED. NO SUBCONTRACTOR CHANGE ORDERS WILL BE ACCEPTED FOR ADA SLOPE COMPLIANCE ISSUES.

DEMOLITION NOTES:

1. THE SUBCONTRACTOR SHALL FIELD VERIFY AND LOCATE ALL EXISTING UTILITIES ON SITE PRIOR TO DEMOLITION.
2. THE SUBCONTRACTOR SHALL PERFORM DEMOLITION ACTIVITIES AS NOTED AND SHOWN ON THESE PLANS AND AS DIRECTED BY THE OWNER.
3. IT WILL BE THE SUBCONTRACTOR'S RESPONSIBILITY TO OBTAIN ANY PERMITS AND PAY FEES REQUIRED FOR DEMOLITION AND HAUL-OFF FROM THE APPROPRIATE AUTHORITIES.
4. THE SUBCONTRACTOR SHALL PREPARE ALL DOCUMENTS AND ACQUIRE APPROPRIATE PERMITS AS REQUIRED PRIOR TO THE COMMENCEMENT OF DEMOLITION.
5. THE DEMOLITION PLAN IS INTENDED TO DEPICT GENERAL DEMOLITION AND UTILITY WORK. IT IS NOT INTENDED TO IDENTIFY EACH ELEMENT OF DEMOLITION OR RELOCATION. SUBCONTRACTOR SHALL COORDINATE WITH THE OWNER AND APPROPRIATE UTILITY COMPANY PRIOR TO WORK.
6. SUBCONTRACTOR TO COMPLETELY DEMOLISH AND DISPOSE OF OFFSITE OR AS DIRECTED BY OWNER IN A LAWFUL MANNER EXISTING BUILDINGS, INCLUDING FOUNDATIONS AND ALL APPURTEINANCES.
7. REMOVE AND DISPOSE OF ANY SIDEWALK, FENCES, STAIRS, WALLS, FOUNDATIONS, CONDUITS, LIGHT POLE BASES, DEBRIS AND RUBBISH REQUIRING REMOVAL FROM THE WORK AREA IN AN APPROVED LANDFILL.
8. REMOVE AND/OR PLUG EXISTING UTILITIES SUCH AS SANITARY SEWER, WATER, GAS, ELECTRIC, AND TELEPHONE AS SHOWN. THE SUBCONTRACTOR IS RESPONSIBLE FOR CONTACTING EACH UTILITY COMPANY TO COORDINATE REMOVAL OF ALL UTILITIES AND FOR DETERMINING HORIZONTAL AND VERTICAL LOCATIONS OF UTILITIES PRIOR TO COMMENCING WORK.
9. THE SUBCONTRACTOR SHALL ARRANGE FOR RESETTING OF CURB BOXES, VALVE BOXES AND REMOVAL AND/OR RELOCATION OF OVER-HEAD UTILITIES AND POLES WITH THE APPROPRIATE UTILITY COMPANY.
10. INSTALL ALL EROSION AND SEDIMENT CONTROL DEVICE PROTECTION PRIOR TO BEGINNING DEMOLITION WORK.

UTILITY NOTES:

1. SUBCONTRACTOR SHALL REFER TO THE CONSTRUCTION DOCUMENTS, INCLUDING BUT NOT LIMITED TO THE WRITTEN SPECIFICATIONS, CONSTRUCTION DRAWINGS, AND GEOTECHNICAL REPORT.
2. ALL CONSTRUCTION SHALL BE IN STRICT ACCORDANCE WITH THE OWNERS DESIGN GUIDELINES AND SPECIFICATIONS, AND WHERE APPLICABLE, SHALL MEET THE REQUIREMENTS OF THE GOVERNING/PERMITTING AUTHORITY HAVING JURISDICTION.
3. THE SUBCONTRACTOR SHALL FIELD VERIFY EXISTING ELEVATIONS/PROPERTY LINES/UTILITIES/DRAINAGE PRIOR TO CONSTRUCTION START.
4. SUBCONTRACTOR SHALL REFER TO THE ARCHITECTURAL AND MEP PLANS AND SPECIFICATIONS BEING A PART OF THE CONSTRUCTION DOCUMENTS FOR THE EXACT LOCATIONS AND DIMENSIONS OF ENTRY, EXIT PORCHES, PRECISE BUILDING DIMENSIONS, EXACT BUILDING UTILITY ENTRANCE, AND DOWNSPOUT LOCATIONS/SPECIFICATIONS/DETAILS.
5. SUBCONTRACTOR IS REQUIRED TO CALL ONE CALL AS WELL AS THE APPROPRIATE UTILITY COMPANY AT LEAST 48 HOURS BEFORE ANY EXCAVATION/CONSTRUCTION ACTIVITIES TAKE PLACE. IT SHALL BE THE RESPONSIBILITY OF THE SUBCONTRACTOR TO RELOCATE ALL EXISTING UTILITIES WHICH ARE IN CONFLICT WITH PROPOSED IMPROVEMENTS.
6. SUBCONTRACTOR SHALL ENSURE ALL CONSTRUCTED UTILITIES MEET THE MINIMUM SEPARATION AND COVER REQUIREMENTS SET FORTH BY THE PROVIDER, FEDERAL/STATE/LOCAL REGULATIONS, OR SPECIFICATIONS. IN THE EVENT THERE IS A CONFLICT, THE MOST STRINGENT SHALL APPLY.
7. DIMENSIONS SHOWN ARE TO CENTERLINE OF UTILITY
8. SUBCONTRACTOR SHALL COMPLY COMPLETELY WITH THE LATEST STANDARDS OF OSHA DIRECTIVES OR ANY OTHER AGENCY HAVING JURISDICTION FOR EXCAVATION AND TRENCHING PROCEDURES. THE SUBCONTRACTOR SHALL USE SUPPORT SYSTEMS, SLOPING, BENCHING, AND OTHER MEANS OF PROTECTION. THIS IS TO INCLUDE, BUT NOT LIMITED TO, ACCESS AND EGRESS FROM ALL EXCAVATION AND TRENCHING. SUBCONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH PERFORMANCE CRITERIA AS REQUIRED BY OSHA.

EROSION CONTROL NOTES:

1. ALL SUBCONTRACTORS INVOLVED WITH STORMWATER POLLUTION PREVENTION SHALL OBTAIN A COPY OF THE STORMWATER POLLUTION PREVENTION PLAN
2. ALL TEMPORARY EROSION AND SEDIMENT CONTROLS MEASURES SHALL BE DISPOSED OF WITHIN 30 DAYS AFTER FINAL STABILIZATION. FINAL STABILIZATION HAS OCCURRED WHEN ALL SOIL DISTURBING ACTIVITIES ARE COMPLETED AND ESTABLISHED.
3. BEST MANAGEMENT PRACTICES (BMPS) AND CONTROLS SHALL CONFORM TO FEDERAL, STATE, OR LOCAL REQUIREMENTS OR MANUAL OF PRACTICES, AS APPLICABLE. SUBCONTRACTOR SHALL IMPLEMENT ADDITIONAL CONTROLS AS DIRECTED BY PERMITTING AGENCY OR OWNER.
4. SUBCONTRACTOR SHALL MINIMIZE CLEARING TO THE MAXIMUM EXTENT PRACTICAL.
5. ALL STORMWATER POLLUTION PREVENTION MEASURES PRESENTED ON THIS PLAN, AND IN THE STORMWATER POLLUTION PREVENTION PLAN, SHALL BE INITIATED AS SOON AS PRACTICABLE.
6. DISTURBED PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITY HAS STOPPED FOR AT LEAST 14-DAYS SHALL BE TEMPORARILY SEEDED AND COVERED. THESE AREAS SHALL BE SEEDED AND COVERED NO LATER THAN 14-DAYS FROM THE LAST CONSTRUCTION ACTIVITY OCCURRING IN THESE AREAS.
7. DISTURBED PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITY HAS PERMANENTLY STOPPED SHALL BE PERMANENTLY SEEDED AND COVERED. THESE AREAS SHALL BE SEEDED AND COVERED NO LATER THAN 14-DAYS AFTER THE LAST CONSTRUCTION ACTIVITY OCCURRING IN THESE AREAS. REFER TO THE GRADING PLAN AND/OR LANDSCAPE PLAN.
8. ALL MATERIALS SPILLED, DROPPED, WASHED, OR TRACKED FROM VEHICLES ONTO ROADWAYS OR INTO STORM DRAINS MUST BE REMOVED IMMEDIATELY.
9. SUBCONTRACTORS WILL BE RESPONSIBLE FOR REMOVING SEDIMENT THAT MAY HAVE COLLECTED IN THE STORM SEWER DRAINAGE SYSTEMS IN CONJUNCTION WITH THE STABILIZATION OF THE SITE.
10. ONSITE AND OFFSITE SOIL STOCKPILE AND BORROW AREAS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION THROUGH IMPLEMENTATION OF BEST MANAGEMENT PRACTICES. STOCKPILE AND BORROW AREA LOCATIONS SHALL BE NOTED ON THE SITE PLAN AND PERMITTED IN ACCORDANCE WITH GENERAL PERMIT REQUIREMENTS.
11. SILT FENCING SHALL BE INSTALLED DOWN GRADIENT OF ALL STOCKPILES TO PREVENT RUNOFF OF CONSTRUCTION MATERIAL.
12. SLOPES SHALL BE LEFT IN A ROUGHENED CONDITION DURING THE GRADING PHASE TO REDUCE RUNOFF VELOCITIES AND EROSION.
13. DUE TO THE GRADE CHANGES DURING THE DEVELOPMENT OF THE PROJECT, THE SUBCONTRACTOR SHALL BE RESPONSIBLE FOR ADJUSTING THE EROSION CONTROL MEASURES (SILT FENCES, ETC.) TO PREVENT EROSION AND RUNOFF.

NOTES
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

NOTES

CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

ENVIROTECH ENGINEERING

2500 North Eleventh Street
Enid, Oklahoma 74801
580.234.8780
envirotechconsulting.com
P.E. #24553 - Expiration Date: 1-31-2023

COPYRIGHT



NO.	DATE	DESCRIPTION

CleanHarbors
ENVIRONMENTAL SERVICES INC.

NOTES
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

DATE: NOVEMBER 2025
SCALE: NOT TO SCALE
DESIGNED BY: J. IRBY
DRAWN BY: J. IRBY
CHECKED BY: T. WILLIAMS
PROJECT NO. 024330-00
SHEET NO. 4 OF 7

4 OF 7



ENVROTECH
ENGINEERING
2500 North Eleventh Street
Enid, Oklahoma •
501.234.8760 •
envirotechconsulting.com
P.E. #24553 - Expiration Date: 1-31-2025

COPYRIGHT
The document and information contained may NOT be reproduced or excerpted from without the express written permission of Envirotech Engineering and Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.

NO. DATE DESCRIPTION

CleanHarbors
ENVIRONMENTAL SERVICES, INC.




ENVIROTECH
ENGINEERING


2500 North Eleventh Street
Enid, Oklahoma •
580.234.8700 •
envirotechconsulting.com
P.E. #24533 - Expiration Date: 1-31-2025

COPYRIGHT
This document and the information contained may NOT be reproduced or excerpted from without the express written permission of EnviroTech Engineering and Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.


NO. DATE DESCRIPTION



SWA



SWC



ARCHITECTURAL PROFILES
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

DATE: NOVEMBER 2025
SCALE: NOT TO SCALE
DESIGNED BY: I. IRBY
DRAWN BY: I. IRBY
CHECKED BY: T. WILLIAMS
PROJECT NO. 024330-00
SHEET NO. 6 OF 7
11/25/2025 9:27:50 AM



ENVIROTECH
ENGINEERING
2500 1/2 East Fourth Street
Edmond, Oklahoma •
• 502.214.8700 •
envirotechconsulting.com
P.E. #24353 - Expiration Date: 1-31-2025

COPYRIGHT
This document and the information contained may NOT be reproduced or
exempted from without the express written permission of Envirotech Engineering and
Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited
by the copyright law.



NO. DATE DESCRIPTION




ARCHITECTURAL PROFILES
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

DATE: NOVEMBER 2025
SCALE: NOT TO SCALE
DESIGNED BY: J. IRBY
DRAWN BY: J. IRBY
CHECKED BY: T. WILLIAMS
PROJECT NO. 024330-00
SHEET NO. 7 OF 7
11/25/2025 9:28:01 AM

LOUVERS SIZE AND QUANTITY
TO BE SPECIFIED BY OTHERS



EWD



EWB



11/25/2025

7 OF 7



**Clean Harbors Environmental Services, LLC
Lone Mountain Facility
Waynoka, Oklahoma**

**Secondary Containment Design Report
for
Container Management Building Addition**

December 15, 2025



Farz R. Khan

12-15-2025

Table of Contents

1.0 Introduction	2
2.0 Container Management Building Addition Capacity	2
3.0 Requirement for the Base or Liner to Contain Liquids.....	2
4.0 Secondary Containment System Drainage	3
5.0 Secondary Containment System capacity	3
6.0 Control of Run-on	3
7.0 Removal of Liquid from Containment	4

List of Appendix

Appendix 1 – Containment Management Building Addition Capacity Calculations

List of Figures

Figure 1A – Container Management Building – Analytical Profile
Figure 1B - Inclination Angle of Wind Driven Rain
Figure 2 - Container Management Building –Plan View Section
Figure 3 – Container Management Building Cross- Sections
Figure 4 - Container Management Building -Trough/Trench Details
Figure 5 - Container Management Building – Rainfall Tributary Area
Figure 6 - Container Management Building Side View - North and South Side
Figure 7 - Container Management Building Side View - East and West Side

List of References

Reference 1: National Oceanic and Atmospheric Administration (NOAA) Atlas 14, Volume 8
Reference 2: Oklahoma Climatological Survey for Major County by Mesonet.
Reference 3: The speed of falling raindrop – The Physics Factbook.

1.0 Introduction

Clean Harbors Lone Mountain Facility, LLC (Clean Harbors) plans to permit Container Management Building Addition, which will be located immediately south of the existing Containment Management Building. The footprint and the storage capacity of the proposed Container Management Building Addition will be the same as that of the existing building. A Class 3, Tier 3 Permit Modification Request ("application") for Containment Management Building Addition was submitted to the Oklahoma Department of Environmental Quality (DEQ) on August 20, 2025.

Subsequently, on November 20, 2025, DEQ notified Clean Harbors that the Class 3 Permit application was found to be administratively complete and began conducting technical review of the application. As a part of the technical review, DEQ issued a Notice of Deficiency (NOD) and stated that a Secondary Containment capacity calculations for the proposed Container Management Building Addition must be submitted in accordance with 40 C.F.R. Part 264.175. This secondary containment design report contains the engineering analyses, detailed secondary containment capacity calculations, drawings, and supporting documentation (including references) for the Container Management Building addition.

It should be noted that the container storage management procedures (including off-loading, handling, transfer, inspection, sampling etc.) will be identical to that of the existing building. These procedures are described in detail in Volume 5 of the Lone Mountain Facility Permit Renewal document dated September, 2020.

2.0 Container Building Addition Capacity

The Container Management Building Addition can store a maximum capacity of 182,930 gallons of hazardous wastes, (equivalent to 3,326 55-gallon drums). This capacity is the same as that of the existing building capacity. A typical layout of the Container Management Building Addition is presented in Figure 2 (attached). Most of the containers in this proposed building are 55- gallon drums, 23 inches in diameter by 34 inches in height. The proposed building will handle approximately 1,000 containers of each flammable, solvent-based waste, acidic waste, and caustic waste. Approximately 300, 55-gallon drums may contain liquid reactive waste and lab packs.

These proportions may vary according to the daily fluctuations in the quantities received and stored at the facility. The Container Management Building includes a receiving dock, segregated storage areas, and storage/processing area. Assignment and transfer to the appropriate segregated storage or disposal area will occur in conjunction with waste characterization/analysis.

3.0 Requirement for the Base or Liner to Contain Liquids

The Container Management Building shall be constructed on a nominal eight (8) inch thick reinforced concrete pad over a compacted fill base. All concrete construction shall meet the design and construction standards specified in Americal Concrete Institute (ACI) Section ACI-318- 83, referred to as

“Reinforced Concrete Design” standards. The concrete compressive strength (after twenty-eight (28) days of curing) shall be three thousand (3000) psi or greater. The floor slab and containment walls shall be watertight, free of cracks or gaps¹. All joints shall contain continuous water-stop to prevent any migration of liquid outside the containment. The containment system is designed to contain accumulated liquid resulting from leaks, spills, and wind-driven rain and shall be removed expeditiously. Liquids accumulated in the secondary containment areas, sumps, or low points because of spills or leaks will be removed within 24 hours of discovery, while liquids resulting from precipitation only will be removed within 48 hours of discovery or when the precipitation event has ended.

Concrete containment shall be provided by an eight (8) inch minimum thick, and a minimum of six (6) inch high curb around the building perimeter except for the loading dock (east) side. Containment is achieved at the loading dock side by abruptly sloping the floor 2-inches as shown in Figure 1A. In addition, internal curbs shall be constructed to segregate the storage areas from each other. Concrete sealant(s)/hardener(s), compatible with the waste types to which it may be exposed, shall be applied to all concrete surfaces in the containment system sumps prior to placing the new building in operation (see Figure 4).

4.0 Secondary Containment System Drainage

The floor of the container receiving and storage areas of the Container Management Building Addition is sloped at a grade of approximately one eighth (1/8) inch per foot from the front and rear of the slot towards a drainage trough along the slot centerline. The drainage trough is a minimum of twenty-four (24) inches deep and slopes at approximately one quarter (1/4) inch per foot from one side of the slot towards the other side of the slot. A plan view and cross section of the Container Management Building Addition is presented in Figures 2 and 3, respectively.

5.0 Secondary Containment System Capacity

A summary of the Secondary containment capacity calculations for the different areas of the Container Management Building Addition is presented in Appendix 1. The secondary containment capacity calculations show that the available containment capacity is substantially more than the capacity required per 40 CFR 264.175 (b)(3) and 40 CFR 264.175 (b)(4). The covered storage areas minimize infiltration of rain or dispersion of waste by wind. Rainwater from the roof is brought to ground level by a system of roof drains. Site grading around the building diverts water away from the building. Walls, curbs, and elevated floors prevent the run-on of storm water into containment areas.

6.0 Control of Run On

The covered storage areas minimize infiltration of rain or dispersion of waste by wind. The east side of the building has a 25-foot canopy (overhang) where the loading dock is located. The canopy(overhang) will prevent wind driven rain from entering the containment area. The west, north and south side of the building is protected from rain by metal siding. However, the north side of the building is partially open

¹Cracks and gaps in the concrete surface will be corrected in a timely fashion. It is noted that superficial or insignificant cracks and gaps may occur in concrete surfaces which do not infringe upon secondary containment.



and subjected to wind driven rain. A very conservative estimate of the volume of rain entering the containment area from the north side is presented in Appendix 1. Rainwater from the roof is transported to ground level by a system of roof drains(downspouts). Positive site grading around the building diverts water away from the building. Walls, curbs, and elevated floors minimize run-on of storm water into the containment areas.

7.0 Removal of Liquids from Containment System

The slopes of the floors in the receiving and storage areas promote drainage toward troughs. Troughs will be inspected daily for the presence of liquids. Inspection schedules are discussed in detail in the facility permit Inspection Program. Liquids shall be removed by means of pumps or a vacuum tanker. The estimated volume of liquid removed, available analytical data, and disposal method shall be entered into the facilities Operating Record. The liquids shall be tested in accordance with the facilities Waste Analysis Plan.



LONE MOUNTAIN FACILITY
Container Management Building Addition
Class 3 Permit Modification
NOD Response
December 15, 2025

APPENDIX 1

CONTAINER MANAGEMENT BUILDING ADDITION SECONDARY CONTAINMENT CAPACITY CALCULATIONS

PROBLEM: Calculate the secondary containment Capacity of Container Management Building Additions.

REGULATORY CRITERIA (40 CFR Part 264.175): Secondary containment must be able to store storm water resulting from a 25-year, 24-hour storm event plus the volume of the largest tank or 10% of the total volume, whichever is larger.

GIVEN:

- 25-year, 24-hour storm event = 5.85 inches (Per attached NOAA Atlas 14)
- Building Size: 150.0 feet by 172.0 feet,
- Height of Curb above Floor = 2.0 inches (minimum),
- Trough width: 2.0', Depth = 2.25' (average)
- Volume of the Largest Container (Totes) = 350 Gallons
- Total Permitted Capacity = 182,930 Gallons.
- Prevailing wind direction is towards north in Major County, Oklahoma (Per OK Climatological Survey)

ASSUMPTIONS: a) All drums are placed on the floor. Maximum Number of Drum on the floor = 1480 (Conservative -worst case assumptions). Deduction for volume occupied by 1480 drums from gross secondary containment capacity will be considered.

FACTOR OF SAFETY AND BASIS: Net available capacity must exceed the required storage capacity in accordance with 40CFR Part 264.175 for container storage area.

SOLUTION:

The gross available secondary containment capacity is the summation of $V_1 + V_2 + V_3$ where,

V_1 = Volume of rectangular prism with a minimum 2-inch-high perimeter curb/slope.

V_2 = Volume of triangular Prism due to sloping floor

V_3 = Volume of square prism for trough/trench




FIGURE 1A - ANALYTICAL PROFILE

Treatment Building Containment Calculations

Volume Calculations - See Figures 1A and 2

Notation	DETERMINE AVAILABLE VOLUME (ft ³)		
V1	Volume 1 (V1) of Rect. Prism	Measurements	Unit
	L (Length)=	170.67	ft
	W (Width)=	149.84	ft
	D (Depth)=	0.167	ft
	Volume =	4270.7	ft ³
V2A	Volume 2 (V2A) - Triangular Prism(Receiving Area)		
	L =	170.67	ft
	W =	49.17	ft
	D ₁ =	0.33	ft
	Volume =	1397.2	ft ³
V2B	Volume 2 (V2B) - Triangular Prism (Storage Area)		
	L =	170.67	ft
	W =	88.00	ft
	D ₁ =	0.50	ft
	Volume =	3754.7	ft ³
V3	Volume 3 (V3) Square Prism (Trough/Trench)		
	L (total length) =	335.3	ft
	W =	2.00	ft
	D ₁ (Average Depth of Trough)	2.25	ft
	Volume =	1,509.0	ft ³
	Gross Volume of Containment =	10931.6	ft³

Calculate Volume Displaced by Internal Curbs

C1	Displaced Volume (East-West Curb)		
	L(east-west) – Sum of 6 Curbs	528.0	ft
	W =	1.00	ft
	D (average depth)	0.33	ft
	Displaced Volume (East-West)	174.2	ft ³
C2	Displaced Volume (N-S rollover Curb)		
	L (North-South-sum of 2 curbs)	298.0	ft
	W =	2.00	ft
	D (average depth)	0.170	ft
	Displaced Volume (East-West)	101.3	ft ³
	Total Displaced Volume- Curb	275.5	ft³

D1	Calculate Volume Displaced by Drums		
	Drum Diameter	1.92 feet	ft
	Area of Drum	2.89	ft ²
	Avg. Drum height below containment	0.40	ft
	Max. Number of Drums (bottom Row)	1480	
	Total Displaced Volume (Drum)	1,710.9	ft ³

Net Available Volume = $V1+V2A+V2B+V3-C1-C2 -D1$	8945.2	ft³
--	---------------	-----------------------

Calculate Required Containment Storage Capacity Due to Added Containers

1) EPA 40CFR Part 264.175(b)(3) – Capacity Increase

The containment system must have sufficient capacity to contain 10% of the volume of containers or the volume of the largest container, whichever is greater. Container Management Building Addition Capacity = 182,930 Gallons

10% of total capacity = 18,293 gallons = 2,446 ft³

Volume of the largest Container = 350 gallons

Required Containment System Capacity = 2,446 ft³ (governs per 40CFR Part 265.175(b)(3)).

Calculate Required Containment Storage Capacity Due to Run-On (40CFR Part 264.175(b)(4))

2) EPA 40 CFR Part 264.175(b)(4) - Run-on into Containment System

The proposed Container Management Building has the following enclosure/siding:

- East side of the building at Loading Dock: Protected from rain by a 25-feet Canopy/overhang
- West side of the building: Metal siding.
- South Side of the building: Metal siding; and
- North Side of the building: Partial metal siding.

Therefore, run-on into Containment System from wind driven rain is not possible **except for the partial opening on the North side of the building (see attached Figures 6 and 7).**

2a) Calculate the volume of run-on from the North side of the building

The prevailing wind for the Major County, Oklahoma generally comes from the south (see attached reference) where building is protected from wind driven rain by metal siding. The north side of the building is partially open as shown in Figure 6. The proximity of the **existing** container management building located on the north side will obstruct majority of wind driven rain falling into north-east side of the new building. A strong wind of 30 mph (sustaining for a duration of 24-hour) is assumed as a very conservative estimate for the purpose of calculating the volume of wind driven rain into the containment area.

Wind driven rain entering the containment from the north side will be dependent on the size, the speed of the raindrops, wind speed and wind directions. Terminal velocity of rain drop can be calculated using fluid mechanics formula given the diameter of the raindrops. A large raindrop has a diameter of 6 mm(see attached reference). The terminal velocity of a 6 mm diameter raindrop is between 9 to 10 meters per second (20 to 22 mph).

Design Rainfall Amount = 5.85 inches = 0.49 inches (Per attached NOAA Atlas 14)

Windspeed = 30 MPH

Terminal velocity of raindrops = 22 MPH

Determine the inclination angle(α) raindrops make with vertical direction during wind driven rain :




Figure 1B – Inclination Angle of Wind Driven Rain

Inclination Angle (α)= $\text{Arctan} (30/22) = 53.7^\circ$.

Height of North Side Opening = 8 feet (given)

Wind Driven Run-on Distance inside the Building = $8' \tan 53.7^\circ = 10.9 \text{ feet} \approx 11 \text{ feet}$

Tributary Area of Wind Driven Rain = $0.5 \times 150' \times 11 \text{ feet} = 825 \text{ ft}^2$ (assuming triangular distribution)

Volume of wind driven rain = $825 \times 0.49 \times 1 = 404.3 \text{ ft}^3$

Total Required Capacity = 10% of total container capacity + Wind Driven Rain Volume

Required Capacity = $2,446 + 404.3 = 2,850.3 \text{ ft}^3$

Total Available Capacity ($8,945.2 \text{ ft}^3$) is greater than Required Capacity = $2,850.3 \text{ ft}^3$


Factor of Safety = Available Capacity/Required Capacity = $8945.2/2850.3 = 3.1 \text{ OK}$

Conclusion: A secondary containment for the proposed Container Building Addition as designed will provide sufficient containment capacity to store storm water resulting from a 25-year, 24-hour storm event plus the volume of the largest tank. Therefore, the proposed secondary containment system meets the requirement of 40 C.F.R. Part 264.175.




LONE MOUNTAIN FACILITY
Container Management Building Addition
Class 3 Permit Modification
NOD Response
December 15, 2025

FIGURES




NOTE: THIS DRAWING IS PREPARED FOR SECONDARY CONTAINMENT CALCULATION ONLY

Clean Harbors Lone Mountain Facility
Figure 2.
Plan View – Container Management Building Addition



SECTION ACROSS TROUGHS



SECTION ALONG TROUGH

Figure 3


BY	DATE
DRAWN WRB	3/6/98
CHECKED PRK	12/15/25
APPROVED	
APPROVED	
APPROVED	
REVIEWED KMC	9/4/09



LONE MOUNTAIN FACILITY



FIGURE 2-3
CONTAINER MANAGEMENT BUILDING Addition

SCALE: NOT TO SCALE DWG. NO.: 792441-0017 REV. B



Clean Harbors Lone Mountain Facility
Figure 4

Proposed Container Management Building Addition
Collection Trough Cross-Section



**ENVIROTECH
ENGINEERING**
2500 North Eleventh Street
Enid, Oklahoma • 501.234.0700 • envirotechconsulting.com
P.E. #24553 - Expiration Date: 1-1-2025

C O P Y R I G H T
The document and the information contained may NOT be reproduced or excerpted without the express written permission of Envirotech Engineering and Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.


NO. DATE DESCRIPTION

CleanHarbors
ENVIRONMENTAL SERVICES, INC.


ADJOINING STRUCTURE DIMENSIONS
CONTAINER MANAGEMENT BUILDING
LONE MOUNTAIN FACILITY
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN
MAJOR COUNTY, OKLAHOMA

DATE: DECEMBER 2025
SCALE: 1"=20'
DESIGNED BY: I. IRBY
DRAWN BY: I. IRBY
CHECKED BY: T. WILLIAMS
PROJECT NO. 024330-00
SHEET NO. 5 OF 7





SWA (NORTH SIDE OF BUILDING - LOOKING SOUTH)




SWC (SOUTH SIDE OF BUILDING - LOOKING NORTH)


LICENSED PROFESSIONAL ENGINEER
TYLER WILLIAMS
26476
OKLAHOMA
12/15/2025

ENVIROTECH ENGINEERING	2500 North Fluvanna Street Enid, Oklahoma • 501.234.8780 envirotechconsulting.com P.E. #24553 - Expiration Date: 1-31-2025
COPYRIGHT	
This document and the information contained herein may NOT be reproduced or excerpted in whole or in part without the permission of Envirotech Engineering and Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.	
NO. DATE DESCRIPTION	
 CleanHarbors ENVIRONMENTAL SERVICES, INC.	
ARCHITECTURAL PROFILES	
CONTAINER MANAGEMENT BUILDING	
LONE MOUNTAIN FACILITY	
SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN MAJOR COUNTY, OKLAHOMA	
DATE:	DECEMBER 2025
SCALE:	NOT TO SCALE
DESIGNED BY:	I. IRBY
DRAWN BY:	I. IRBY
CHECKED BY:	T. WILLIAMS
PROJECT NO.	024330-00
SHEET NO.	6 OF 7


12/15/2025 3:11:59 PM
X:\Projects\2024\024330-00\00 CleanHarbors Lone Mountain Container Management Building Geotech, Survey, & Design\CAD\Sheets\Site Min CMB Site Design Ch1 Coordinates 1219-24 Midwg



EWD (WEST SIDE OF BUILDING - LOOKING EAST)



EWB (EAST SIDE OF BUILDING - LOOKING WEST)



ENVIROTECH ENGINEERING <small>2300 North Cleveland Street Enid, Oklahoma • 501.234.8700 envirotechconsulting.com P.E. #24553 - Expiration Date: 1-31-2025</small>					
COPYRIGHT <small>This document and the information contained herein NOT be reproduced or excerpted from without the express written permission of EnviroTech Engineering and Consulting, Inc. Unauthorized copying, disclosure or construction use are prohibited by the copyright law.</small>					
<table border="1"> <tr> <td>NO.</td> <td>DATE</td> <td>DESCRIPTION</td> </tr> </table>			NO.	DATE	DESCRIPTION
NO.	DATE	DESCRIPTION			
ARCHITECTURAL PROFILES CONTAINER MANAGEMENT BUILDING LONE MOUNTAIN FACILITY <small>SECTION 33, TOWNSHIP 23 NORTH, RANGE 15 WEST, INDIAN MERIDIAN MAJOR COUNTY, OKLAHOMA</small>					
<small>12/15/2025 3:12:09 PM X:\Projects\2024\24339-00-000 CleanHarbors Lone Mountain Container Management Building Geotech, Survey, & Design\CAD\Sheets\Stone Min CMX Site Design CH1 Coordinates 12.19.24 Mid.Dwg</small>					
DATE:	DECEMBER 2025				
SCALE:	NOT TO SCALE				
DESIGNED BY:	I. IRBY				
DRAWN BY:	I. IRBY				
CHECKED BY:	T. WILLIAMS				
PROJECT NO.	024330-00				
SHEET NO.	7 OF 7				



References 1



NOAA Atlas 14, Volume 8, Version 2
Location name: Waynoka, Oklahoma, USA*
Latitude: 36.4286°, Longitude: -98.8042°
Elevation: 1418 ft**
 * source: ESRI Maps
 ** source: USGS



POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Deborah Martin, Sandra Pavlovic, Ishani Roy, Michael St. Laurent, Carl Trypaluk, Dale Unruh, Michael Yekta, Geoffery Bonnin

NOAA, National Weather Service, Silver Spring, Maryland

[PF tabular](#) | [PF graphical](#) | [Maps & aerials](#)

PF tabular

Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.379 (0.312-0.462)	0.453 (0.373-0.552)	0.574 (0.470-0.700)	0.672 (0.547-0.824)	0.805 (0.629-1.01)	0.906 (0.691-1.16)	1.00 (0.739-1.31)	1.10 (0.777-1.48)	1.23 (0.832-1.70)	1.33 (0.874-1.86)
10-min	0.555 (0.457-0.676)	0.664 (0.546-0.809)	0.840 (0.688-1.03)	0.984 (0.800-1.21)	1.18 (0.921-1.48)	1.33 (1.01-1.69)	1.47 (1.08-1.92)	1.62 (1.14-2.17)	1.81 (1.22-2.49)	1.95 (1.28-2.73)
15-min	0.677 (0.557-0.824)	0.810 (0.666-0.987)	1.02 (0.839-1.25)	1.20 (0.976-1.47)	1.44 (1.12-1.81)	1.62 (1.23-2.06)	1.80 (1.32-2.34)	1.97 (1.39-2.64)	2.20 (1.49-3.03)	2.38 (1.56-3.33)
30-min	0.967 (0.796-1.18)	1.16 (0.953-1.41)	1.47 (1.20-1.80)	1.73 (1.40-2.12)	2.07 (1.62-2.60)	2.33 (1.78-2.97)	2.59 (1.90-3.38)	2.84 (2.00-3.81)	3.18 (2.14-4.37)	3.42 (2.25-4.79)
60-min	1.25 (1.03-1.52)	1.51 (1.24-1.84)	1.92 (1.58-2.35)	2.26 (1.84-2.78)	2.73 (2.13-3.43)	3.08 (2.35-3.92)	3.42 (2.51-4.46)	3.76 (2.64-5.04)	4.21 (2.84-5.79)	4.54 (2.98-6.35)
2-hr	1.53 (1.27-1.85)	1.85 (1.53-2.24)	2.38 (1.96-2.88)	2.80 (2.30-3.41)	3.38 (2.66-4.22)	3.82 (2.93-4.84)	4.25 (3.15-5.51)	4.68 (3.31-6.23)	5.24 (3.56-7.16)	5.65 (3.74-7.86)
3-hr	1.69 (1.41-2.04)	2.06 (1.71-2.47)	2.64 (2.19-3.19)	3.13 (2.57-3.79)	3.78 (2.99-4.71)	4.29 (3.31-5.41)	4.79 (3.56-6.18)	5.29 (3.76-7.01)	5.94 (4.05-8.09)	6.43 (4.28-8.91)
6-hr	2.00 (1.68-2.39)	2.41 (2.01-2.88)	3.09 (2.57-3.70)	3.66 (3.03-4.40)	4.46 (3.56-5.55)	5.10 (3.97-6.41)	5.74 (4.31-7.40)	6.41 (4.60-8.47)	7.30 (5.03-9.91)	8.00 (5.35-11.0)
12-hr	2.35 (1.98-2.79)	2.78 (2.34-3.29)	3.52 (2.95-4.18)	4.17 (3.48-4.98)	5.13 (4.15-6.38)	5.92 (4.66-7.44)	6.75 (5.12-8.67)	7.63 (5.53-10.1)	8.86 (6.16-12.0)	9.84 (6.64-13.4)
24-hr	2.72 (2.31-3.20)	3.18 (2.69-3.74)	4.00 (3.37-4.71)	4.74 (3.97-5.61)	5.85 (4.78-7.25)	6.79 (5.39-8.49)	7.78 (5.95-9.96)	8.86 (6.48-11.6)	10.4 (7.29-14.0)	11.6 (7.90-15.8)
2-day	3.10 (2.64-3.61)	3.62 (3.08-4.22)	4.53 (3.85-5.30)	5.36 (4.53-6.30)	6.61 (5.43-8.11)	7.65 (6.11-9.49)	8.76 (6.74-11.1)	9.95 (7.33-13.0)	11.6 (8.22-15.6)	13.0 (8.90-17.5)
3-day	3.37 (2.88-3.91)	3.90 (3.34-4.52)	4.84 (4.13-5.63)	5.69 (4.82-6.66)	6.98 (5.76-8.53)	8.05 (6.46-9.94)	9.20 (7.11-11.6)	10.4 (7.72-13.5)	12.2 (8.66-16.2)	13.6 (9.36-18.3)
4-day	3.59 (3.08-4.15)	4.13 (3.54-4.78)	5.10 (4.36-5.91)	5.97 (5.08-6.96)	7.28 (6.02-8.86)	8.38 (6.74-10.3)	9.55 (7.40-12.0)	10.8 (8.02-14.0)	12.6 (8.96-16.7)	14.0 (9.67-18.8)

7-day	4.12 (3.56-4.74)	4.75 (4.10-5.46)	5.83 (5.02-6.72)	6.79 (5.80-7.86)	8.18 (6.78-9.84)	9.32 (7.52-11.4)	10.5 (8.18-13.1)	11.8 (8.78-15.1)	13.5 (9.68-17.8)	15.0 (10.4-19.9)
10-day	4.62 (4.01-5.29)	5.32 (4.60-6.09)	6.49 (5.60-7.45)	7.50 (6.43-8.64)	8.95 (7.43-10.7)	10.1 (8.18-12.2)	11.3 (8.83-14.0)	12.6 (9.39-16.0)	14.3 (10.3-18.7)	15.7 (10.9-20.8)
20-day	6.13 (5.35-6.95)	6.94 (6.05-7.88)	8.28 (7.20-9.43)	9.41 (8.13-10.8)	11.0 (9.16-12.9)	12.2 (9.94-14.6)	13.4 (10.6-16.5)	14.7 (11.1-18.5)	16.4 (11.8-21.2)	17.7 (12.4-23.3)
30-day	7.34 (6.43-8.28)	8.28 (7.24-9.35)	9.80 (8.55-11.1)	11.1 (9.60-12.6)	12.8 (10.7-15.0)	14.1 (11.5-16.8)	15.5 (12.2-18.8)	16.8 (12.7-21.0)	18.6 (13.4-23.9)	19.9 (14.0-26.0)
45-day	8.79 (7.74-9.88)	9.94 (8.74-11.2)	11.8 (10.3-13.3)	13.3 (11.6-15.1)	15.3 (12.8-17.8)	16.9 (13.8-19.9)	18.4 (14.5-22.2)	19.9 (15.0-24.7)	21.8 (15.8-27.9)	23.2 (16.4-30.3)
60-day	9.97 (8.80-11.2)	11.3 (10.0-12.7)	13.5 (11.9-15.2)	15.3 (13.4-17.3)	17.7 (14.8-20.4)	19.4 (15.9-22.8)	21.1 (16.7-25.4)	22.8 (17.3-28.2)	24.9 (18.1-31.8)	26.5 (18.8-34.4)

¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).


Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.


[Back to Top](#)

PF graphical

PDS-based depth-duration-frequency (DDF) curves
Latitude: 36.4286°, Longitude: -98.8042°



Average recurrence interval (years)
1
2
5
10
25
50
100
200
500
1000



Duration	
5-min	2-day
10-min	3-day
15-min	4-day
30-min	7-day
60-min	10-day
2-hr	10-day
3-hr	20-day
6-hr	30-day
12-hr	45-day
24-hr	60-day


Average recurrence interval (years)

NOAA Atlas 14, Volume 8, Version 2

Created (GMT): Mon Dec 1 20:31:05 2025

[Back to Top](#)

Maps & aerials



Lone Mountain Facility
40355 South County Road 236
Waynoka, OK 73860



Large scale map



Large scale aerial



[Back to Top](#)

[US Department of Commerce](#)
[National Oceanic and Atmospheric Administration](#)
[National Weather Service](#)
[National Water Center](#)
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC.Questions@noaa.gov

[Disclaimer](#)

Reference 2

MAJOR COUNTY

CLIMATE SUMMARY

AVERAGES

TEMPERATURE (°F)														
	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	
DAILY AVG	37.4	40.3	49.5	58.6	68.7	78.7	83.1	81.3	73.5	60.9	48.2	38.6	59.9	
DAILY MIN	25.9	28.0	37.2	45.8	56.6	66.5	70.7	69.5	61.2	48.4	36.5	27.8	47.8	
DAILY MAX	48.9	52.6	61.9	71.4	80.8	90.9	95.5	93.1	85.8	73.5	59.9	49.4	72.0	

Annual number of days max temperature is greater than 90°F: 90
Annual number of days max temperature is greater than 100°F: 25
Annual number of days max temperature is less than 32°F: 11
Annual number of days min temperature is less than 32°F: 89
Annual number of heating degree days (HDD): 3868
Annual number of cooling degree days (CDD): 2049
Annual length of growing season: 208 days
Date of first fall freeze: November 1
Date of last spring freeze: April 5

PRECIPITATION														
	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	
AMOUNT (in.)	1.03	1.22	2.19	3.56	4.33	4.72	4.47	3.17	2.89	2.88	1.58	1.50	33.54	
NUMBER OF DAYS WITH RAIN	1.9	3.4	4.0	5.8	6.7	5.4	5.2	6.1	4.6	4.1	2.3	2.0	51.5	

Annual snowfall: 8.2 in.
Annual percent sunshine (2006-2020): 69%
Annual number of thunderstorm days (1901-1995): 50
Annual number of hail (>1 in.) days (1986-2015): 5+
Annual number of tornadoes (1950-2021): 0.67
Total number of tornadoes (1950-2021): 48

Notes:

- 1.) Average first and last freeze dates are based on the 50th probability percentile.
- 2.) Unless noted, averages/ normals are based on the 1991-2020 period.



OKLAHOMA
CLIMATOLOGICAL SURVEY



Mesonet
Oklahoma's Weather Network

RECORDS & EXTREMES

Record high temperature: 114°F (August 6, 1964)

Record low temperature: -15°F (February 10, 2011)

Earliest freeze date: October 19

Latest freeze date: April 20

Wettest year: 54.32 in. (1957)

Driest year: 17.55 in. (1968)

Greatest daily rainfall: 9.13 in. (September 12, 2008)

Greatest seasonal snowfall (Sep - Apr): 25.0 in. (1968-1969; 1987-1988; 1992-1993)

Greatest daily snowfall: 11.2 in. (February 26, 2013)

Note: Extreme earliest and latest freeze dates are based on the 10th probability percentile.


HOLIDAY STATS

	Avg Max Temp (°F)	Avg Min Temp (°F)	Record High (°F)	Record Low (°F)
NEW YEAR'S EVE, December 31	49	26	78 (1951)	0 (1968)
VALENTINE'S DAY, February 14	53	29	82 (1954)	12 (1949)
INDEPENDENCE DAY, July 4	94	68	105 (1954)	58 (1940)
HALLOWEEN, October 31	68	44	88 (1947)	28 (1949)
CHRISTMAS, December 25	51	29	78 (1955)	9 (1952)


WIND

Average wind speed: 11 mph

Wind Roses: Wind roses show the prevailing direction from which the wind is blowing. North is up in the image. The circles show the percentage of time from which the wind is blowing in that direction, as well as the percentage of time for different wind speed ranges. The wind speed ranges are represented by different shades of color. For example, Fairview records a south wind about 15% of the time, with winds blowing between 10 and 15 mph about 5% (11%-6%=5%) of the time from that direction. The table below shows the percentage of time the wind is blowing from each of the 16-point compass headings, and the percent of time the prevailing wind is recorded in each speed bin.



Legend: Estimated trajectory of wind driven rain towards south and south-east direction.



Oklahoma Climatological Survey:

climate.ok.gov

Oklahoma Mesonet:

mesonet.org

120 David L. Boren Blvd., Suite 2900

Norman, OK 73072

phone: 405.325.2541

fax: 405.325.7282

Reference 3

Speed of a Falling Raindrop

An educational, fair use website

Bibliographic Entry	Result (w/surrounding text)	Standardized Result
Corbert, John H. <i>Physical Geography Manual</i> . 1974. 5th ed. N.p.: Kendall/Hunt, 2003. 127.	"A large drop of about 5 mm (3/16 in.) diameter reaches a maximum speed of about 9 m/sec."	9 m/s
"Climate." <i>Encyclopedia Britannica</i> . 2007, Encyclopedia Britannica Online. 25 May 2007.	"Large raindrops, up to six millimeters in diameter, have terminal velocities of about 10 metres per second and so may cause considerable compaction and erosion of the soil by their force of impact."	10 m/s
Beard, K.V. Terminal Velocity and Shape of Cloud and Precipitation Drops [pdf] . <i>Journal of the Atmospheric Sciences</i> (May 1976): 851-864.	[see graph 1 below]	9-13 m/s
Spilhaus, A.F. Raindrop Size, Shape, and Falling Speed [pdf] . <i>Journal of Meteorology</i> . 5 (June 1948): 108-110.	[see graph 2 below]	9.3 m/s
Holladay, April. Falling raindrops hit 5 to 20 mph speeds . Wonderquest. Albuquerque: 19 Dec 2001.	"At sea level, a large raindrop about 5 millimeters across (housefly size) falls at the rate of 9 meters per second (20 miles per hour). Drizzle drops (less than 0.5 mm across, i.e., salt-grain size) fall at 2 meters per second (4.5 mph)."	9 m/s

22 MPH




FIG. 3. Terminal velocity of raindrops at five pressure levels in a normal atmosphere as a function of the equivalent spherical diameter. Also shown is the standard curve for sea level.

Graph 1




FIG. 4. Variation of the terminal fall speed, v , with radius of the raindrop, r . Experimental values shown by crosses, theory by full line.

Graph 2

Rain is the liquid form of precipitation on Earth. It is part of the hydrologic cycle that begins when water evaporates and forms clouds in the atmosphere. The water that forms these clouds is frozen and vaporized. Once enough water has evaporated, it is then released in the form of droplets of rain back to the surface of the Earth.

The average size of a raindrop is 6 millimeters in diameter, about the size of a housefly. Of course all raindrops vary in size due to the strength of a specific rainstorm, but this is considered a reasonable value of a typical raindrop. When a raindrop falls to the surface of the Earth, it is acted on by two main forces, gravity and drag. A stationary raindrop initially experiences an acceleration due to gravity of 9.8 m/s^2 , as would any falling body. As gravity increases the speed of the raindrop in its descent, drag retards the downward acceleration of the raindrop. Usually,

air resistance that comes in contact with the water molecules as they fall causes the drag. The combination of these two forces causes a raindrop to reach a terminal velocity when the drag force is approximately equal to the weight of the raindrop. At this point, a raindrop experiences no further acceleration and therefore falls at a constant velocity.

The magnitude of the terminal velocity of an object is also affected by its orientation. A common misconception is the shape of the raindrop. It is often depicted as pointy and lopsided. However, research has found the shape of a raindrop to be rather spherical or slightly flattened on the bottom by airflow like a hamburger bun.

The terminal velocity of a 6-millimeter raindrop was found to be approximately 10 m/s. This value has been found to vary between 9 m/s and 13 m/s when measurements were taken on different days. The variance has been contributed to different air temperatures and pressures. In comparison, a human being falling to the surface of the Earth experiences a drastically larger terminal velocity of approximately 56 m/s.

Evan Kaplan -- 2007

External links to this page:

- [How Fast Is Falling Rain?](#) Rhett Allain. *Wired*. 29 August 2011.
- [Estimating rainfall precipitation amounts by applying computer vision in cameras](#). Renato F. Cerqueira, Kiran Mantripragada, International Business Machines Corp. Patent [US9436997](#) and [US9582730](#) (2016, 2017).
- [Important Parameters for the Characterization of Rain as an Energy Source](#). Nathan Dalton, Ben King, Chelsea Saucedo, Thomas M. Adams. *Proceedings of the 10th World Congress on Mechanical, Chemical, and Material Engineering* (MCM'24). Barcelona, Spain (22–24 August 2024).
- [Simulation of the Rough Network Structure of Plant Leaves in Multiple Loading Cases](#). Liu Wang Yu, Liu Xi Feng. *Science Technology and Engineering*. Vol. 9 No. 23 (2009).



The Physics Factbook
Edited by Glenn Elert
Written by his students