

# ***SECTION 10 – School Buses***

---

- **Danger Zones and Use of Mirrors**
- **Loading and Unloading**
- **Emergency Exit and Evacuation**
- **Railroad-Highway Crossings**
- **Student Management**
- **Antilock Braking Systems**
- **Special Safety Considerations**



*This section is for drivers who will be driving school buses.*



## SECTION 10: School Buses

### *This Section Covers:*

- Danger Zones and Use of Mirrors
- Loading and Unloading
- Emergency Exit and Evacuation
- Railroad-Highway Grade Crossings
- Student Management
- Antilock Braking Systems
- Special Safety Situation

School bus drivers must have a commercial driver's license if they drive a vehicle designed to transport (seat) 16 or more persons, including the driver.

School bus drivers must have a school bus endorsement in addition to a passenger endorsement on their commercial driver's license (CDL). To get the school bus endorsement, you must pass a knowledge test on sections 2, 4, and 10 of this manual. (If your school bus has air brakes, you must also pass a knowledge test on Section 5.) You must also pass the skills test required for the class of school bus you drive or intend to drive.

This section does NOT provide information on all the federal and state requirements needed before you drive a school bus. You should be thoroughly familiar with all specific school bus procedures, laws, and regulations in your state and local school district.

State law requires school bus drivers to attend a 25-hour school bus driver workshop prior to operating a school bus in addition to obtaining a school bus endorsement. Contact your local school district transportation office for more information regarding the workshop.

## 10.1 Danger Zones and Use of Mirrors


### 10.1.1 - Danger Zones

The danger zone is the area anywhere outside of the bus where children are in the most danger of being hit, either by another vehicle or their own bus. The danger zones extend as much as 30 feet from the front bumper, 10 feet from the left and right sides of the bus and 10 feet behind the rear bumper of the school bus. In addition, the area to the left of the bus is always considered dangerous because of passing vehicles. Figure 10.01 illustrates these danger zones.

### 10.1.2 - Correct Mirror Adjustment

Proper adjustment and use of all mirrors is vital to the safe operation of the school bus. Use mirrors to observe the danger zone

around the bus and look for students, traffic, and other objects in this area. You should always check each mirror before operating the school bus to obtain the maximum viewing area consistent with the vision requirements of Federal Motor Vehicle Safety Standard No. 111, "Mirror Systems." If necessary, have the mirrors adjusted.



### 10.1.3 - Outside Left and Right Side Flat Mirrors


These mirrors are mounted at the left and right front corners of the bus at the side or front of the windshield. They are used to monitor traffic and check clearances and students on the sides and to the rear of the bus. There is a blind spot immediately below and in front of each mirror and directly in back of the rear bumper. The blind spot behind the bus could extend up to 400 feet depending on the width of the bus.

Ensure that the mirrors are properly adjusted so you can see:

- *200 feet or four bus lengths behind the bus*
- *Along the sides of the bus*
- *The rear tires touching the ground*

## 10.1 Danger Zones and Use of Mirrors (continued)

Figure 10.02 shows how both the outside left and right side flat mirrors should be adjusted.




### 10.1.4 - Outside Left and Right Side Convex Mirrors

The convex mirrors are located below the outside flat mirrors. They are used to monitor the left and right sides at a wide angle. They provide a view of traffic, clearances, and students at the side of the bus. These mirrors present a view of people and objects that does not accurately reflect their size and distance from the bus.

Ensure that the mirrors are properly adjusted so you can see:

- The entire side of the bus up to the mirror mounts
- Front of the rear tires touching the ground
- At least one traffic lane on either side of the bus

Figure 10.03 shows how both the outside left and right side convex mirrors should be adjusted.




### 10.1.5 - Outside Left and Right Side Cross View Mirrors

These mirrors are mounted on both left and right front corners of the bus. They are used to see the “danger zone” area directly in front of the bus that is not visible by direct vision and to view the “danger zone” areas to the left side and right side of the bus, including the service door and front wheel areas. The mirror presents a view of people and objects that does not accurately reflect their size and distance from the bus. The driver must ensure that these mirrors are properly adjusted.

Ensure that the mirrors are properly adjusted so you can see:

- The entire area in front of the bus from the front bumper at ground level to a point where direct vision is possible. Direct vision and mirror view vision should overlap.
- The right and left front tires touching the ground.
- The area from the front of the bus to the service door.
- These mirrors, along with the convex and flat mirrors, should be viewed in a logical sequence to ensure that a child or object is not in any of the danger zones.

Figures 10.04a and 10.04b illustrate how the left and right side cross-view mirrors should be adjusted.



### 10.1.6 - Overhead Inside Rearview Mirror

This mirror is mounted directly above the windshield on the driver's side area of the bus. This mirror is used to monitor passenger activity inside the bus. It may provide limited visibility directly in back of the bus if the bus is equipped with a glass-bottomed rear emergency door. There is a blind spot area directly behind the driver's seat as well as a large blind spot area that begins at the rear bumper and could extend up to 400 feet or more behind the bus. You must use the exterior side mirrors to monitor traffic that approaches and enters this area.

Ensure that the mirrors are properly adjusted so you can see:

- *The top of the rear window in the top of the mirror.*
- *All of the students, including the heads of the students right behind you.*

## 10.2 Loading and Unloading

More students are killed while getting on or off a school bus each year than are killed as passengers inside of a school bus. As a result, knowing what to do before, during, and after loading or unloading students is critical. This section will give you procedures to help you avoid unsafe conditions which could result in injuries and fatalities during and after loading and unloading students.

### 10.2.1 - Approaching the Stop

Each school district establishes official routes and official school bus stops. All stops should be approved by the school district prior to making the stop. You should never change the location of a bus stop without written approval from the appropriate school district official.

You must use extreme caution when approaching a school bus stop. You are in a very demanding situation when entering these areas. It is critical that you understand and follow all state and local laws and regulations regarding approaching a school bus stop. This would involve the proper use of mirrors, alternating flashing lamps, and when equipped, the moveable stop signal arm and crossing control arm.

When approaching the stop, you should:

- *Approach cautiously at a slow rate of speed.*
- *Look for pedestrians, traffic, or other objects before, during, and after coming to a stop.*
- *Continuously check all mirrors.*
- *If the school bus is so equipped, activate alternating flashing amber warning lamps 300 to 100 feet before the school bus stop.*
- *Continuously check mirrors to monitor the danger zones for students, traffic, and other objects.*
- *Move as far as possible to the right on the traveled portion of the roadway.*
- *Bring school bus to a full stop with the front bumper at least 10 feet away from students at the designated stop. This forces the students to walk to the bus so you have a better view of their movements.*
- *Set the parking brake, place the transmission in park, or if there is no Park shift point, place the transmission in Neutral at each stop.*
- *Open service door, if possible, enough to activate alternating red lamps when traffic is a safe distance from the school bus.*
- *Make a final check to see that all traffic has stopped before completely opening the door and signaling students to approach.*

### 10.2.2 - Loading Procedures

- *Perform a safe stop as described in subsection 10.2.1.*
- *Students should wait in a designated location for the school bus, facing the bus as it approaches.*
- *Students should board the bus only when signaled by the driver.*
- *Monitor all mirrors continuously.*
- *Count the number of students at the bus stop and be sure all board the bus. If possible, know names of students at each stop. If there is a student missing, ask the other students where the student is.*

## 10.2 Loading and Unloading (continued)

- *Have the students board the school bus slowly, in single file, and use the handrail. The dome light should be on while loading in the dark.*
  - *Wait until students are seated and facing forward before moving the bus.*
  - *Check all mirrors. Make certain no one is running to catch the bus.*
  - *If you cannot account for a student outside, secure the bus, take the key, and check around and underneath the bus.*
  - *When all students are accounted for, prepare to leave by:*
    - ✧ Closing the door.
    - ✧ Engaging the transmission.
    - ✧ Releasing the parking brake.
    - ✧ Turning on left turn signal.
    - ✧ Allowing congested traffic to disperse.
    - ✧ Checking all mirrors again.
  - *When it is safe, move the bus to enter traffic flow and continue the route.*
- *If you cannot account for a student outside the bus, secure the bus, and check around and underneath the bus.*
  - *When all students are accounted for, prepare to leave by:*
    - ✧ Closing the door.
    - ✧ Engaging transmission.
    - ✧ Releasing parking brake.
    - ✧ Turning on left turn signal.
    - ✧ Allowing congested traffic to disperse.
    - ✧ Checking all mirrors again.
  - *When it is safe, move the bus, enter the traffic flow and continue the route.*

**Note.** If you have missed a student's unloading stop, do not back up. Be sure to follow local procedures.

### Additional Procedures for Students That Must Cross the Roadway

You should understand what students should do when exiting a school bus and crossing the street in front of the bus. In addition, the school bus driver should understand that students might not always do what they are supposed to do. If a student or students must cross the roadway, they should follow these procedures:

- *Walk approximately 10 feet away from the side of the school bus to a position where you can see them.*
- *Walk to a location at least 10 feet in front of the right corner of the bumper, but still remaining away from the front of the school bus.*
- *Stop at the right edge of the roadway. You should be able to see the student's feet.*
- *When students reach the edge of the roadway, they should:*
  - ✧ Stop and look in all directions, making sure the roadway is clear and is safe.
  - ✧ Check to see if the red flashing lamps on the bus are still flashing.
  - ✧ Wait for your signal before crossing the roadway.
- *Upon your signal, the students should:*
  - ✧ Cross far enough in front of the school bus to be in your view.
  - ✧ Walk to the left edge of the school bus, stop, and look again for your signal to continue to cross the roadway.
  - ✧ Look for traffic in both directions, making sure roadway is clear.
  - ✧ Proceed across the roadway, continuing to look in all directions.

The loading procedure is essentially the same wherever you load students, but there are slight differences. When students are loading at the school campus, you should:

- *Turn off the ignition switch.*
- *Remove key if leaving driver's compartment.*
- *Position yourself to supervise loading as required or recommended by your state or local regulations.*

### 10.2.3 - Unloading Procedures on the Route

- *Perform a safe stop at designated unloading areas as described in subsection 10.2.1.*
- *Have the students remain seated until told to exit.*
- *Check all mirrors.*
- *Count the number of students while unloading to confirm the location of all students before pulling away from the stop.*
- *Tell students to exit the bus and walk at least 10 feet away from the side of the bus to a position where the driver can plainly see all students.*
- *Check all mirrors again. Make sure no students are around or returning to the bus.*

## Notes:

1. The school bus driver should enforce any state or local regulations or recommendations concerning student actions outside the school bus.
2. It is important for the driver to understand that any hand or other signal that is given to a student also could be misinterpreted by motorists that are stopped in the area.

### 10.2.4 - Unloading Procedures at School

State and local laws and regulations regarding unloading students at schools, particularly in situations where such activities take place in the school parking lot or other location that is off the traveled roadway, are often different than unloading along the school bus route. It is important that the school bus driver understands and obeys state and local laws and regulations. The following procedures are meant to be general guidelines.

When unloading at the school, you should follow these procedures:

- **Perform a safe stop at designated unloading areas as described in subsection 10.2.1.**
- **Secure the bus by:**
  - ◇ Turning off the ignition switch.
  - ◇ Removing key if leaving driver's compartment.
- **Have the students remain seated until told to exit.**
- **Position yourself to supervise unloading as required or recommended by your state or local regulations.**
- **Have students exit in orderly fashion.**
- **Observe students as they step from bus to see that all move promptly away from the unloading area.**
- **Walk through the bus and check for hiding/sleeping students and items left by students.**
- **Check all mirrors. Make certain no students are returning to the bus.**
- **If you cannot account for a student outside the bus and the bus is secure, check around and underneath the bus.**
- **When all students are accounted for, prepare to leave by:**
  - ◇ Closing the door.
  - ◇ Fastening safety belt.
  - ◇ Starting engine.
  - ◇ Engaging the transmission.
  - ◇ Releasing the parking brake.
  - ◇ Turning off alternating flashing red lamps.
  - ◇ Turning on left turn signal.

◇ Allowing congested traffic to disperse.

◇ Checking all mirrors again.

- **When it is safe, pull away from the unloading area.**

### 10.2.5 - Special Dangers of Loading and Unloading

**Dropped or Forgotten Objects.** Always focus on students as they approach the bus and watch for any student who disappears from sight.

Students may drop an object near the bus during loading and unloading. Stopping to pick up the object, or returning to pick up the object, may cause the student to disappear from the driver's sight at a very dangerous moment.

Students should be told to leave any dropped object and move to a point of safety out of the danger zones and attempt to get the driver's attention to retrieve the object.

**Handrail Hang-ups.** Students have been injured or killed when clothing, accessories, or even parts of their body get caught in the handrail or door as they exited the bus. You should closely observe all students exiting the bus to confirm that they are in a safe location prior to moving the bus.

### 10.2.6 - Post-Trip Inspection

When your route or school activity trip is finished, you should conduct a post-trip inspection of the bus.

You should walk through the bus and around the bus looking for the following:

- **Articles left on the bus.**
- **Sleeping students.**
- **Open windows and doors.**
- **Mechanical/operational problems with the bus, with special attention to items that are unique to school buses — mirror systems, flashing warning lamps, and stop signal arms.**
- **Damage or vandalism.**

Any problems or special situations should be reported immediately to your supervisor or school authorities.

## 10.3 Emergency Exit and Evacuation

An emergency situation can happen to anyone, anytime, anywhere. It could be a crash, a stalled school bus on a railroad-highway crossing or in a high-speed intersection, an electrical fire in the engine compartment, a medical emergency to a student on the school bus, etc. Knowing what to do in an emergency—before, during, and after an evacuation—can mean the difference between life and death.

## 10.3 Emergency Exit and Evacuation (continued)

### 10.3.1 - Planning for Emergencies

#### - *Determine Need to Evacuate Bus*

The first and most important consideration is for you to recognize the hazard. If time permits, school bus drivers should contact their dispatcher to explain the situation before making a decision to evacuate the school bus.

As a general rule, student safety and control is best maintained by keeping students on the bus during an emergency and/or impending crisis situation, if so doing does not expose them to unnecessary risk or injury. Remember, the decision to evacuate the bus must be a timely one.

A decision to evacuate should include consideration of the following conditions:

- ✧ Is there a fire or danger of fire?
- ✧ Is there a smell of leaking fuel?
- ✧ Is there a chance the bus could be hit by other vehicles?
- ✧ Is the bus in the path of a sighted tornado or rising waters?
- ✧ Are there downed power lines?
- ✧ Would removing students expose them to speeding traffic, severe weather, or a dangerous environment such as downed power lines?
- ✧ Would moving students complicate injuries such as neck and back injuries and fractures?
- ✧ Is there a hazardous spill involved? Sometimes, it may be safer to remain on the bus and not come in contact with the material.

#### - *Mandatory Evacuations*

The driver must evacuate the bus when:

- ✧ The bus is on fire or there is a threat of a fire.
- ✧ The bus is stalled on or adjacent to a railroad-highway crossing.
- ✧ The position of the bus may change and increase the danger.
- ✧ There is an imminent danger of collision.
- ✧ There is a need to quickly evacuate because of a hazardous materials spill.

### 10.3.2 - Evacuation Procedures

#### - *Be Prepared and Plan Ahead*

When possible, assign two responsible, older student assistants to each emergency exit. Teach them how to assist the other students off the bus. Assign another student

assistant to lead the students to a “safe place” after evacuation. However, you must recognize that there may not be older, responsible students on the bus at the time of the emergency. Therefore, emergency evacuation procedures must be explained to all students. This includes ensuring that they know the location of and operation of the various emergency exits and the importance of listening to and following all instructions given by you.

Some tips to determine a safe place:

- ✧ A safe place for the students will be at least 100 feet off the road in the direction of oncoming traffic. This will keep them from being hit by debris if another vehicle collides with the bus.
- ✧ Lead students upwind of the bus if fire is present.
- ✧ Lead students as far away from railroad tracks as possible and in the direction of any oncoming train.
- ✧ Lead students upwind of the bus at least 300 feet if there is a risk from spilled hazardous materials.
- ✧ If the bus is in the direct path of a sighted tornado and evacuation is ordered, escort students to a nearby ditch or culvert if shelter in a building is not readily available, and direct them to lie face down, hands covering their head. They should be far enough away so the bus cannot topple on them. Avoid areas that are subject to flash floods.

#### - *General Procedures*

Determine if evacuation is in the best interest of safety.

- ✧ Determine the best type of evacuation:
  - Front, rear or side door evacuation, or some combination of doors.
  - Roof or window evacuation.
- ✧ Secure the bus by:
  - Setting parking brakes.
  - Placing transmission in Park, or if there is no shift point, in Neutral.
  - Shutting off the engine.
  - Removing ignition key.
  - Activating hazard-warning lamps.
- ✧ If time allows, notify dispatch office of evacuation location, conditions, and type of assistance needed.
- ✧ Dangle radio microphone or telephone out of driver’s window for later use, if operable.
- ✧ If no radio, or radio is inoperable, dispatch a passing motorist or area resident to call for help. As a last resort, dispatch two older, responsible students to go for help.

- ❖ Order the evacuation.
- ❖ Evacuate students from the bus.
  - Do not move a student you believe may have suffered a neck or spinal injury unless his or her life is in immediate danger.
  - Special procedures must be used to move neck or spinal injury victims to prevent further injury.
- ❖ Direct a student assistant to lead students to the nearest safe place.
- ❖ Walk through the bus to ensure no students remain on the bus. Retrieve emergency equipment.
- ❖ Join waiting students. Account for all students and check for their safety.
- ❖ Protect the scene. Set out emergency warning devices as necessary and appropriate.
- ❖ Prepare information for emergency responders.

Fig. 10-05

## Round Yellow Warning Sign



## 10.4 Railroad-Highway Crossings

### 10.4.1 - Types of Crossings

#### - *Passive Crossings*

This type of crossing does not have any type of traffic control device. You must stop at these crossings and follow proper procedures. However, the decision to proceed rests entirely in your hands. Passive crossings require you to recognize the crossing, search for any train using the tracks, and decide if there is sufficient clear space to cross safely. Passive crossings have yellow circular advance warning signs, pavement markings and crossbucks to assist you in recognizing a crossing.

#### - *Active Crossings*

This type of crossing has a traffic control device installed at the crossing to regulate traffic. These active devices can include flashing red lights, flashing red lights with bells, and flashing red lights with bells and gates.

### 10.4.2 - Warning Signs and Devices

#### - *Advance Warning Signs*

The round, black-on-yellow warning sign is placed ahead of a public railroad-highway crossing. The advance warning sign tells you to slow down, look and listen for the train, and be prepared to stop at the tracks if a train is coming. See Figure 10.05.

#### - *Pavement Markings*

Pavement markings mean the same as the advance warning sign. They consist of an "X" with the letters "RR" and a no-passing marking on two-lane roads. See Figure 10.06.

There is also a no passing zone sign on two-lane roads. There may be a white stop line painted on the pavement before the railroad tracks. The front of the school bus must remain behind this line while stopped at the crossing.

Fig. 10-06

## Pavement Markings



## 10.4 Railroad-Highway Crossings (continued)

### - Crossbuck Signs

This sign marks a passive crossing. It requires you to yield the right-of-way to the train. When the road crosses over more than one set of tracks, a sign below the crossbuck indicates the number of tracks. See Figure 10.07.

### - Flashing Red Light Signals

At many active highway-rail grade crossings, the crossbuck sign has flashing red lights and bells. When the lights begin to flash, stop! A train is approaching. You are required to yield the right-of-way to the train. If there is more than one track, make sure all tracks are clear before crossing. See Figure 10.08.

### - Gates

Many active railroad-highway crossings have gates with flashing red lights and bells. Stop when the lights begin to flash and before the gate lowers across the road lane. Remain stopped until the gates go up and the lights have stopped flashing. Proceed when it is safe. If the gate stays down after the train passes, do not drive around the gate. Instead, contact your dispatcher. See Figure 10.08.

Fig. 10-07





Fig. 10-08

## Gates/Lights



### 10.4.3 - Recommended Procedures

Each state has laws and regulations governing how school buses must operate at railroad-highway crossings. It is important for you to understand and obey these state laws and regulations. In general, school buses must stop at all crossings, and ensure it is safe to proceed across the tracks. The specific procedures required in each state vary.

A school bus is one of the safest vehicles on the highway. However, a school bus does not have the slightest edge when involved in a crash with a train. Because of a train's size and weight, it cannot stop quickly. An emergency escape route does not exist for a train. You can prevent school bus/train crashes by following these recommended procedures.

#### - Approaching the Crossing:

- ✧ Slow down, including shifting to a lower gear in a manual transmission bus, and test your brakes.
- ✧ Activate amber pre-warning lights approximately 300 to 100 feet before the crossing. Make sure your intentions are known.
- ✧ Scan your surroundings and check for traffic behind you.
- ✧ Stay to the right of the roadway, if possible.
- ✧ Choose an escape route in the event of a brake failure or problems behind you.

- **At the Crossing:**

- ❖ Stop no closer than 15 feet and no farther than 50 feet from the nearest rail, where you have the best view of the tracks.
- ❖ If a train is present, set the parking brake, place the transmission in Park, or if there is no Park shift point, place in Neutral.
- ❖ Turn off all radios and noisy equipment, and silence the passengers.

- **Crossing the Track:**

- ❖ Check the crossing signals again before proceeding.
- ❖ At a multiple-track crossing, stop only before the first set of tracks. When you are sure no train is approaching on any track, proceed across all of the tracks until you have completely cleared them.
- ❖ Cross the tracks in a low gear. Do not change gears while crossing.
- ❖ If the gate comes down after you have started across, drive through it even if it means you will break the gate.

#### 10.4.4 - Special Situations

- **Bus Stalls or Trapped on Tracks**

If your bus stalls or is trapped on the tracks, get everyone out of the bus and off the tracks immediately. Move everyone far from the bus at an angle, which is both away from the tracks and toward the train.

- **Police Officer at the Crossing**

If a police officer is at the crossing, obey directions. If there is no police officer, and you believe the signal is malfunctioning, contact your dispatcher to report the situation and ask for instructions on how to proceed.

- **Obstructed View of Tracks**

Plan your route so it provides maximum sight distance at highway-rail grade crossings. Do not attempt to cross the tracks unless you can see far enough down the track to know for certain that no trains are approaching. Be especially careful at “passive” crossings. Even if there are active railroad signals that indicate the tracks are clear, you must look and listen to be sure it is safe to proceed.

- **Containment or Storage Areas**

If it won't fit, don't commit! Know the length of your bus and the size of the containment area at highway-rail crossings on the school bus route, as well as any crossing you encounter in the course of a school activity trip. When approaching a crossing with a signal or stop sign on the opposite side, pay attention to the amount of room there. Be certain the bus has enough containment or storage area

to completely clear the railroad tracks on the other side if there is a need to stop. As a general rule, add 15 feet to the length of the school bus to determine an acceptable amount of containment or storage area.

## 10.5 Student Management

### 10.5.1 - Don't Deal With On-Bus Problems When Loading and Unloading

In order to get students to and from school safely and on time, you need to be able to concentrate on the driving task. Loading and unloading requires all your concentration. Don't take your eyes off what is happening outside the bus. If there is a behavior problem on the bus, wait until the students unloading are safely off the bus and have moved away. If necessary, pull the bus over to handle the problem.

### 10.5.2 - Handling Serious Problems

- **Tips on Handling Serious Problems**

- ❖ Follow your school's procedures for discipline or refusal of rights to ride the bus.
- ❖ Stop the bus. Park in a safe location off the road, perhaps a parking lot or a driveway.
- ❖ Secure the bus. Take the ignition key with you if you leave your seat.
- ❖ Stand up and speak respectfully to the offender or offenders. Speak in a courteous manner with a firm voice. Remind the offender of the expected behavior. Do not show anger, but do show that you mean business.
- ❖ If a change of seating is needed, request that the student move to a seat near you.
- ❖ Never put a student off the bus except at school or at his or her designated school bus stop. If you feel that the offense is serious enough that you cannot safely drive the bus, calling for a school administrator or the police to come and remove the student may be appropriate. Always follow your state or local procedures for requesting assistance.

## 10.6 Antilock Braking Systems

### 10.6.1 - Vehicles Required to Have Antilock Braking Systems

The Department of Transportation requires that antilock braking systems be on:

- **Air brake vehicles, (trucks, buses, trailers, and converter dollies) built on or after March 1, 1998.**

## 10.6 Antilock Braking Systems (continued)

- *Hydraulically braked trucks and buses with a gross vehicle weight rating of 10,000 lbs or more built on or after March 1, 1999.*

Many buses built before these dates have been voluntarily equipped with ABS.

Your school bus will have a yellow ABS malfunction lamp on the instrument panel if it is equipped with ABS.

### 10.6.2 - How ABS Helps You

When you brake hard on slippery surfaces in a vehicle without ABS, your wheels may lock up. When your steering wheels lock up, you lose steering control. When your other wheels lock up, you may skid or even spin the vehicle.

ABS helps you avoid wheel lock up and maintain control. You may or may not be able to stop faster with ABS, but you should be able to steer around an obstacle while braking and avoid skids caused by over braking.

### 10.6.3 - Braking With ABS

When you drive a vehicle with ABS, you should brake as you always have. In other words:

- *Use only the braking force necessary to stop safely and stay in control.*
- *Brake the same way, regardless of whether you have ABS on the bus. However, in emergency braking, do not pump the brakes on a bus with ABS.*
- *As you slow down, monitor your bus and back off the brakes (if it is safe to do so) to stay in control.*

### 10.6.4 - Braking if ABS Is Not Working

Without ABS, you still have normal brake functions. Drive and brake as you always have.

Vehicles with ABS have yellow malfunction lamps to tell you if something is not working. The yellow ABS malfunction lamp is on the bus's instrument panel.

As a system check on newer vehicles, the malfunction lamp comes on at start-up for a bulb check and then goes out quickly. On older systems, the lamp could stay on until you are driving over five mph.

If the lamp stays on after the bulb check, or goes on once you are under way, you may have lost ABS control at one or more wheels.

Remember, if your ABS malfunctions, you still have regular brakes. Drive normally, but get the system serviced soon.

### 10.6.5 - Safety Reminders

- *ABS does not compensate for bad driving habits, such as driving too fast, following too closely, or driving less carefully.*
- *ABS won't prevent power or turning skids—ABS should prevent brake-induced skids but not those caused by spinning the drive wheels or going too fast in a turn.*
- *ABS won't necessarily shorten stopping distance. ABS will help maintain vehicle control, but not always shorten stopping distance.*
- *ABS won't increase or decrease ultimate stopping power—ABS is an "add-on" to your normal brakes, not a replacement for them.*
- *ABS won't change the way you normally brake. Under normal brake conditions, your vehicle will stop as it always stopped. ABS only comes into play when a wheel would normally have locked up because of over braking.*
- *ABS won't compensate for bad brakes or poor brake maintenance.*
- *Remember: The best vehicle safety feature is still a safe driver.*
- *Remember: Drive so you never need to use your ABS.*
- *Remember: If you need it, ABS could help prevent a serious crash.*

## 10.7 Special Safety Considerations

### 10.7.1 - Headlight Operation

Oklahoma state law requires the use of headlights at all times while operating church buses and school buses.

### 10.7.2 - Strobe Lights

Some school buses are equipped with roof-mounted, white strobe lights. If your bus is so equipped, the overhead strobe light should be used when you have limited visibility. This means that you cannot easily see around you — in front, behind, or beside the school bus. Your visibility could be only slightly limited or it could be so bad that you can see nothing at all. In all instances, understand and obey your state or local regulations concerning the use of these lights.

### 10.7.3 Speed Limits for School Buses

Oklahoma law has special speed limits for operators of school buses. The maximum limits are set as follows:

- *55 miles per hour on paved two-lane highways*
- *65 miles per hour on multi-lane divided highways, turnpikes and interstate highways*

### 10.7.4 - Driving in High Winds

Strong winds affect the handling of the school bus! The side of a school bus acts like a sail on a sailboat. Strong winds can push the school bus sideways. They can even move the school bus off the road or, in extreme conditions, tip it over.

#### - *If You Are Caught in Strong Winds*

- ❖ Keep a strong grip on the steering wheel. Try to anticipate gusts.
- ❖ You should slow down to lessen the effect of the wind, or pull off the roadway and wait.
- ❖ Contact your dispatcher to get more information on how to proceed.

### 10.7.5 - Backing

Backing a school bus is strongly discouraged. You should back your bus only when you have no other safe way to move the vehicle. You should never back a school bus when students are outside of the bus. Backing is dangerous and increases your risk of a collision.

#### - *If You Have No Choice and You Must Back Your Bus, Follow These Procedures:*

- ❖ Post a lookout, preferably inside the school bus looking out the rear window. The purpose of the lookout is to warn you about obstacles, approaching persons, and other vehicles. The lookout should not give directions on how to back the bus.
- ❖ Signal for quiet on the bus.
- ❖ Constantly check all mirrors and rear windows.
- ❖ Back slowly and smoothly.
- ❖ If no lookout is available:
  - Set the parking brake.
  - Turn off the motor and take the keys with you.
  - Walk to the rear of the bus to determine whether the way is clear.

- *If you must back-up at a student pick-up point, be sure to pick up students before backing and watch for late comers at all times.*

- *Be sure that all students are in the bus before backing.*

- *If you must back-up at a student drop-off point, be sure to unload students after backing.*

### 10.7.6 – Tail Swing

A school bus can have up to a three-foot tail swing. You need to check your mirrors before and during any turning movements to monitor the tail swing.

## TEST YOUR KNOWLEDGE

1. Define the danger zone. How far does the danger zone extend around the bus?
2. What should you be able to see if the outside flat mirrors are adjusted properly? The outside convex mirrors? The cross-view mirrors?
3. You are loading students along the route. When should you activate your alternating flashing amber warning lamps?
4. You are unloading students along your route. Where should students walk to after exiting the bus?
5. After unloading at school, why should you walk through the bus?
6. What position should students be in front of the bus before they cross the roadway?
7. Under what conditions must you evacuate the bus?
8. How far from the nearest rail should you stop at a highway-rail crossing?
9. What is a passive highway-rail crossing? Why should you be extra cautious at this type of crossing?
10. How should you use your brakes if your vehicle is equipped with antilock brakes (ABS)?

*These questions may be on the test. If you can't answer all, re-read Section 10.*