

# **RED ROCK**

---

# **CONSULTING**

## ***Report of Geotechnical Investigation***

**OF**

***I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA***

**35589(04)**

***Prepared For:***

Olsson Associates  
11600 Broadway Extension, Suite 300  
Oklahoma City, Oklahoma 73114  
Attention: Mr. Russell Beaty, PE

***Prepared By:***

Red Rock Consulting, LLC  
PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

June 23, 2023  
Project No. 22118

# RED ROCK CONSULTING

June 23, 2023

Olsson Associates  
11600 Broadway Extension, Suite 300  
Oklahoma City, Oklahoma 73114

Attention: Mr. Russell Beaty, PE

Re: Report of Geotechnical Investigation  
**I-35 Pavement and Subgrade Survey**  
**35589(04)**  
**McClain County, Oklahoma**  
Project No. 22118

Dear Mr. Beaty:

I am pleased to submit herewith this report entitled "Geotechnical Investigation, I-35 Pavement and Subgrade Survey, 35589(04), McClain County, Oklahoma".

In an effort to provide a more environmentally friendly service, this report has been provided electronically.

It has been our pleasure to assist you with this project. Should you have any questions regarding the contents of this report, please contact Red Rock Consulting.

Yours very truly,  
**RED ROCK CONSULTING, LLC**  
CA No. 5707 Exp. 06/30/23



Emma Coggin, EI  
Project Specialist



Jeremy Basler, PE  
Geotechnical Manager  
Oklahoma PE No. 20233



**REPORT OF GEOTECHNICAL INVESTIGATION**

**I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA**

**35589(04)**

**PROJECT NO. 22118**

**INTRODUCTION..... 1**  
    GENERAL..... 1  
    PROPOSED CONSTRUCTION ..... 1  
    SCOPE OF WORK ..... 1  
**FIELD AND LABORATORY INVESTIGATIONS ..... 3**  
    FIELD EXPLORATION ..... 3  
    LABORATORY TESTING..... 4  
**SITE DESCRIPTION..... 5**  
    SURFACE CONDITIONS..... 5  
    SITE GEOLOGY ..... 5  
    SUBSURFACE CONDITIONS..... 6  
    GROUNDWATER CONDITIONS ..... 7  
**CLOSURE..... 8**

**APPENDICES**

- APPENDIX A – Boring Location Diagrams
- APPENDIX B – Pavement Core Data and Subgrade Soils Chart
- APPENDIX C – Core Logs and Pavement Photographs
- APPENDIX D – FWD Report
- APPENDIX E – Laboratory Results
- APPENDIX F – General Notes

# **REPORT OF GEOTECHNICAL INVESTIGATION**

## **I-35 PAVEMENT AND SUBGRADE SURVEY MCCLAIN COUNTY, OKLAHOMA**

**35589(04)**

**PROJECT NO. 22118**

### **INTRODUCTION**

#### **General**

This report presents the results of the geotechnical investigation performed for the potential overlay or reconstruction of the existing pavement of the I-35 mainline along the current alignment from 1.0 mile south of Ladd Road extending north approximately 4.7 miles in McClain County, Oklahoma.

#### **Proposed Construction**

The proposed project will include the potential overlay or reconstruction of the existing pavement of the I-35 mainline along the current alignment from 1.0 mile south of Ladd Road extending north approximately 4.7 miles in McClain County, Oklahoma. The project also includes the widening of the existing pavement of I-35 in the center median and outside lanes to accommodate adding one lane of traffic in each direction.

The purpose of this investigation is to evaluate the existing pavement, base and subgrade materials at the site and to provide information pertaining to the geotechnical aspects of the proposed project.

#### **Scope of Work**

The scope of this investigation includes the following:

1. Review of previous geotechnical and geological information of sites near this site. This was augmented with data obtained during the field investigation phase of the project.
2. Evaluation of the existing pavement using Falling Weight Deflectometer (FWD) testing
3. Investigation of the subsurface soils of the mainline pavement by coring, drilling, sampling and testing a total of 46 boreholes within the planned project area

**I-35 Pavement and Subgrade Survey**  
**McClain County, Oklahoma**  
**35589(04)**  
**Project No. 22118**  
**June 23, 2023**

4. A laboratory testing program consisting of moisture content, Atterberg limits, and full sieve tests on the soils encountered

## FIELD AND LABORATORY INVESTIGATIONS

### Field Exploration

Falling Weight Deflectometer (FWD) testing was performed by Naji Khoury on December 6<sup>th</sup>, 2022 along the existing I-35 in accordance with Oklahoma Department of Transportation's (ODOT) Geotechnical Specifications for Roadway Design (2011). The tests were performed in the outside wheel path of the outside lane approximately every 500 feet or less per lane, staggered at a spacing of 250 feet or less between the northbound and southbound lanes. After completing the FWD testing, the data was analyzed and the structural properties of the pavement and subgrade layers were provided for each testing location. The full FWD report is presented in Appendix D.

Following the FWD testing, the subsurface exploration program consisted of coring and sampling 46 borings in the roadway. The subsurface exploration was performed by Red Rock Consulting on December 16<sup>th</sup>, 19<sup>th</sup>, 20<sup>th</sup>, 27<sup>th</sup> and 28<sup>th</sup>, 2022. The borings were located in the field by a representative of Red Rock Consulting by using GPS coordinates that correlated with marked locations that were provided by Naji Khoury. The GPS coordinates of each boring is included in the Core Logs in Appendix C. The locations of the borings should be considered accurate only to the degree implied by the methods used to define them.

Twenty three (23) borings were located within the pavement of I-35 northbound and twenty three (23) borings within the pavement of I-35 southbound. The roadway borings were located at selected FWD test locations, which were recommended by Naji Khoury. The approximate locations of the borings are shown on the Boring Location Diagrams in Appendix A.

The pavement at each boring location was cored with a 4-inch barrel using a coring machine which was mounted on the back of a trailer for the 4-inch samples. Measured pavement thicknesses are shown on the Pavement Core Data and Subgrade Soils Chart in Appendix B. Photographs of the cores and existing pavement are included on the Core Logs and Pavement Photographs in Appendix C. Correlation between the pavement thickness, FWD test locations and stations along the project length are included in the FWD report in Appendix D.

Following the coring of the pavement, the roadway boring locations were then drilled to depths of approximately 36 inches or refusal beneath the existing pavement. The borings were drilled using a HD99 Hydraulic Earth Drill.

Representative samples of the subgrade materials were obtained from the auger cuttings at depths shown on the Pavement Core Data and Subgrade Soils in Appendix B.

Samples were collected and transported back to the lab for further classification and testing. The final Pavement Core Data and Subgrade Soils Chart was developed from the draft logs, observations and test results of the samples returned to the laboratory. The stratigraphic contacts indicated are only for the specific dates and locations reported, and therefore, are not necessarily representative of other locations and times.

### **Laboratory Testing**

Representative soil samples were tested to refine the field classifications and evaluate physical properties of the soils which may affect the geotechnical aspects of project design and construction.

The laboratory testing program included the following:

- Moisture content (AASHTO T265)
- Liquid limit (AASHTO T89)
- Plastic limit (AASHTO T90)
- Particle size analysis of soils (AASHTO T88)

The results of the physical laboratory tests conducted on the subgrade soils are shown on the Pavement Core Data and Subgrade Soils Chart in Appendix B. The laboratory results in entirety are included in Appendix E.

The above laboratory tests were performed in general accordance with applicable AASHTO procedures, or generally accepted practice. It should be noted that reference to AASHTO procedures does not imply that all cross-referenced procedures in AASHTO standards have been used, or that all AASHTO procedures used have been followed exactly. Only those AASHTO procedures and/or portions of procedures, which, in the professional judgment of the geotechnical engineer of record for this report, are applicable, appropriate, and necessary for this particular project, have been used or followed.

## SITE DESCRIPTION

### Surface Conditions

At the time of the field exploration, I-35 was a four lane divided Asphalt Concrete paved roadway with a grass median for the entire length of the project. The project area was partially developed with a few businesses and a small airport near the SH 74 interchange. Continuing south along I-35 was primarily agricultural fields and a few residences. The town of Goldsby was located towards the northern end of the job.

Traffic was high on I-35 during drilling operations. Large trucks consisted of approximately half of the traffic. Traffic control was required to drill the borings.

The existing pavement was in fair to good condition. A recent asphalt overlay was observed across the northern half of the project length along the northbound and southbound lanes. Minor to moderate transverse cracking and minor longitudinal cracking were observed.

For the Boring Location Diagrams, refer to Appendix A. For more detailed descriptions of the pavement distress, refer to the notes column in the Pavement Core Data and Subgrade Soils Chart in Appendix B and the Pavement Photographs in Appendix C. For photographs of the pavement cores and the existing pavement, refer to Appendix C.

### Site Geology

The geology of the project site was researched using the "Division Three Engineering Classification of Geological Materials", published by the Oklahoma Department of Transportation (ODOT) and the Geologic Map of the "Hydrologic Atlas 4 of Oklahoma," Reconnaissance of the Water Resources of the Oklahoma City quadrangle, central Oklahoma," by Roy H. Bingham and Robert L. Moore, U.S. Geological Survey, 1975.

### ODOT PUBLICATION

Division Three of the "Engineering Classification of Geological Materials", published by the Oklahoma Department of Transportation (ODOT) indicates the project site consists of Alluvium (Qas) and Terrace deposits (Qts) underlain by the Hennessey Unit (Phy).

**Terrace deposits consist of sand, silt, clay, gravel, or mixtures of these.** These materials were deposited by streams or wind and may be found adjacent to most streams.

**The Hennessey unit consists of red platy to blocky clay shales and mudstone.** The mudstones are hard and appear blocky. The red clay shale of the Hennessey unit is characterized by numerous bands or streaks of gray, white, or light green color ranging from a few inches to four feet in thickness. Small spheres of light green color up to 10 inches in diameter are an odd characteristic of the unit.

The total thickness of the unit varies from 400 to 600 feet. The Hennessey unit outcrops in a 5 to 20 mile wide north-south band across Cleveland, McClain, and Garvin Counties in Division three.

Topographically, the unit is near level to gently rolling prairies, but most of the more level outcrops of the unit are cultivated.

#### USGS MAP

According to the USGS geologic map, the project consists of Alluvium (Qal) and Terrace deposits (Qt) which are underlain by Purcell Sandstone (Pp).

**Terrace deposits consist of lenticular beds of sand, silt, clay, and gravel.** Thickness ranges from a few feet to about 100 feet and probably averages about 50 feet along major streams. These deposits are major aquifers along Cimarron, Canadian, and North Canadian Rivers.

**Purcell Sandstone consists of red-brown to maroon fine- to coarse-grained sandstone, mudstone conglomerate, and red-brown shale.** Thickness, 150 feet.

#### Subsurface Conditions

Information collected from the core locations explored indicates that the existing pavement of I-35 along the project consisted of Asphalt Concrete. The total thickness of the full depth asphalt concrete in the roadway cores ranged between 9.25 to 16.5 inches. A cement stabilized subgrade was encountered underneath cores C-1 to C-18 and C-29 to C-46, ranging from 4.5 to 10 inches. Aggregate base was encountered underneath the remaining cores C-19 to C-28, ranging from 6 to 10 inches.

The condition of the existing surface pavement and the pavement cores are described in the Pavement Core Data and Subgrade Soils Chart in Appendix B and the Core Logs in Appendix C.

Beneath the pavement section, the subgrade materials consisted of silty, clayey sand with various amounts of gravel, clayey sand, sandy silt, silty sand with various amounts

**I-35 Pavement and Subgrade Survey**  
**McClain County, Oklahoma**  
**35589(04)**  
**Project No. 22118**  
**June 23, 2023**

of gravel and lean clay with various amounts of sand and silt. The subgrade materials encountered in the borings classified as A-1-b, A-2-4, A-4 and A-6 soils. The subgrade materials extended to the boring termination depth of 36 inches below the pavement, except for borings C-4, C-5, C-21 to C-23, C-37, C-40 and C-41 where auger refusal was encountered between 17.5 and 52 inches below the pavement. The subgrade materials appeared to be native to the site. The subgrade in borings C-19 and C-20 had an organic smell. Subsurface conditions are described in greater detail on the Pavement Data and Subgrade Soils Chart in Appendix B and on the Core Logs in Appendix C. Laboratory results of the subsurface materials tested are included in Appendix E.

### **Groundwater Conditions**

Groundwater conditions were monitored in the borings during and following coring/boring and sampling. Groundwater was not encountered in any of the borings during these times.

To obtain more accurate groundwater level information, long-term observations in a well or piezometer that is sealed from the influence of surface water would be needed. Fluctuations in groundwater levels can occur due to seasonal variations in the amount of rainfall, runoff, altered drainage paths, and other factors not evident at the time borings were advanced. Consequently, the contractor should be aware of this possibility while constructing this project.

## **CLOSURE**

The data presented in this report are based on the negotiated scope for this project and site conditions as they existed at the time of the field exploration. The conditions encountered in the exploratory borings are assumed to be representative of the subsurface conditions within the study area.

This report was prepared for the exclusive use of Olsson Associates, ODOT, and their agents and consultants. It should be made available to prospective contractors for information and factual data only and not as a warranty of subsurface conditions similar to those interpreted from the Pavement Core Data and Subgrade Soils Chart or discussions presented herein.


## **APPENDIX A**

Utilities		
Utility	CONTACT	Phone Number
ONG	LEE ANN PULLIAM	405-552-1834
OEC	KOLTON HOWRY	405-217-6623
WINDSTREAM		405-228-2530
GOLDSBY WATER AUTHORITY	RONNY NELSON	405-288-6697
CENTURYLINK/LEVEL3/IRC		800-441-0223
HILL OIL COMPANY		405-273-8046
DCP MIDSTREAM		405-288-2387
WESTERN FARMERS ELECTRIC		405-247-3351
TRACE FIBER NETWORKS		844-499-5656

Sta. 635+03.34 @ 5"x7"x151.2" Rdy  
 RCB X-Drain 75.6" LI & 75.6" RT  
 I.L. Elev. LI = 1132.97 & RT = 1131.01  
 Sta. 635+13.88 @ 18" x16.3" Long  
 CMP S.D. 0.5' RT - I.L. Elev. N =  
 1136.72 & S = 1135.44 (assumed)  
 Sta. 635+23.02 @ Median Inlet  
 0.5' RT - Top Grate = 1141.09  
 I.L. Elev. 18" CMP Out S = 1136.65

SECTION 5  
 T-7-N, R-2-W

STA. 632+50.00  
 BEGIN CONSTRUCTION  
 X=2138203.5696  
 Y=645409.8476



LEGEND:  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-46	633+22	40' left
C-1	640+24	40' right


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
 CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No.	22118
Designed By:	DLW	Scale:	NOT TO SCALE
Checked By:	JWB	Date:	1/11/2023
Approved By:	JWB	Page No:	1/17



Sta. 651+66.54 @ Station, Inlet  
 0.2' LI - 7.00' Long = 1:40:22  
 E. Elev. 18' CWP CWP N = 1136.05  
 Sta. 651+74.58 @ 18" x 38" Long  
 CWP S.D. 0.2' LI - E. Elev. S =  
 1135.85 & N = 1134.70 (assumed)  
 Sta. 651+64.86 @ 4" x 20" x 14.8' Rod  
 Served RCS X-Cross 75.4' LI &  
 74.2' RI - E. Elev. LI = 1132.61 &  
 RI = 1138.78

Boring	Station	I-35 CL Survey
C-45	648+15	40' left
C-2	652+91	40' right
C-44	658+08	40' left


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 2/17



SECTION 5  
T-7-N, R-2-W

665+00

670+00

675+00

660+00

I-35 SOUTHBOUND

I-35 NORTHBOUND

BRIDGE STRUCTURE

SURVEY I-35

BL RAMP A

C-3

C-43

C-4

LEGEND:

I-35 RECONSTRUCTION

SECTION 5  
T-7-N, R-2-W

Boring	Station	I-35 CL Survey
C-3	662+06	40' right
C-43	668+19	40' left
C-4	672+36	40' right


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 3/17



**LEGEND:**  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-42	677+79	40' left
C-5	682+54	40' right
C-41	687+92	41' left


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 4/17



Boring	Station	I-35 CL Survey
C-6	690+04	40' right
C-40	693+85	40' left
C-7	701+90	40' right


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 DISTRICT 3, MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No.	22118
Designed By:	DLW	Scale:	NOT TO SCALE
Checked By:	JWB	Date:	1/11/2023
Approved By:	JWB	Page No.:	5/17



Boring	Station	I-35 CL Survey
C-39	707+72	40' left
C-8	712+30	40' right
C-38	717+64	40' left

Stations and offsets estimated from plans provided by Olsson Associates


**LEGEND:**  
 I-35 RECONSTRUCTION

**RED ROCK CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No.	22118
Designed By:	DLW	Scale:	NOT TO SCALE
Checked By:	JWB	Date:	1/11/2023
Approved By:	JWB	Page No:	6/17



LEGEND:  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-9	722+10	40' right
C-37	727+60	40' left
C-10	731+99	40' right

Stations and offsets estimated from plans provided by Olsson Associates


**RED ROCK CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

---

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 7/17



LEGEND:  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-36	737+44	40' left
C-11	741+97	40' right
C-35	747+34	40' left


Stations and offsets estimated from plans provided by Olsson Associates

## RED ROCK CONSULTING

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No.	22118
Designed By:	DLW	Scale:	NOT TO SCALE
Checked By:	JWB	Date:	1/11/2023
Approved By:	JWB	Page No:	8/17



SECTION 30  
T-8-N, R-2-W

LEGEND:  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-12	752+06	40' right
C-34	757+26	40' left
C-13	761+72	40' right

Stations and offsets estimated from plans provided by Olsson Associates


**RED ROCK  
CONSULTING**

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 9/17

SECTION 25  
T-8-N, R-3-W



LEGEND:

I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-33	767+10	40' left
C-14	771+57	40' right
C-32	777+24	40' left

Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**


PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 10/17

SECTION 25  
T-8-N, R-3-W

Sta. 788+42.18 Elev. End 24' x 74.5' = 1588.62  
 Long RCP S.C. 78.0' R.I. - E. Elev = 1588.62  
 Sta. 785+62.80 @ Consume  
 X-ING - CNS  
 Sta. 785+82.23 @ 4'-W-P High  
 Tension CH X-ING - Low Wire = 1171.71 - Western Farmers  
 Sta. 785+89.89 @ Median Inlet  
 21' R.I. - Top Grade = 1142.78  
 Elev. 24' RCP In W = 1537.88  
 Elev. 24' RCP Out E = 1537.71  
 Sta. 785+88.71 Elev. End 24' x 74.5' = 1588.07  
 Long RCP S.C. 78.0' R.I. - E. Elev = 1588.07  
 Sta. 785+94.31 @ Gravel Inlet  
 27' A.L.L. - Top Grade = 1142.87  
 Elev. 24' RCP Out E = 1588.07



LEGEND:  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-15	781+57	40' right
C-31	787+20	40' left
C-16	791+38	40' right


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 11/17



**SECTION 25  
T-8-N, R-3-W**

Sta. 801+12.18 @ 102x10x14.8' 4"  
 Rwy. RCB X-Depth 73' 4.11' & 75.01' R/L  
 E. Elev. LI = 1122.63 & RI = 1121.62  
 Sta. 801+84.54 @ 24' x 14.8' Long  
 CWP S.D. Ch. 6' - E. Elev. / N =  
 1150.67 & S = 1128.87  
 Sta. 801+82.86 @ Noncon. Inset  
 Ch. 6' Top Choke = 1154.55  
 E. Elev. 24' CWP Choke = 1150.67

Boring	Station	I-35 CL Survey
C-30	797+11	40' left
C-17	801+33	40' right
C-29	807+01	40' left

Stations and offsets estimated from plans provided by Olsson Associates


**LEGEND:**  
 I-35 RECONSTRUCTION

**RED ROCK  
CONSULTING**

PO Box 30591  
 Edmond, Oklahoma 73003  
 (405) 562-3328

**BORING LOCATION DIAGRAM**  
 I-35 PAVEMENT AND SUBGRADE SURVEY  
 MCCLAIN COUNTY, OKLAHOMA  
 J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 12/17



Boring	Station	I-35 CL Survey
C-18	813+93	40' right
C-28	821+87	40' left


Stations and offsets estimated from plans provided by Olsson Associates

## RED ROCK CONSULTING

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 13/17



Boring	Station	I-35 CL Survey
C-19	828+73	40' right
C-27	836+73	40' left

Stations and offsets estimated from plans provided by Olsson Associates


**LEGEND:**  
 I-35 RECONSTRUCTION

## RED ROCK CONSULTING

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 14/17



**LEGEND:**  
 I-35 RECONSTRUCTION

Boring	Station	I-35 CL Survey
C-20	843+61	40' right
C-26	851+52	40' left


Stations and offsets estimated from plans provided by Olsson Associates

## RED ROCK CONSULTING

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAINE COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 15/17



Boring	Station	I-35 CL Survey
C-21	860+17	40' right
C-25	866+41	40' left
C-22	868+53	40' right


Stations and offsets estimated from plans provided by Olsson Associates

**RED ROCK  
CONSULTING**

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mngr:	EDC	RRC Project No. 22118
Designed By:	DLW	Scale: NOT TO SCALE
Checked By:	JWB	Date: 1/11/2023
Approved By:	JWB	Page No: 16/17



Boring	Station	I-35 CL Survey
C-24	871+41	40' left
C-23	875+98	40' right

Stations and offsets estimated from plans provided by Olsson Associates

## RED ROCK CONSULTING

PO Box 30591  
Edmond, Oklahoma 73003  
(405) 562-3328

**BORING LOCATION DIAGRAM**  
I-35 PAVEMENT AND SUBGRADE SURVEY  
DISTRICT 3, MCCLAIN COUNTY, OKLAHOMA  
J/P 35589(04)

Project Mgr:	EDC	RRC Project No.	22118
Designed By:	DLW	Scale:	NOT TO SCALE
Checked By:	JWB	Date:	1/11/2023
Approved By:	JWB	Page No:	17/17

## **APPENDIX B**

Surveyed By: Dawson Wiseman  
 Date Surveyed: December 16, 19, 20, 27 and 28, 2022



RRC Project No: 22118  
 J/P No: 35589(04)  
 Location: McClain County, Oklahoma

Pavement Core Data and Subgrade Soils Chart

Boring	Field No.	Soil Group	Station	I-35 CL	Description	Depth (in)	LL	PI	Percent Passing				OSI	MC %	Notes
									# 4	# 10	# 40	# 200			
C-1			640+24	40' right	15" ASPHALT CONCRETE	0-15			tack layer at 11 inches						•Minor severity transverse cracking
					7" CEMENT STABILIZED SUBGRADE	15-22									
	1A	A-4(0)			SANDY SILTY CLAY (CL-ML), brown	22-46	22	5	99	98	89	53.9	4.0	19	
	1B				SANDY SILTY CLAY (CL-ML), red	46-58								16	
C-2			652+91	40' right	16" ASPHALT CONCRETE	0-16			separation at 8 inches, tack layer at 11 inches						
					8" CEMENT STABILIZED SUBGRADE	16-24									
	2A				SILTY, CLAYEY SAND (SC-SM), brown	24-42								13	
	2B	A-4(1)			SANDY SILTY CLAY (CL-ML), reddish brown	42-60	21	7	99	99	88	60.2	5.4	11	
C-3			662+06	40' right	15" ASPHALT CONCRETE	0-15			separation at 3, 8 and 11 1/2 inches, minor stripping at 3, 8 and 11 1/2 to 15 inches						
					8" CEMENT STABILIZED SUBGRADE	15-23								14	
	3A				SANDY SILTY CLAY (CL-ML), brown	23-41									
	3B	A-4(1)			SANDY SILTY CLAY (CL-ML), reddish brown	41-59	20	7	98	97	89	58.8	5.2	12	
C-4			672+36	40' right	14 1/2" ASPHALT CONCRETE	0-14.5			separation at 6 1/2 inches, tack layer at 10 1/2 inches						•Minor severity transverse cracking
					6" CEMENT STABILIZED SUBGRADE	14.5-20.5									
	4A	A-4(0)			SILTY, CLAYEY SAND (SC-SM), reddish brown	20.5-50.5	19	5	100	99	91	47.1	2.8	12	
					*Auger refusal at 50.5 inches										
C-5			682+54	40' right	14" ASPHALT CONCRETE	0-14			tack layer at 11 inches						
					8" CEMENT STABILIZED SUBGRADE	14-22									
	5A	A-4(0)			SILTY, CLAYEY SAND (SC-SM), brown	22-40	20	4	99	97	83	44.2	2.1	14	
	5B				SANDY LEAN CLAY (CL), reddish brown	40-52								16	
					*Auger refusal at 52 inches										
C-6			690+04	40' right	14" ASPHALT CONCRETE	0-14			tack layer at 10 inches						
					8" CEMENT STABILIZED SUBGRADE	14-22									
	6A				CLAYEY SAND (SC), brown	22-40								14	
	6B	A-6(9)			LEAN CLAY with SAND (CL), brown	40-58	29	15	99	99	96	77.4	11.8	18	
C-7			701+90	C-7	14 1/2" ASPHALT CONCRETE	0-14.5			separation at 2 inches, tack layer at 9 inches						•Minor severity longitudinal cracking
					4 1/2" CEMENT STABILIZED SUBGRADE	14.5-19									
	7A	A-4(1)			CLAYEY SAND (SC), brown	19-55	21	10	97	95	81	45.9	4.2	13	







Surveyed By: Dawson Wiseman  
 Date Surveyed: December 16, 19, 20, 27 and 28, 2022



RRC Project No: 22118  
 J/P No: 35589(04)  
 Location: McClain County, Oklahoma

Pavement Core Data and Subgrade Soils Chart

Boring	Field No.	Soil Group	Station	I-35 CL	Description	Depth (in)	LL	PI	Percent Passing				OSI	MC %	Notes
									# 4	# 10	# 40	# 200			
C-27			836+73	40' left	12" ASPHALT CONCRETE	0-12			tack layer at 9 inches						Recent asphalt overlay
					8" AGGREGATE BASE	12-20									
	27A				SILTY SAND with GRAVEL (SM), light brown	20-32							6		
	27B	A-4(0)			SANDY SILT (ML), brown	32-56	NV	NP	100	99	92	51.3	0.0	10	
C-28			821+87	40' left	11" ASPHALT CONCRETE	0-11			separation at 5 1/2 inches						Recent asphalt overlay
					6" AGGREGATE BASE	11-17									
	28A	A-2-4			SILTY SAND (SM), brown	17-41	NV	NP	94	90	75	30.4	0.0	6	
	28B				LEAN CLAY with SAND (CL), brown	41-53								12	
C-29			807+01	40' left	13" ASPHALT CONCRETE	0-13			separation at 8 1/2 inches						Recent asphalt overlay
					6" CEMENT STABILIZED SUBGRADE	13-19									
	29A				SILTY SAND (SM), brown	19-43								13	
	29B	A-4(5)			LEAN CLAY with SAND(CL), dark brown	43-55	24	9	100	100	96	78.1	8.4	14	
C-30			797+11	40' left	11" ASPHALT CONCRETE	0-11			separation at 6 1/2 inches, severe stripping from 8 to 11 inches						Recent asphalt overlay
					8" CEMENT STABILIZED SUBGRADE	11-19									
	30A				SILTY SAND (SM), brown	19-31								12	
	30B	A-4(0)			SILTY, CLAYEY SAND (SC-SM), brown	31-43	19	4	99	99	90	46.3	2.3	9	
	30C				SANDY LEAN CLAY (CL), brown	43-55								15	
C-31			787+20	40' left	12" ASPHALT CONCRETE	0-12			separation at 4 1/2 inches, tack layer at 7 inches						Recent asphalt overlay
					6 1/2" CEMENT STABILIZED SUBGRADE	12-18.5									
	31A				CLAYEY SAND (SC), brown	18.5-42.5								12	
	31B	A-4(1)			SANDY SILTY CLAY (CL-ML), dark brown to black	42.5-54.5	21	5	100	99	93	67.6	5.4	13	
C-32			777+24	40' left	11 1/2" ASPHALT CONCRETE	0-11.5			tack layer at 7 inches						Recent asphalt overlay
					6" CEMENT STABILIZED SUBGRADE	11.5-17.5									
	32A				SILTY, CLAYEY SAND (SC-SM), brown	17.5-29.5								16	
	32B	A-6(6)			LEAN CLAY with SAND (CL), brown	29.5-53.5	25	11	100	99	95	74.7	9.4	15	

Surveyed By: Dawson Wiseman  
 Date Surveyed: December 16, 19, 20, 27 and 28, 2022



RRC Project No: 22118  
 J/P No: 35589(04)  
 Location: McClain County, Oklahoma

Pavement Core Data and Subgrade Soils Chart

Boring	Field No.	Soil Group	Station	I-35 CL	Description	Depth (in)	LL	PI	Percent Passing				OSI	MC %	Notes
									# 4	# 10	# 40	# 200			
C-33			767+10	40' left	11" ASPHALT CONCRETE	0-11			tack layer at 6 inches						•Recent asphalt overlay
					7" CEMENT STABILIZED SUBGRADE	11-18									
	33A				SILTY SAND (SM), light brown	18-42								13	
	33B	A-4(1)			SANDY SILTY CLAY (CL-ML), light brown	42-54	20	6	100	99	92	63.5	5.2	14	
C-34			757+26	40' left	15" ASPHALT CONCRETE	0-15			tack layer at 6 inches, separation at 11 inches						•Minor severity transverse cracking
					5" CEMENT STABILIZED SUBGRADE	15-20									
	34A				SILTY SAND (SM), brown	20-44								9	
	34B	A-4(0)			SILTY, CLAYEY SAND (SC-SM), reddish brown	44-56	20	6	99	98	86	47.6	3.2	13	
C-35			747+34	40' left	14" ASPHALT CONCRETE	0-14			separation at 7 inches, tack layer at 9 1/2 inches						•Minor severity transverse cracking
					7" CEMENT STABILIZED SUBGRADE	14-21									
	35A	A-2-4			SILTY SAND (SM), brown	21-39	NV	NP	98	96	81	31.4	0.0	14	
	35B				SANDY LEAN CLAY (CL), brown	39-50								17	
C-36			737+44	40' left	15 1/2" ASPHALT CONCRETE	0-15.5			separation at 2 1/2 and 8 inches, tack layer at 11 inches						•Minor severity transverse cracking
					7" CEMENT STABILIZED SUBGRADE	15.5-22.5									
	36A				SILTY SAND (SM), brown	22.5-46.5								12	
	36B	A-4(4)			SANDY LEAN CLAY (CL), brown	46.5-58.5	24	10	100	99	93	68.3	8.0	14	
C-37			727+60	40' left	14 1/2" ASPHALT CONCRETE	0-14.5			separation at 2 1/2 inches, tack layer at 10 inches						•Minor severity transverse cracking
					7 1/2" CEMENT STABILIZED SUBGRADE	14.5-22									
	37A	A-4(0)			SILTY SAND (SM), reddish brown	22-46	NV	NP	100	98	85	38.2	0.0	11	
	37B				SANDY LEAN CLAY (CL), reddish brown	46-52								11	
					*Auger refusal at 52 inches										
C-38			717+64	40' left	14" ASPHALT CONCRETE	0-14			separation at 3 inches, tack layer at 10 1/2 inches						
					7 1/2" CEMENT STABILIZED SUBGRADE	14-21.5									
	38A				SILTY SAND (SM), brown	21.5-51.5								13	
	38B	A-4(2)			SANDY LEAN CLAY (CL), brown	51.5-57.5	23	9	100	99	90	57.3	6.2	13	



Surveyed By: Dawson Wiseman  
 Date Surveyed: December 16, 19, 20, 27 and 28, 2022



RRC Project No: 22118  
 J/P No: 35589(04)  
 Location: McClain County, Oklahoma

Pavement Core Data and Subgrade Soils Chart

Boring	Field No.	Soil Group	Station	I-35 CL	Description	Depth (in)	LL	PI	Percent Passing				OSI	MC %	Notes
									# 4	# 10	# 40	# 200			
C-45			648+15	40' left	14 3/4" ASPHALT CONCRETE	0-14.75			separation at 8 inches, tack layer at 10 inches						•Minor severity transverse cracking
					8 1/2" CEMENT STABILIZED SUBGRADE	14.75-23.25									
	45A	A-4(0)			SILTY, CLAYEY SAND (SC-SM), reddish brown	23.25-53.25	19	5	99	98	82	42.8	2.1	13	
	45B				SANDY LEAN CLAY (CL), reddish brown	53.25-59.25								10	
C-46			633+22	40' left	16" ASPHALT CONCRETE	0-16			separation at 10 1/2 inches						•Minor severity transverse cracking
					8" CEMENT STABILIZED SUBGRADE	16-24									
	46A				SILTY, CLAYEY SAND (SC-SM), reddish brown	24-54								14	
	46B	A-4(5)			LEAN CLAY with SAND (CL), brown	54-60	25	10	100	99	95	76.1	9.0	16	

## **APPENDIX C**

Coring  
C-1

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10	Type B
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 11 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' right	<hr/>			
Core	C-1	Total Core Thickness		15	
Station	640+24				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.107261	2	CEMENT STABILIZED SUBGRADE	7	AASHTO
Longitude	-97.434100	3	SANDY SILTY CLAY (CL-ML), brown	24	OSI
		4	SANDY SILTY CLAY (CL-ML), red	12	A-4(0) 4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



Coring  
C-2

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	11	Type B, separation at 8 inches
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 12 inches
County	McClain		Asphalt Concrete	3	Type B
I-35 CL	40' right				
Core	C-2				
Station	652+91				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.109989				
Longitude	-97.436700				
			Total Core Thickness	16	
					AASHTO
					OSI
		2	CEMENT STABILIZED SUBGRADE	8	
		3	SILTY, CLAYEY SAND (SC-SM), brown	18	
		4	SANDY SILTY CLAY (CL-ML), reddish brown	18	A-4(1) 5.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-3

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10 1/2	Type B, separation and minor stripping at 3 and 8 inches
Location	I-35		Asphalt Concrete	1	Type C, separation at 11 1/2 inches
County	McClain		Asphalt Concrete	3 1/2	Type B, minor stripping from 11 1/2 to 15 inches
I-35 CL	40' right				
Core	C-3				
Station	662+06				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.112131				
Longitude	-97.438600				
		Total Core Thickness		15	
					<u>AASHTO</u> <u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	8	
		3	SANDY SILTY CLAY (CL-ML), brown	18	
		4	SANDY SILTY CLAY (CL-ML), reddish brown	18	A-4(1)      5.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.     P.C.C.     Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping     Separation     N/A

Honeycomb or "D" Cracking in PCC:     Honeycomb     "D"     N/A

Stabilized Subgrade Beneath Pavement or Sub-base?     Yes     No     Unknown



Coring  
C-4

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	9 1/2	Type B, separation at 6 1/2 inches
Location	I-35		Asphalt Concrete	2 1/2	Type C, tack layer at 10 1/2 inches
County	McClain		Asphalt Concrete	2 1/2	Type B
I-35 CL	40' right		<hr/>		
Core	C-4		Total Core Thickness	14 1/2	
Station	672+36				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.114300	2	CEMENT STABILIZED SUBGRADE	6	<u>AASHTO</u> <u>OSI</u>
Longitude	-97.440600	3	SILTY, CLAYEY SAND (SC-SM), reddish brown	30	A-4(0)      2.8
			*Auger refusal at 50.5 inches		

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:    Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:    Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?    Yes    No    Unknown



**Coring  
C-5**

Top



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10	Type B
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 11 inches
County	McClain		Asphalt Concrete	2	Type B
I-35 CL	40' right		<hr/>		
Core	C-5		Total Core Thickness	14	
Station	682+54				<u>AASHTO</u> <u>OSI</u>
Coring Location	Outer Wheel Path	2	CEMENT STABILIZED SUBGRADE	8	
Lane Direction	NB	3	SILTY, CLAYEY SAND (SC-SM), brown	18	A-4(0)      2.1
Latitude	35.116489	4	SANDY LEAN CLAY (CL), reddish brown	12	
Longitude	-97.442700		*Auger refusal at 52 inches		

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:    Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:    Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?    Yes    No    Unknown



Coring  
C-6

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' right  
 Core C-6  
 Station 690+04  
 Coring Location Outer Wheel Path  
 Lane Direction NB  
 Latitude 35.118111  
 Longitude -97.444200

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	9	Type B	
	Asphalt Concrete	2 1/2	Type C, tack layer at 10 inches	
	Asphalt Concrete	2 1/2	Type B	
<b>Total Core Thickness</b>		<b>14</b>	<u>AASHTO</u>	<u>OSI</u>
2	CEMENT STABILIZED SUBGRADE	8		
3	CLAYEY SAND (SC), brown	18		
4	LEAN CLAY with SAND (CL), brown	18	A-6(9)	11.8

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-7

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	8	Type B, separation at 2 inches
Location	I-35		Asphalt Concrete	2 1/2	Type C, tack layer at 9 inches
County	McClain		Asphalt Concrete	4	Type B
I-35 CL	40' right				
Core	C-7				
Station	701+90				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.120811				
Longitude	-97.446700				
			Total Core Thickness	14 1/2	
		2	CEMENT STABILIZED SUBGRADE	4 1/2	AASHTO
		3	CLAYEY SAND (SC), brown	36	OSI
					A-4(1)
					4.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-8

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' right  
 Core C-8  
 Station 712+30  
 Coring Location Outer Wheel Path  
 Lane Direction NB  
 Latitude 35.123031  
 Longitude -97.448700

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	10 1/4	Type B, separation at 3 inches	
	Asphalt Concrete	2	Type C, tack layer at 11 inches	
	Asphalt Concrete	1 3/4	Type A	
<b>Total Core Thickness</b>		<b>14</b>	<b>AASHTO</b>	<b>OSI</b>
2	CEMENT STABILIZED SUBGRADE	10		
3	SILTY SAND (SM), brown	24	A-4(0)	0
4	SANDY LEAN CLAY (CL), reddish brown	12		

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-9

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10	Type B, separation at 3 inches
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 11 inches
County	McClain		Asphalt Concrete	2 1/2	Type A
I-35 CL	40' right				
Core	C-9				
Station	722+10				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.125150				
Longitude	-97.450700				
			Total Core Thickness	14 1/2	
		2	CEMENT STABILIZED SUBGRADE	8	AASHTO
		3	SANDY SILT (ML), brown	30	OSI
		4	SANDY LEAN CLAY (CL), brown	6	A-4(2) 6.3

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-10

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' right  
 Core C-10  
 Station 731+99  
 Coring Location Outer Wheel Path  
 Lane Direction NB  
 Latitude 35.127319  
 Longitude -97.452700

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	8	Type B, separation at 2 1/2 inches	
	Asphalt Concrete	2	Type C, tack layer at 9 inches	
	Asphalt Concrete	4	Type A	
Total Core Thickness		14		
2	CEMENT STABILIZED SUBGRADE	9	<u>AASHTO</u>	<u>OSI</u>
3	SILTY SAND (SM), brown	18	A-2-4	0.59
4	SANDY LEAN CLAY (CL), reddish brown	18		

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-11

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' right  
 Core C-11  
 Station 741+97  
 Coring Location Outer Wheel Path  
 Lane Direction NB  
 Latitude 35.129511  
 Longitude -97.454770

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	8 1/2	Type B, separation at 2 1/2 inches	
	Asphalt Concrete	2 1/2	Type C, tack layer at 9 1/2 inches	
	Asphalt Concrete	2 1/2	Type A	
<b>Total Core Thickness</b>		<b>13 1/2</b>	<u>AASHTO</u>	<u>OSI</u>
2	CEMENT STABILIZED SUBGRADE	10		
3	SILTY, CLAYEY SAND (SC-SM), brown	24		
4	LEAN CLAY with SAND (CL), reddish brown	12	A-6(12)	14.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-12

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	9 1/2	Type B, separation at 2 1/2 and 8 inches, moderate stripping at 8 inches
Location	I-35		Asphalt Concrete	2 1/2	Type C, tack layer at 10 inches
County	McClain		Asphalt Concrete	3 1/2	Type A
I-35 CL	40' right		<hr/>		
Core	C-12		Total Core Thickness	15 1/2	
Station	752+06				<u>AASHTO</u> <u>OSI</u>
Coring Location	Outer Wheel Path	2	CEMENT STABILIZED SUBGRADE	10	
Lane Direction	NB	3	SILTY, CLAYEY SAND (SC-SM), brown	24	
Latitude	35.131669	4	SANDY LEAN CLAY (CL), brown	12	A-4(4)      8.2
Longitude	-97.456700				

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:    Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?    Yes    No    Unknown



Coring  
C-13

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	10	Type B, separation and minor stripping at 9 1/2 inches
County	McClain		Asphalt Concrete	3	Type C, tack layer at 11 inches
I-35 CL	40' right		Asphalt Concrete	3 1/2	Type A
Core	C-13	<hr/>			
Station	761+72	Total Core Thickness		16 1/2	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	NB				<u>OSI</u>
Latitude	35.133831	2	CEMENT STABILIZED SUBGRADE	8	
Longitude	-97.458700	3	SILTY, CLAYEY SAND (SC-SM), brown	24	A-4(0)
		4	SANDY LEAN CLAY (CL), brown	12	1.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:    Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?    Yes    No    Unknown



Coring  
C-14

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	5	Type B, separation at 10 inches
Location	I-35		Asphalt Concrete	2 1/2	Type C, tack layer at 11 inches
County	McClain		Asphalt Concrete	5 1/2	Type A
I-35 CL	40' right		*3 inches destroyed in core barrel		
Core	C-14		<hr/>		
Station	771+57		Total Core Thickness	13	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	NB	2	CEMENT STABILIZED SUBGRADE	6	<u>OSI</u>
Latitude	35.136000	3	SILTY SAND (SM), brown	33	A-2-4
Longitude	-97.460700	4	LEAN CLAY with SAND (CL), brown	3	0

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

**Coring  
C-15**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	6	Type B, separation at 4 1/4 inches
County	McClain		Asphalt Concrete	2	Type C, tack layer at 7 inches
I-35 CL	40' right		Asphalt Concrete	4	Type A
Core	C-15				
Station	781+57				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.138181				
Longitude	-97.462700				
		Total Core Thickness		12	
					<u>AASHTO</u>
		2	CEMENT STABILIZED SUBGRADE	9	<u>OSI</u>
		3	SANDY SILT (ML), brown	24	
		4	LEAN CLAY with SAND (CL), brown	12	A-6(7) 10.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK  
CONSULTING**

Coring  
C-16

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' right  
 Core C-16  
 Station 791+38  
 Coring Location Outer Wheel Path  
 Lane Direction NB  
 Latitude 35.140350  
 Longitude -97.464700

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	5	Type B	
	Asphalt Concrete	2 1/2	Type C, tack layer at 6 inches	
	Asphalt Concrete	3 1/2	Type A	
Total Core Thickness		11		
2	CEMENT STABILIZED SUBGRADE	7	<u>AASHTO</u>	<u>OSI</u>
3	SANDY SILT (ML), light brown	18	A-4(0)	2.8
4	SANDY SILT (ML), brown	18		

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-17

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	5	Type B
Location	I-35		Asphalt Concrete	2 1/2	Type C, separation at 6 1/4 inches
County	McClain		Asphalt Concrete	3 1/2	Type A
I-35 CL	40' right				
Core	C-17				
Station	801+33				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.142500				
Longitude	-97.466700				
			Total Core Thickness	11	
					<u>AASHTO</u> <u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	10	
		3	SILTY SAND (SM), light brown	18	
		4	LEAN CLAY with SAND (CL), dark brown	18	A-4(6)      9.2

\*Asphalt type based on visual observation only

CORE DATA	
Surface Material Type:	<input checked="" type="checkbox"/> A.C. <input type="checkbox"/> P.C.C. <input type="checkbox"/> Continuously Reinforced Concrete
Stripping and/or Separation:	<input type="checkbox"/> Stripping <input checked="" type="checkbox"/> Separation <input type="checkbox"/> N/A
Honeycomb or "D" Cracking in PCC:	<input type="checkbox"/> Honeycomb <input type="checkbox"/> "D" <input checked="" type="checkbox"/> N/A
Stabilized Subgrade Beneath Pavement or Sub-base?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-18

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	6 1/2	Type B, separation at 2 1/2 inches
Location	I-35		Asphalt Concrete	2 1/2	Type C, tack layer at 7 1/4 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' right	<hr/>			
Core	C-18	Total Core Thickness			
Station	813+93			12	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	NB	2	CEMENT STABILIZED SUBGRADE	10	<u>OSI</u>
Latitude	35.145219	3	SANDY SILT (ML), light brown	24	A-4(0)
Longitude	-97.469300	4	SANDY LEAN CLAY (CL), brown	12	2.8

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown



Coring  
C-19

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	5 1/2	Type B
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 7 1/4 inches
County	McClain		Asphalt Concrete	4	Type A
I-35 CL	40' right				
Core	C-19				
Station	828+73				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.148461				
Longitude	-97.472300				
			Total Core Thickness	11 1/2	
					<u>AASHTO</u> <u>OSI</u>
		2	AGGREGATE BASE	10	
		3	SILTY SAND (SM), dark brown, organic smell	24	
		4	LEAN CLAY with SAND (CL), dark brown, organic smell	12	A-4(4)      7.8

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-20

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	5	Type B
Location	I-35		Asphalt Concrete	1/2	Type C, tack layer at 5 1/2 inches
County	McClain		Asphalt Concrete	2	Type B
I-35 CL	40' right		Asphalt Concrete	2 1/2	Type A
Core	C-20				
Station	843+61				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.135053				
Longitude	-97.475300				
			Total Core Thickness	10	
					<u>AASHTO</u> <u>OSI</u>
		2	AGGREGATE BASE	6	
		3	SILTY SAND (SM), light brown	24	A-2-4      0
		4	SILTY, CLAYEY SAND (SC-SM), dark brown, organic smell	12	

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-21

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	4	Type B,
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 5 inches
County	McClain		Asphalt Concrete	3 1/4	Type A
I-35 CL	40' right		<hr/>		
Core	C-21		Total Core Thickness	9 1/4	
Station	860+17				
Coring Location	Outer Wheel Path				
Lane Direction	NB	2	AGGREGATE BASE	8	<u>AASHTO</u>
Latitude	35.155275	3	SILTY, CLAYEY SAND (SC-SM), light brown	24	<u>OSI</u>
Longitude	-97.478611	4	CLAYEY SAND (SC), dark brown	6	A-4(1)
			*Auger refusal at 47.25 inches		4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-22

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	8	Type B, separation and deterioration at 2 1/2 inches
Location	I-35		Asphalt Concrete	2	Type C, separation at 9 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' right				
Core	C-22				
Station	868+53				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.157150				
Longitude	-97.480400				
			Total Core Thickness	13	
		2	AGGREGATE BASE	6	AASHTO
		3	SILTY, CLAYEY SAND (SC-SM), light brown	12	OSI
			*Auger refusal at 31 inches		0.91

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



Coring  
C-23

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	5	Type B,
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 5 1/2 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' right				
Core	C-23				
Station	875+98				
Coring Location	Outer Wheel Path				
Lane Direction	NB				
Latitude	35.158769				
Longitude	-97.481900				
			Total Core Thickness	10	
		2	AGGREGATE BASE	10	AASHTO
		3	SILTY, CLAYEY SAND with GRAVEL (SC-SM), light brown	12	A-1-b
			*Auger refusal at 32 inches		0.25

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING

Coring  
C-24

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	5 1/2	Type B
County	McClain		Asphalt Concrete	2 1/2	Type C
I-35 CL	40' left		Asphalt Concrete	3	Type A, separation at 9 1/2 inches
Core	C-24	<hr/>			
Station	871+41	Total Core Thickness		11	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	SB	2	AGGREGATE BASE	8	<u>OSI</u>
Latitude	35.157669	3	SILTY SAND (SM), brown	24	
Longitude	-97.481100	4	SILTY CLAY with SAND (CL-ML), reddish brown	12	A-4(3) 7

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



Coring  
C-25

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	6	Type B
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 6 1/2 inches
County	McClain		Asphalt Concrete	3	Type A, separation at 9 inches
I-35 CL	40' left	<hr/>			
Core	C-25	Total Core Thickness		11	
Station	866+41				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.156581	2	AGGREGATE BASE	8	<u>AASHTO</u> <u>OSI</u>
Longitude	-97.480100	3	SILTY SAND with GRAVEL (SM), brown	24	
		4	SILTY CLAY with SAND (CL-ML), brown	12	A-4(3)      7.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.     P.C.C.     Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping     Separation     N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb     "D"     N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes     No     Unknown



**Coring  
C-26**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	3 1/2	Type B
Location	I-35		Asphalt Concrete	3/4	Type C, separation and minor stripping at 4 1/4 inches
County	McClain		Asphalt Concrete	5	Type A, deterioration at 8 inches
I-35 CL	40' left				
Core	C-26				
Station	851+52				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.153331				
Longitude	-97.477100				
			Total Core Thickness	9 1/4	
		2	AGGREGATE BASE	8	
		3	SILTY SAND with GRAVEL (SM), brown	12	AASHTO A-2-4
		4	SANDY SILT (ML), brown	24	OSI 0

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



Coring  
C-27

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	8	Type B
Location	I-35		Asphalt Concrete	1	Type C, tack layer at 9 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' left				
Core	C-27				
Station	836+73				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.150069				
Longitude	-97.474100				
		Total Core Thickness		12	
					<u>AASHTO</u>
					<u>OSI</u>
		2	AGGREGATE BASE	8	
		3	SILTY SAND with GRAVEL (SM), light brown	12	
		4	SANDY SILT (ML), brown	24	A-4(0) 0

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**



Coring  
C-28

Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20,  
27 and 28, 2022

**CORE LOG**

RRC No. 22118  
 State Aid Project No. 35589(04)  
 Location I-35  
 County McClain  
 I-35 CL 40' left  
 Core C-28  
 Station 821+87  
 Coring Location Outer Wheel Path  
 Lane Direction SB  
 Latitude 35.146819  
 Longitude -97.471100

**CORE LAYER DATA (FROM TOP TO BOTTOM)**

Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics	
1	Asphalt Concrete	5	Type B	
	Asphalt Concrete	2 1/4	Type C, separation at 5 1/2 inches	
	Asphalt Concrete	3 3/4	Type A	
Total Core Thickness		11		
2	AGGREGATE BASE	6		
3	SILTY SAND (SM), brown	24	A-2-4	0
4	LEAN CLAY with SAND (CL), brown	12		

AASHTO

OSI

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete  
 Stripping and/or Separation:  Stripping  Separation  N/A  
 Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A  
 Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
CONSULTING



**Coring  
C-29**

**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20,  
27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	7 1/2	Type B
County	McClain		Asphalt Concrete	2 1/2	Type C, separation at 8 1/2 inches
I-35 CL	40' left		Asphalt Concrete	3	Type A
Core	C-29				
Station	807+01				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.143561				
Longitude	-97.468100				
		Total Core Thickness		13	
					<u>AASHTO</u>
					<u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	6	
		3	SILTY SAND (SM), brown	24	
		4	LEAN CLAY with SAND (CL), dark brown	12	A-4(5) 8.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK  
CONSULTING**

**Coring  
C-30**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	5 1/2	Type B
County	McClain		Asphalt Concrete	1 1/2	Type C, separation at 6 1/2 inches
I-35 CL	40' left		Asphalt Concrete	4	Type A, severe stripping from 8 to 11 inches
Core	C-30				
Station	797+11				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.141389				
Longitude	-97.466100				
			Total Core Thickness	11	
					<u>AASHTO</u> <u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	8	
		3	SILTY SAND (SM), brown	12	
		4	SILTY, CLAYEY SAND (SC-SM), brown	12	A-4(0)      2.3
		5	SANDY LEAN CLAY (CL), brown	12	

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown



**Coring  
C-31**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	6	Type B, separation at 4 1/2 inches
County	McClain		Asphalt Concrete	2 1/2	Type C, tack layer at 7 inches
I-35 CL	40' left		Asphalt Concrete	3 1/2	Type A
Core	C-31				
Station	787+20				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.139219				
Longitude	-97.464100				
			<b>Total Core Thickness</b>	<b>12</b>	
					<u>AASHTO</u>
					<u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	6 1/2	
		3	CLAYEY SAND (SC), brown	24	
		4	SANDY SILTY CLAY (CL-ML), dark brown to black	12	A-4(1) 5.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK  
CONSULTING**

Coring  
C-32

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	6	Type B
County	McClain		Asphalt Concrete	2 1/2	Type C, tack layer at 7 inches
I-35 CL	40' left		Asphalt Concrete	3	Type A
Core	C-32				
Station	777+24				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.137050				
Longitude	-97.462100				
			Total Core Thickness	11 1/2	
					<u>AASHTO</u> <u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	6	
		3	SILTY, CLAYEY SAND (SC-SM), brown	12	
		4	LEAN CLAY with SAND (CL), brown	24	A-6(6)      9.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown





**Coring  
C-33**

**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	5 1/2	Type B
County	McClain		Asphalt Concrete	2	Type C, tack layer at 6 inches
I-35 CL	40' left		Asphalt Concrete	3 1/2	Type A
Core	C-33				
Station	767+10				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.134881				
Longitude	-97.460000				
			<b>Total Core Thickness</b>	<b>11</b>	
					<u>AASHTO</u>
					<u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	7	
		3	SILTY SAND (SM), light brown	24	
		4	SANDY SILTY CLAY (CL-ML), light brown	12	A-4(1) 5.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-34

Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

Top



CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	10	Type B
County	McClain		Asphalt Concrete	1	Type C, tack layer at 6 inches
I-35 CL	40' left		Asphalt Concrete	4	Type A, separation at 11 inches
Core	C-34		*4 inches destroyed in barrel		
Station	757+26		<hr/>		
Coring Location	Outer Wheel Path		Total Core Thickness	15	
Lane Direction	SB				<u>AASHTO</u>
Latitude	35.132711	2	CEMENT STABILIZED SUBGRADE	5	<u>OSI</u>
Longitude	-97.458000	3	SILTY SAND (SM), brown	24	
		4	SILTY, CLAYEY SAND (SC-SM), reddish brown	12	A-4(0)      3.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.     P.C.C.     Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping     Separation     N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb     "D"     N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes     No     Unknown



Coring  
C-35

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	9	Type B, separation at 7 inches
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 9 1/2 inches
County	McClain		Asphalt Concrete	3	Type A
I-35 CL	40' left				
Core	C-35				
Station	747+34				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.130550				
Longitude	-97.456000				
			Total Core Thickness	14	
					<u>AASHTO</u> <u>OSI</u>
		2	CEMENT STABILIZED SUBGRADE	7	
		3	SILTY SAND (SM), brown	18	A-2-4      0
		4	SANDY LEAN CLAY (CL), brown	18	

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.     P.C.C.     Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping     Separation     N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb     "D"     N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes     No     Unknown



Coring  
C-36

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10	Type B, separation at 2 1/2 and 8 inches
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 11 inches
County	McClain		Asphalt Concrete	3 1/2	Type A
I-35 CL	40' left				
Core	C-36				
Station	737+44				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.128369				
Longitude	-97.454000				
		Total Core Thickness		15 1/2	
					<u>AASHTO</u>
		2	CEMENT STABILIZED SUBGRADE	7	<u>OSI</u>
		3	SILTY SAND (SM), brown	24	
		4	SANDY LEAN CLAY (CL), brown	12	A-4(4) 8

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

**Coring  
C-37**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	9	Type B, separation at 2 1/2 inches
County	McClain		Asphalt Concrete	2 1/2	Type C, tack layer at 10 inches
I-35 CL	40' left		Asphalt Concrete	3	Type A
Core	C-37				
Station	727+60				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.126200				
Longitude	-97.452000				
		Total Core Thickness		14 1/2	
					<u>AASHTO</u>
		2	CEMENT STABILIZED SUBGRADE	7 1/2	<u>OSI</u>
		3	SILTY SAND (SM), reddish brown	24	A-4(0)
		4	SANDY LEAN CLAY (CL), reddish brown	6	0
		*Auger refusal at 52 inches			

\*Asphalt type based on visual observation only

CORE DATA	
Surface Material Type:	<input checked="" type="checkbox"/> A.C. <input type="checkbox"/> P.C.C. <input type="checkbox"/> Continuously Reinforced Concrete
Stripping and/or Separation:	<input type="checkbox"/> Stripping <input checked="" type="checkbox"/> Separation <input type="checkbox"/> N/A
Honeycomb or "D" Cracking in PCC:	<input type="checkbox"/> Honeycomb <input type="checkbox"/> "D" <input checked="" type="checkbox"/> N/A
Stabilized Subgrade Beneath Pavement or Sub-base?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Unknown

**RED ROCK  
CONSULTING**



Coring  
C-38

Top

Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20,  
27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	9 1/2	Type B, separation at 3 inches
Location	I-35		Asphalt Concrete	2	Type C, tack layer at 10 1/2 inches
County	McClain		Asphalt Concrete	2 1/2	Type A
I-35 CL	40' left		<hr/>		
Core	C-38		Total Core Thickness	14	
Station	717+64				
Coring Location	Outer Wheel Path				
Lane Direction	SB	2	CEMENT STABILIZED SUBGRADE	7 1/2	<u>AASHTO</u> <u>OSI</u>
Latitude	35.124031	3	SILTY SAND (SM), brown	30	
Longitude	-97.450000	4	SANDY LEAN CLAY (CL), brown	6	A-4(2)      6.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown



Coring  
C-39

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	8 3/4	Type B,
Location	I-35		Asphalt Concrete	2	Type C, separation at 9 inches
County	McClain		Asphalt Concrete	3 1/4	Type A
I-35 CL	40' left				
Core	C-39				
Station	707+72				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.121869				
Longitude	-97.448000				
		Total Core Thickness		14	
					<u>AASHTO</u>
		2	CEMENT STABILIZED SUBGRADE	8	<u>OSI</u>
		3	SILTY SAND (SM), brown	18	A-4(0)
		4	SANDY LEAN CLAY (CL), brown	18	0

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown





**Coring  
C-40**

**Top**

**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	7 1/2	Type B,
Location	I-35		Asphalt Concrete	1 1/2	Type C, tack layer at 7 1/2 inches
County	McClain		Asphalt Concrete	3 1/2	Type A
I-35 CL	40' left	<hr/>			
Core	C-40	Total Core Thickness		12 1/2	
Station	693+85				<u>AASHTO</u> <u>OSI</u>
Coring Location	Outer Wheel Path	2	CEMENT STABILIZED SUBGRADE	5	
Lane Direction	SB		*Auger refusal at 17.5 inches		
Latitude	35.118819				
Longitude	-97.445200				

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:    Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:    Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?    Yes    No    Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-41

Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

Top



CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	12	Type B
Location	I-35	Total Core Thickness			
County	McClain			12	
I-35 CL	41' left				
Core	C-41				
Station	687+92				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.117519				
Longitude	-97.444000				
		2	CEMENT STABILIZED SUBGRADE	6	AASHTO
		3	SANDY LEAN CLAY (CL), red	24	OSI
			*Auger refusal at 42 inches		6.7

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



**Coring  
C-42**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	9	Type B, separation at 6 1/2 inches
County	McClain		Asphalt Concrete	2 1/2	Type C, tack layer at 9 3/4 inches
I-35 CL	40' left		Asphalt Concrete	2 1/2	Type A
Core	C-42	<hr/>			
Station	677+79	Total Core Thickness		14	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	SB				<u>OSI</u>
Latitude	35.115339	2	CEMENT STABILIZED SUBGRADE	8	
Longitude	-97.441900	3	SILTY, CLAYEY SAND (SC-SM), brown	24	A-4(0)
		4	SANDY LEAN CLAY (CL), reddish brown	12	2.4

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown





Coring  
C-43

Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20,  
27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	10 1/2	Type B, separation and severe stripping at 7 inches
County	McClain		Asphalt Concrete	3	Type C, tack layer at 11 1/2 inches
I-35 CL	40' left		Asphalt Concrete	2	Type A
Core	C-43				
Station	668+19				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.113189	Total Core Thickness		15 1/2	
Longitude	-97.440000				
		2	CEMENT STABILIZED SUBGRADE	8	
		3	SANDY SILTY CLAY (CL-ML), brown	24	
		4	SANDY LEAN CLAY (CL), reddish brown	12	
					AASHTO
					OSI
					A-4(3)
					7.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK**  
**CONSULTING**

Coring  
C-44

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	10	Type B, separation at 6 1/2 inches
Location	I-35		Asphalt Concrete	2 1/4	Type C, separation and deterioration at 11 inches
County	McClain		Asphalt Concrete	3 1/4	Type A
I-35 CL	40' left	<hr/>			
Core	C-44	Total Core Thickness		15 1/2	
Station	658+08				
Coring Location	Outer Wheel Path				
Lane Direction	SB				
Latitude	35.111019	2	CEMENT STABILIZED SUBGRADE	8	AASHTO
Longitude	-97.437900	3	SANDY SILTY CLAY (CL-ML), brown	18	OSI
		4	SANDY LEAN CLAY (CL), brown	18	A-4(0) 4.2

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown



Coring  
C-45

Top



Surveyed By: Dawson Wiseman

Date Surveyed: December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)	1	Asphalt Concrete	9 1/2	Type B, separation at 8 inches
Location	I-35		Asphalt Concrete	1 1/2	Type C, tack layer at 10 inches
County	McClain		Asphalt Concrete	3 3/4	Type A
I-35 CL	40' left	<hr/>			
Core	C-45	Total Core Thickness		14 3/4	
Station	648+15				<u>AASHTO</u>
Coring Location	Outer Wheel Path	2	CEMENT STABILIZED SUBGRADE	8 1/2	<u>OSI</u>
Lane Direction	SB	3	SILTY, CLAYEY SAND (SC-SM), reddish brown	30	A-4(0)
Latitude	35.108850	4	SANDY LEAN CLAY (CL), reddish brown	6	2.1
Longitude	-97.435900				

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.    P.C.C.    Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping    Separation    N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb    "D"    N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes    No    Unknown



**Coring  
C-46**

**Top**



**Surveyed By:** Dawson Wiseman

**Date Surveyed:** December 16, 19, 20, 27 and 28, 2022

CORE LOG		CORE LAYER DATA (FROM TOP TO BOTTOM)			
RRC No.	22118	Sample No.	Layer Type	Layer Thickness (in.)	Layer Characteristics
State Aid Project No.	35589(04)				
Location	I-35	1	Asphalt Concrete	9 1/2	Type B,
County	McClain		Asphalt Concrete	2 1/2	Type C, separation at 10 1/2 inches
I-35 CL	40' left		Asphalt Concrete	4	Type A
Core	C-46	<hr/>			
Station	633+22		Total Core Thickness	16	
Coring Location	Outer Wheel Path				<u>AASHTO</u>
Lane Direction	SB				<u>OSI</u>
Latitude	35.105589	2	CEMENT STABILIZED SUBGRADE	8	
Longitude	-97.432900	3	SILTY, CLAYEY SAND (SC-SM), reddish brown	30	
		4	LEAN CLAY with SAND (CL), brown	6	A-4(5)
					9

\*Asphalt type based on visual observation only

**CORE DATA**

Surface Material Type:  A.C.  P.C.C.  Continuously Reinforced Concrete

Stripping and/or Separation:  Stripping  Separation  N/A

Honeycomb or "D" Cracking in PCC:  Honeycomb  "D"  N/A

Stabilized Subgrade Beneath Pavement or Sub-base?  Yes  No  Unknown

**RED ROCK  
CONSULTING**

## Pavement Photographs



**Photo #1** Minor severity transverse cracking near C-1.



**Photo #2** No cracking observed near C-2.



**Photo #3** No cracking observed near C-3.



**Photo #4** Minor severity transverse cracking near C-4.




**Photo #5** No cracking observed near C-5.



**Photo #6** No cracking observed near C-6.



**Photo #7** Minor severity longitudinal cracking near C-7.



**Photo #8** No cracking observed near C-8.



**Photo #9** Minor severity transverse cracking near C-9.



**Photo #10** Minor severity transverse cracking near C-10.



**Photo #11** Moderate severity transverse cracking near C-11.




**Photo #12** No cracking observed near C-12.



**Photo #13** No cracking observed near C-13.



**Photo #14** Recent asphalt overlay near C-14.



**Photo #15** Recent asphalt overlay near C-15.



**Photo #16** Recent asphalt overlay near C-16.



**Photo #17** Recent asphalt overlay near C-17.



**Photo #18** Recent asphalt overlay near C-18.



**Photo #19** Recent asphalt overlay near C-19.



**Photo #20** Recent asphalt overlay near C-20.



**Photo #21** Recent asphalt overlay near C-21.



**Photo #22** Recent asphalt overlay near C-22.



**Photo #23** Recent asphalt overlay near C-23.




**Photo #24** Recent asphalt overlay near C-24.



**Photo #25** Recent asphalt overlay near C-25.



**Photo #26** Recent asphalt overlay near C-26.



**Photo #27** Recent asphalt overlay near C-27.



**Photo #28** Recent asphalt overlay near C-28.



**Photo #29** Recent asphalt overlay near C-29.



**Photo #30** Recent asphalt overlay near C-30.



**Photo #31** Recent asphalt overlay near C-31.



**Photo #32** Recent asphalt overlay near C-32.



**Photo #33** Recent asphalt overlay near C-33.



**Photo #34** Minor severity transverse cracking near C-34.




**Photo #35** Minor severity transverse cracking near C-35.



**Photo #36** Minor severity transverse cracking near C-36.




**Photo #37** Minor severity transverse cracking near C-37.



**Photo #38** No cracking observed near C-38.



**Photo #39** No cracking observed near C-39.



**Photo #40** No cracking observed near C-40.



**Photo #41** No cracking observed near C-41.



**Photo #42** No cracking observed near C-42.




**Photo #43** Minor severity transverse cracking near C-43.



**Photo #44** Minor severity transverse cracking near C-44.



**Photo #45** Minor severity transverse cracking near C-45.



**Photo #46** Minor severity transverse cracking near C-46.

## **APPENDIX D**



## **FALLING WEIGHT DEFLECTOMETER MODULUS TESTING**

I-35, McCLAIN COUNTY, OK

### **Prepared for**

*RED ROCK CONSULTING, LLC  
PO Box 30591  
Edmond, OK 73003*

### **Prepared by**

*EINCK, Corp*

### **Maryland Office**

*1850 York Rd, Suite E (REAR)  
Timonium, MD 21093*

### **Oklahoma Office**

*6906 E 191<sup>st</sup> Street S  
Bixby, OK 74008*

**June 23, 2023**



**June 23, 2023**

To: RED ROCK CONSULTING, LLC  
PO Box 30591  
Edmond, OK 73003


Subject: Falling Weight Deflectometer  
I-35 McClain County, Oklahoma

Dear Ms. Coggin,

We are pleased to submit this report summarizing the Falling Weight Deflectometer (FWD) field results conducted on December 06, 2022 on I-35 McClain County (JP35589-04), Oklahoma. The purpose of the FWD survey/testing was to back-calculate the modulus of encountered layers of the tested pavement for the referenced project.

We thank you for giving us the opportunity to work on this project. Should you have any questions or need additional information, please contact us and will be glad to address/provide.

Sincerely,  
EINCK, Corp.



**Naji Khoury, PhD, PE, MBA**  
**Vice President**

---

1850 York Road, Suite E (REAR)  
Timonium, MD 21093

Office: 443 465 6970

Cell: 405 640 8686

e-mail: [info@einckcorp.com](mailto:info@einckcorp.com)



## **Table of Contents**

List of Figures .....	iii
List of Tables .....	iii
1. Introduction.....	4
2. Procedure and Field-Testing Operation .....	4
3. Pavement Structure.....	4
4. Back-calculation Analyses.....	5
5. Limitations.....	9
6. References.....	10
Appendix A – FWD Test Locations	
Appendix B – FWD Field Testing Data	

## **List of Figures**

Figure 1 – Project Section I-35 (Provided by Redrock) .....	4
Figure 2 – NB lane pavement segments, input layer modulus and Poisson’s ratio values for back-calculation.....	6
Figure 3 – SB lane pavement segments, input layer modulus and Poisson’s ratio values for back-calculation.....	6
Figure 4 – NB lane back-calculated modulus versus station locations .....	7
Figure 5 – SB lane back-calculated modulus versus station locations.....	7

## **List of Tables**

Table 1 – Pavement Core Information (provided by RedRock) .....	5
Table 2 – NB lane back-calculation analysis results.....	8
Table 3 – SB lane back-calculation analysis results.....	9



## 1. Introduction

EINCK, Corp, conducted falling weight deflectometer (FWD) testing on I-35 in McClain County, Oklahoma. The testing section extends approximately 4.7 miles, refer to Figure 1. The purpose of the study was to perform FWD survey and estimate pavement section moduli using back-calculation technique. We did not perform any other field testing such as visual inspection of the existing pavement, coring/borings, or dynamic cone penetration testing.




Figure 1 – Project Section I-35 (Provided by Redrock)

## 2. Procedure and Field-Testing Operation

EINCK, Corp used JILS-20 FWD equipment for this project. We performed FWD testing in accordance with the ASTM standards (D4694 - 09 and D4695 – 03) and *ODOT Geotechnical Specifications for Roadway Design (ODOT Specs.)*. The deflection tests consisted of two seating drops and four recording drops per test location. We used a load of approximately 15,000 lbs. EINCK, Corp performed the FWD testing at an interval of approximately 500 feet along each lane (North and South-bound) and approximately 250 feet in staggered pattern for both lanes. The testing was divided into two sections, I-35 Northbound (NB) outer lane and Southbound (SB) outer lane. The testing length for each section was approximately 4.7 miles. Test locations were along the right wheel of the driving lane. We performed a total of 116 test locations along the existing sections of I-35 with 67 tests for the NB lane, and 49 tests for the SB lane. The FWD test locations are shown in Appendix A.

## 3. Pavement Structure

Following our FWD testing survey, a total of forty-six (46) pavement cores were obtained by



RedRock. The provided pavement core information is presented in Table 1. Note that the back-calculation procedure is sensitive and dependent on the thickness of the provided individual pavement layers. A limited number of cores along with the different pavement sections identified influence the back-calculation results and their reliability. No dynamic cone penetrometer (DCP) testing was performed by EINCK, Corp nor obtained from RedRock.

**Table 1 – Pavement Core Information (provided by RedRock)**

Lane	Boring	Station No.†	Latitude†	Longitude†	AC Thickness (in.)	Aggregate Base (in.)	Cement Stabilized Subgrade (in.)	Subgrade
Northbound	C-1	640+24	35.1073	-97.4341	15.00	N/E	7.00	SANDY SILTY CLAY (CL-ML), brown, SANDY SILTY CLAY (CL-ML), red
	C-2	652+91	35.1100	-97.4367	16.00	N/E	8.00	SILTY, CLAYEY SAND (SC-SM), brown, SANDY SILTY CLAY (CL-ML), reddish brown
	C-3	662+06	35.1121	-97.4386	15.00	N/E	8.00	SANDY SILTY CLAY (CL-ML), brown, SANDY SILTY CLAY (CL-ML), reddish brown
	C-4	672+36	35.1143	-97.4406	14.50	N/E	6.00	SILTY, CLAYEY SAND (SC-SM), reddish brown, *Auger refusal at 50.5 inches
	C-5	682+54	35.1165	-97.4427	14.00	N/E	8.00	SILTY, CLAYEY SAND (SC-SM), brown, SANDY LEAN CLAY (CL), reddish brown, *Auger refusal at 52 inches
	C-6	690+04	35.1181	-97.4442	14.00	N/E	8.00	CLAYEY SAND (SC), brown, LEAN CLAY with SAND (CL), brown
	C-7	701+90	35.1208	-97.4467	14.50	N/E	4.50	CLAYEY SAND (SC), brown
	C-8	712+30	35.1230	-97.4487	14.00	N/E	10.00	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), reddish brown
	C-9	722+10	35.1252	-97.4507	14.50	N/E	8.00	SANDY SILT (ML), brown, SANDY LEAN CLAY (CL), brown
	C-10	731+99	35.1273	-97.4527	14.00	N/E	9.00	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), reddish brown
	C-11	741+97	35.1295	-97.4547	13.50	N/E	10.00	SILTY, CLAYEY SAND (SC-SM), brown, LEAN CLAY with SAND (CL), reddish brown
	C-12	752+06	35.1317	-97.4567	15.50	N/E	10.00	SILTY, CLAYEY SAND (SC-SM), brown, SANDY LEAN CLAY (CL), brown
	C-13	761+72	35.1338	-97.4587	16.50	N/E	8.00	SILTY, CLAYEY SAND (SC-SM), brown, SANDY LEAN CLAY (CL), brown
	C-14	771+57	35.1360	-97.4607	13.00	N/E	6.00	SILTY SAND (SM), brown, LEAN CLAY with SAND (CL), brown
	C-15	781+57	35.1382	-97.4627	12.00	N/E	9.00	SANDY SILT (ML), brown, LEAN CLAY with SAND (CL), brown
	C-16	791+38	35.1403	-97.4647	11.00	N/E	7.00	SANDY SILT (ML), light brown, SANDY SILT (ML), brown
	C-17	801+33	35.1425	-97.4667	11.00	N/E	10.00	SILTY SAND (SM), light brown, LEAN CLAY with SAND (CL), dark brown
	C-18	813+93	35.1452	-97.4693	12.00	N/E	10.00	SANDY SILT (ML), light brown, SANDY LEAN CLAY (CL), brown
	C-19	828+73	35.1485	-97.4723	11.50	10.00	N/E	SILTY SAND (SM), dark brown, organic smell, LEAN CLAY with SAND (CL), dark brown, organic smell
	C-20	843+61	35.1517	-97.4753	10.00	6.00	N/E	SILTY SAND (SM), light brown, SILTY, CLAYEY SAND (SC-SM), dark brown, organic smell
C-21	860+17	35.1553	-97.4786	9.25	8.00	N/E	SILTY, CLAYEY SAND (SC-SM), light brown, CLAYEY SAND (SC), dark brown, *Auger refusal at 47.25 inches	
C-22	868+53	35.1571	-97.4804	13.00	6.00	N/E	SILTY, CLAYEY SAND (SC-SM), light brown, *Auger refusal at 31 inches	
C-23	875+98	35.1588	-97.4819	10.00	10.00	N/E	SILTY, CLAYEY SAND with GRAVEL (SC-SM), light brown, *Auger refusal at 32 inches	
Southbound	C-24	871+25	35.1577	-97.4811	11.00	8.00	N/E	SILTY SAND (SM), brown, SILTY CLAY with SAND (CL-ML), reddish brown
	C-25	866+41	35.1566	-97.4801	11.00	8.00	N/E	SILTY SAND with GRAVEL (SM), brown, SILTY CLAY with SAND (CL-ML), brown
	C-26	851+52	35.1533	-97.4771	9.25	8.00	N/E	SILTY SAND with GRAVEL (SM), brown, SANDY SILT (ML), brown
	C-27	836+73	35.1501	-97.4741	12.00	8.00	N/E	SILTY SAND with GRAVEL (SM), light brown, SANDY SILT (ML), brown
	C-28	821+87	35.1468	-97.4711	11.00	6.00	N/E	SILTY SAND (SM), brown, LEAN CLAY with SAND (CL), brown
	C-29	807+01	35.1436	-97.4681	13.00	N/E	6.00	SILTY SAND (SM), brown, LEAN CLAY with SAND (CL), dark brown
	C-30	797+11	35.1414	-97.4661	11.00	N/E	8.00	SILTY SAND (SM), brown, SILTY, CLAYEY SAND (SC-SM), brown, SANDY LEAN CLAY (CL), brown
	C-31	787+20	35.1392	-97.4641	12.00	N/E	6.50	CLAYEY SAND (SC), brown, SANDY SILTY CLAY (CL-ML), dark brown to black
	C-32	777+24	35.1370	-97.4621	11.50	N/E	6.00	SILTY, CLAYEY SAND (SC-SM), brown, LEAN CLAY with SAND (CL), brown
	C-33	767+10	35.1349	-97.4600	11.00	N/E	7.00	SILTY SAND (SM), light brown, SANDY SILTY CLAY (CL-ML), light brown
	C-34	757+26	35.1327	-97.4580	15.00	N/E	5.00	SILTY SAND (SM), brown, SILTY, CLAYEY SAND (SC-SM), reddish brown
	C-35	747+34	35.1305	-97.4560	14.00	N/E	7.00	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), brown
	C-36	737+44	35.1284	-97.4540	15.50	N/E	7.00	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), brown
	C-37	727+60	35.1262	-97.4520	14.50	N/E	7.50	SILTY SAND (SM), reddish brown, SANDY LEAN CLAY (CL), reddish brown, *Auger refusal at 52 inches
	C-38	717+64	35.1240	-97.4500	14.00	N/E	7.50	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), brown
	C-39	707+72	35.1219	-97.4480	14.00	N/E	8.00	SILTY SAND (SM), brown, SANDY LEAN CLAY (CL), brown
	C-40	693+85	35.1188	-97.4452	12.50	N/E	5.00	*Auger refusal at 17.5 inches
	C-41	687+92	35.1175	-97.4440	12.00	N/E	6.00	SANDY LEAN CLAY (CL), red, *Auger refusal at 42 inches
	C-42	677+79	35.1153	-97.4419	14.00	N/E	8.00	SILTY, CLAYEY SAND (SC-SM), brown, SANDY LEAN CLAY (CL), reddish brown
	C-43	668+19	35.1132	-97.4400	15.50	N/E	8.00	SANDY SILTY CLAY (CL-ML), brown, SANDY LEAN CLAY (CL), reddish brown
	C-44	658+08	35.1110	-97.4379	15.50	N/E	8.00	SANDY SILTY CLAY (CL-ML), brown, SANDY LEAN CLAY (CL), brown
	C-45	648+15	35.1089	-97.4359	14.75	N/E	8.50	SILTY, CLAYEY SAND (SC-SM), reddish brown, SANDY LEAN CLAY (CL), reddish brown
	C-46	633+22	35.1056	-97.4329	16.00	N/E	8.00	SILTY, CLAYEY SAND (SC-SM), reddish brown, LEAN CLAY with SAND (CL), brown

† GPS and Station No. should not be used in any planning  
 N/E: Not Encountered as per RedRock

#### 4. Back-calculation Analyses

We performed back-calculation analyses using AASHTO Back-calculation Tool (BCT). We used a flexible cross section in our back-calculation BCT analyses including the asphalt layer, aggregate base, cement stabilized subgrade, and/or a 2-ft compacted subgrade layer on top of an infinite half-space subgrade layer. This is based on a study by Federal Highway Administration (FHWA), *Publication NO. FHWA-HRT-16-010* (Bruinsma et al., 2017). The study showed that a four-layer system with a 2-ft (0.6-m) compacted subgrade layer on top of an infinite half-space subgrade: (a)



provided the lower root mean square (RMS) values among the other layer combinations considered; and (b) can be the most realistic design inputs for the MEPDG software.

Selected/typical seed, minimum, and maximum values for layer moduli as well as assumed Poisson's ratio values are presented in Figures 2 and 3 for NB and SB lanes, respectively. Based on the FWD deflection data and the pavement thicknesses, the NB lane was divided into fourteen segments (Figure 2) and SB was divided into nine segments (Figure 3). We plotted the back-calculated moduli with station locations for both NB and SB lanes in Figures 4 and 5, respectively. We also summarized the results for the NB and SB lanes in Tables 2 and 3, respectively. The FWD field testing data are presented in Appendix B.



Figure 2 – NB lane pavement segments, input layer modulus and Poisson's ratio values for back-calculation



Figure 3 – SB lane pavement segments, input layer modulus and Poisson's ratio values for back-calculation




Figure 4 – NB lane back-calculated modulus versus station locations




Figure 5 – SB lane back-calculated modulus versus station locations



Table 2 – NB lane back-calculation analysis results

Station No.	HMA Thickness (in)	Aggregate Base Thickness (in)	Cement Stabilized Subgrade (in)	Asphalt Temperature (°F)	Asphalt	Adjusted @ 70°F	Aggregate Base	Cement Stabilized Subgrade	2-ft Subgrade	Infinite Subgrade
					E(1) (ksi)	E(1) (ksi)	E(2) (ksi)	E(3) (ksi)	E(4) (ksi)	E(5) (ksi)
635+28	15.33	N/E	7.67	50.0	566	258	N/E	78.2	24.4	30.5
640+24	15.33	N/E	7.67	50.2	589	271	N/E	15.3	14.1	32.7
645+18	15.33	N/E	7.67	49.8	1136	515	N/E	80.0	25.0	34.4
650+15	15.33	N/E	7.67	49.8	1361	616	N/E	80.0	25.0	39.0
652+91	15.33	N/E	7.67	49.8	1175	532	N/E	80.0	25.0	44.1
655+09	15.33	N/E	7.67	50.0	1352	616	N/E	77.6	24.6	37.2
660+05	15.33	N/E	7.67	49.8	1215	551	N/E	80.0	25.0	43.3
662+06	15.33	N/E	7.67	50.0	1499	683	N/E	80.0	25.0	49.4
665+04	15.33	N/E	7.67	50.0	1375	627	N/E	79.1	20.4	42.1
670+03	14.17	N/E	7.33	52.2	1995	993	N/E	80.0	25.0	48.5
672+36	14.17	N/E	7.33	52.2	1093	544	N/E	15.1	21.0	36.8
674+94	14.17	N/E	7.33	52.2	2000	995	N/E	79.6	24.5	99.9
679+87	14.17	N/E	7.33	52.2	2000	995	N/E	79.8	24.9	55.7
682+54	14.17	N/E	7.33	52.6	2000	1010	N/E	80.0	25.0	69.0
690+04	14.17	N/E	7.33	52.9	1990	1018	N/E	80.0	25.0	38.6
692+34	14.17	N/E	7.33	52.6	2000	1010	N/E	79.8	25.0	36.2
694+78	14.17	N/E	7.33	52.9	2000	1024	N/E	80.0	25.0	43.9
699+72	14.50	N/E	4.50	52.7	1499	762	N/E	80.0	25.0	36.2
701+90	14.50	N/E	4.50	52.7	1500	763	N/E	80.0	24.9	38.1
704+69	14.50	N/E	4.50	52.9	938	480	N/E	79.7	25.0	36.8
709+68	14.00	N/E	10.00	53.1	1500	774	N/E	79.9	24.8	46.6
712+30	14.00	N/E	10.00	52.9	1500	768	N/E	80.0	25.0	98.6
714+60	14.00	N/E	10.00	52.4	1500	751	N/E	80.0	25.0	83.6
719+56	14.00	N/E	9.00	52.7	1528	777	N/E	78.2	24.4	46.1
722+18	14.00	N/E	9.00	53.5	2000	1046	N/E	79.6	24.8	49.9
724+55	14.00	N/E	9.00	52.7	1968	1001	N/E	80.0	25.0	44.0
729+47	14.00	N/E	9.00	52.7	1339	681	N/E	78.2	24.4	32.8
731+99	14.00	N/E	9.00	52.6	1508	762	N/E	78.7	24.8	31.9
734+45	14.00	N/E	9.00	52.6	1419	717	N/E	78.2	24.4	42.6
739+48	14.00	N/E	9.00	52.9	1856	950	N/E	80.0	25.0	47.5
741+97	14.00	N/E	9.00	53.1	2000	1032	N/E	79.8	24.9	41.3
744+45	14.00	N/E	9.00	52.9	1451	743	N/E	80.0	24.4	37.9
749+35	16.00	N/E	9.00	50.3	1027	475	N/E	78.2	24.4	44.9
752+06	16.00	N/E	9.00	50.5	1500	698	N/E	80.0	25.0	46.4
754+34	16.00	N/E	9.00	50.2	1455	669	N/E	78.7	24.7	45.3
759+27	16.00	N/E	9.00	50.2	1394	640	N/E	22.8	11.0	39.4
761+72	16.00	N/E	9.00	50.3	1283	593	N/E	80.0	21.3	48.2
764+22	16.00	N/E	9.00	50.5	1151	535	N/E	78.7	24.7	40.6
769+15	13.00	N/E	6.00	53.1	495	255	N/E	80.0	25.0	30.1
771+57	13.00	N/E	6.00	53.4	1000	522	N/E	80.0	25.0	36.0
774+16	13.00	N/E	6.00	53.4	751	392	N/E	15.1	17.8	27.8
779+17	12.00	N/E	9.00	53.4	699	364	N/E	80.0	25.0	32.1
781+57	12.00	N/E	9.00	53.4	641	334	N/E	78.2	24.5	31.2
784+08	12.00	N/E	9.00	53.9	1000	532	N/E	80.0	25.0	32.0
789+06	11.00	N/E	7.00	53.2	1000	518	N/E	80.0	25.0	37.4
791+38	11.00	N/E	7.00	53.7	1000	529	N/E	80.0	25.0	33.8
794+11	11.00	N/E	7.00	53.2	998	517	N/E	79.1	20.6	27.3
798+97	11.50	N/E	10.00	53.4	571	298	N/E	78.2	23.9	39.3
801+33	11.50	N/E	10.00	53.4	391	204	N/E	31.3	24.4	29.1
803+92	11.50	N/E	10.00	52.3	1000	499	N/E	80.0	25.0	35.0
808+89	11.50	N/E	10.00	53.6	1000	526	N/E	80.0	25.0	37.7
813+93	11.50	N/E	10.00	53.9	1000	532	N/E	80.0	25.0	33.5
816+33	11.50	N/E	10.00	53.6	1000	526	N/E	80.0	25.0	30.1
818+86	11.50	N/E	10.00	54.4	1000	542	N/E	17.6	25.0	33.3
828+73	11.50	10.00	N/E	53.2	983	510	20.4	N/E	15.0	31.8
828+71	11.50	10.00	N/E	53.2	729	378	20.5	N/E	15.0	31.8
833+66	11.50	10.00	N/E	53.2	500	259	20.5	N/E	24.4	31.5
838+67	9.63	7.00	N/E	51.9	827	407	40.2	N/E	24.4	31.4
843+61	9.63	7.00	N/E	51.8	989	484	36.0	N/E	24.7	31.0
848+59	9.63	7.00	N/E	50.9	1000	472	50.0	N/E	25.0	33.3
853+44	9.63	7.00	N/E	51.6	873	424	20.4	N/E	20.9	31.6
860+17	9.63	7.00	N/E	51.6	471	229	43.4	N/E	24.0	23.9
860+97	9.63	7.00	N/E	50.7	496	233	50.0	N/E	25.0	29.3
868+53	13.00	6.00	N/E	52.7	465	237	20.4	N/E	27.9	25.9
873+42	10.00	10.00	N/E	51.8	928	454	20.9	N/E	24.3	25.5
875+98	10.00	10.00	N/E	51.8	755	370	20.5	N/E	24.0	22.5
878+35	10.00	10.00	N/E	51.8	977	478	38.1	N/E	18.9	25.0
Average	13.17	8.31	8.19	52.2	1197	596	31	73	23.7	39.7
Stdev	2.00	1.65	1.46	1.3	469	237	12	19	3	14
COV	15.16	19.89	17.79	2.5	39	40	40	26	13	36

N/E: Not Encountered by Redrock

Subgrade moduli are not factored, per AASHTO/FHWA and MEPDG the adjustment factor varies with pavement type and ranges from 0.1 to 0.5



Table 3 – SB lane back-calculation analysis results

Station No.	HMA Thickness (in)	Aggregate Base Thickness (in)	Cement Stabilized Subgrade (in)	Asphalt Temperature (°F)	Asphalt	Adjusted @ 70°F	Aggregate Base	Cement Stabilized Subgrade	2-ft Subgrade	Infinite Subgrade
					E(1) (ksi)	E(1) (ksi)	E(2) (ksi)	E(3) (ksi)	E(4) (ksi)	E(5) (ksi)
881+33	10.42	8.00	N/E	48.6	1000	432	80.0	N/E	25.0	29.9
876+39	10.42	8.00	N/E	50.7	973	457	47.9	N/E	15.3	30.6
871+41	10.42	8.00	N/E	50.0	912	417	27.4	N/E	20.4	28.8
866+41	10.42	8.00	N/E	50.4	698	323	61.4	N/E	24.8	30.5
856+50	10.42	8.00	N/E	51.1	1000	476	79.0	N/E	24.5	29.8
851+52	10.42	8.00	N/E	52.8	331	169	20.0	N/E	17.7	26.7
841+57	11.50	7.00	N/E	54.7	531	292	56.9	N/E	23.0	30.5
836+73	11.50	7.00	N/E	55.0	1000	556	80.0	N/E	25.0	35.4
831+72	11.50	7.00	N/E	54.2	364	196	32.3	N/E	24.6	29.5
826+74	11.50	7.00	N/E	54.4	520	282	35.4	N/E	21.9	27.3
821+87	11.50	7.00	N/E	53.6	475	250	31.4	N/E	24.6	29.0
816+83	11.50	7.00	N/E	53.2	1000	518	80.0	N/E	25.0	33.8
811+83	13.00	N/E	6.00	53.2	659	342	N/E	23.8	25.0	32.5
807+01	13.00	N/E	6.00	53.2	1484	770	N/E	78.2	12.1	28.2
801+76	11.38	N/E	6.88	53.1	208	107	N/E	17.7	25.0	24.7
797+11	11.38	N/E	6.88	53.4	1398	729	N/E	78.2	12.6	31.3
792+00	11.38	N/E	6.88	53.1	1327	684	N/E	78.7	24.8	30.3
787+20	11.38	N/E	6.88	53.6	699	367	N/E	80.0	25.0	32.1
782+08	11.38	N/E	6.88	53.7	576	305	N/E	42.6	16.9	32.6
777+24	11.38	N/E	6.88	53.6	488	257	N/E	15.0	21.7	30.7
772+14	11.38	N/E	6.88	52.9	1038	531	N/E	78.7	24.6	34.3
767+10	11.38	N/E	6.88	52.3	1384	690	N/E	80.0	25.0	34.2
762+23	11.38	N/E	6.88	53.9	1500	798	N/E	79.8	24.9	50.0
757+26	15.00	N/E	5.00	51.2	1432	685	N/E	78.5	24.6	41.5
752+29	15.00	N/E	5.00	50.2	1500	689	N/E	80.0	25.0	45.7
747+34	14.40	N/E	7.40	51.9	533	262	N/E	80.0	25.0	33.2
742+36	14.40	N/E	7.40	52.2	1425	709	N/E	78.7	24.4	35.0
737+44	14.40	N/E	7.40	52.6	828	418	N/E	24.3	25.0	39.6
732+45	14.40	N/E	7.40	54.2	1818	978	N/E	80.0	25.0	41.6
727+60	14.40	N/E	7.40	52.7	1456	740	N/E	80.0	25.0	32.3
722+54	14.40	N/E	7.40	53.1	1992	1029	N/E	80.0	25.0	49.9
717+64	14.40	N/E	7.40	52.4	1995	999	N/E	80.0	25.0	49.9
712+62	14.40	N/E	7.40	52.9	886	454	N/E	80.0	25.0	49.3
707+72	14.40	N/E	7.40	53.1	1153	595	N/E	78.2	24.4	38.0
704+16	14.40	N/E	7.40	53.1	1501	775	N/E	80.0	25.0	43.7
693+85	12.25	N/E	5.50	54.1	1997	1070	N/E	80.0	25.0	38.8
692+71	12.25	N/E	5.50	53.6	1996	1049	N/E	80.0	25.0	36.1
687+92	12.25	N/E	5.50	54.2	1910	1029	N/E	75.9	24.6	36.9
682+82	12.25	N/E	5.50	54.7	2000	1099	N/E	80.0	25.0	50.0
677+79	14.94	N/E	8.12	54.4	1273	691	N/E	80.0	25.0	49.8
672+86	14.94	N/E	8.12	51.5	745	360	N/E	78.7	24.9	42.6
668+19	14.94	N/E	8.12	54.9	1828	1013	N/E	79.7	25.0	43.5
663+00	14.94	N/E	8.12	54.0	1999	1068	N/E	80.0	24.7	49.7
658+08	14.94	N/E	8.12	53.1	727	375	N/E	80.0	25.0	32.8
653+06	14.94	N/E	8.12	54.7	1407	773	N/E	78.7	23.2	33.4
648+15	14.94	N/E	8.12	53.7	1558	822	N/E	80.0	25.0	44.9
643+15	16.00	N/E	8.00	51.4	998	481	N/E	79.5	25.0	35.9
638+21	16.00	N/E	8.00	49.2	1500	662	N/E	80.0	25.0	38.1
633+22	16.00	N/E	8.00	47.6	1466	608	N/E	78.2	24.4	38.2
Average	12.97	7.50	7.05	52.8	1173	600	53	72	23.6	36.6
Stdev	1.83	0.52	0.95	1.7	521	278	23	19	3	7
COV	14.09	6.96	13.47	3.2	44	46	44	27	13	20

N/E: Not Encountered by Redrock

Subgrade moduli are not factored, per AASHTO/FHWA and MEPDG the adjustment factor varies with pavement type and ranges from 0.1 to 0.5

## 5. Limitations

The procedures and methodologies used to complete this project are consistent with standard and/or accepted/recognized practices in similar pavement and geotechnical investigations. EINCK, Corp assumes no responsibility for survey limitations due to inherent technological limitations and interpretations made by others based on work performed by or recommendations made by us.



## **6. References**


- Bruinsma, J. E., VandeSBossche, J.M., Chatti, K., and Smith, K.D., (2017) Using Falling Weight Deflectometer Data with Mechanistic Empirical Design and Analysis, Volume II: Case Study Reports, Final Report, Submitted to FHWA, *Publication NO. FHWA-HRT-16-010* March 2017.
- MDOT (1994) Temperature Adjustment Factor for Falling Weight Deflectometer Deflections on Full Depth Asphalt Concrete Pavements, Missouri Department of Transportation, RDT 96-002, November 1994.

## **APPENDIX A – FWD TEST LOCATIONS**

**I-35 FWD Testing  
McClain County, Oklahoma**

**FWD Location NB**

**FWD Location SB**



1985

Imagery Date: 7/5/2022 35°07'39.30" N 97°27'44.16" W elev 0 ft eye alt 11685 ft

**APPENDIX B – FWD FIELD TESTING DATA**

## **NORTHBOUND (NB) DATA**

M5

Date-Time: 12/ 6/2022 11:19:12

Sensors: chop chop chop chop chop chop chop chop

Weight/spring: 3

Location: remote

Temp: 52.83

Operator: Ryan

Comments:

1	1	503.000	1	15.33	8.34	6.64	6.04	5.30	4.77	3.75	3.09	2.48	51.7
1	1	503.000	1	15.23	8.22	6.60	5.97	5.28	4.72	3.76	3.11	2.46	51.7
1	1	503.000	1	15.18	8.16	6.62	5.94	5.26	4.73	3.75	3.12	2.46	51.7
1	1	503.000	1	15.05	8.10	6.54	5.92	5.23	4.72	3.73	3.06	2.44	51.7
1	1	503.000	1	15.13	8.12	6.57	5.95	5.24	4.70	3.71	3.07	2.46	51.7
1	1	503.000	1	15.13	8.10	6.51	5.92	5.21	4.70	3.72	3.10	2.48	51.7

Drop Sequence Completed Time: 11:20 Air Temp (F): 52.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.370580 N Longitude = 97 deg25.986891 W PDOP = 2.50

Note:

2	1	1003.000	1	14.98	9.42	7.94	7.20	6.52	5.78	4.31	3.40	2.61	52.1
2	1	1003.000	1	14.73	9.23	7.79	7.13	6.40	5.69	4.25	3.32	2.55	52.1
2	1	1003.000	1	14.81	9.22	7.80	7.13	6.42	5.69	4.24	3.37	2.59	52.1
2	1	1003.000	1	14.83	9.24	7.80	7.20	6.45	5.76	4.29	3.37	2.58	52.1
2	1	1003.000	1	14.91	9.23	7.80	7.17	6.43	5.76	4.27	3.39	2.60	52.1
2	1	1003.000	1	14.88	9.25	7.74	7.21	6.48	5.74	4.29	3.38	2.60	52.1

Drop Sequence Completed Time: 11:21 Air Temp (F): 50.6

GPS: Quality : DGPS Fix Latitude = 35 deg6.435513 N Longitude = 97 deg26.047093 W PDOP = 2.50

Note:

3	1	1501.000	1	15.03	6.31	5.09	4.58	4.21	3.93	3.23	2.75	2.24	51.4
3	1	1501.000	1	14.91	6.18	5.03	4.56	4.19	3.89	3.21	2.72	2.24	51.4
3	1	1501.000	1	14.93	6.11	4.97	4.56	4.18	3.87	3.19	2.69	2.23	51.4
3	1	1501.000	1	14.91	6.11	4.97	4.54	4.14	3.88	3.21	2.71	2.24	51.4
3	1	1501.000	1	15.03	6.09	4.97	4.56	4.16	3.86	3.20	2.72	2.23	51.4
3	1	1501.000	1	14.93	6.05	4.97	4.51	4.13	3.83	3.17	2.68	2.21	51.4

Drop Sequence Completed Time: 11:22 Air Temp (F): 52.3

GPS: Quality : DGPS Fix Latitude = 35 deg6.500251 N Longitude = 97 deg26.107291 W PDOP = 2.50

Note:

4	1	2002.000	1	15.08	5.79	4.55	4.18	3.76	3.43	2.80	2.46	1.68	51.4
4	1	2002.000	1	14.98	5.61	4.49	4.12	3.73	3.37	2.81	2.42	2.04	51.4
4	1	2002.000	1	14.88	5.49	4.47	4.09	3.70	3.36	2.79	2.43	2.05	51.4
4	1	2002.000	1	14.88	5.45	4.45	4.08	3.68	3.36	2.77	2.43	2.03	51.4
4	1	2002.000	1	14.91	5.43	4.47	4.07	3.70	3.38	2.77	2.45	2.05	51.4
4	1	2002.000	1	15.01	5.43	4.48	4.08	3.67	3.35	2.78	2.44	2.06	51.4

Drop Sequence Completed Time: 11:23 Air Temp (F): 50.4

GPS: Quality : DGPS Fix Latitude = 35 deg6.565458 N Longitude = 97 deg26.167633 W PDOP = 2.50

Note:

5	1	2264.000	1	15.15	5.51	4.50	4.12	3.70	3.35	2.66	2.25	1.89	51.4
5	1	2264.000	1	14.93	5.41	4.44	4.01	3.61	3.27	2.61	2.22	1.85	51.4

5 1 2264.000 1 14.91 5.40 4.42 4.04 3.63 3.30 2.61 2.23 1.84 51.4  
5 1 2264.000 1 14.91 5.39 4.41 4.03 3.61 3.26 2.60 2.22 1.84 51.4  
5 1 2264.000 1 14.86 5.42 4.41 4.04 3.63 3.29 2.62 2.23 1.82 51.4  
5 1 2264.000 1 14.83 5.35 4.37 3.99 3.61 3.27 2.59 2.21 1.82 51.4

Drop Sequence Completed Time: 11:24 Air Temp (F): 53.2

GPS: Quality : DGPS Fix Latitude = 35 deg6.599397 N Longitude = 97  
deg26.199057 W PDOP = 2.50

Note:

6 1 2500.000 1 15.18 5.43 4.68 4.35 3.96 3.63 2.96 2.51 2.10 51.7  
6 1 2500.000 1 15.13 5.43 4.70 4.37 4.00 3.65 2.98 2.59 2.16 51.7  
6 1 2500.000 1 14.93 5.33 4.57 4.26 3.92 3.56 2.92 2.50 2.07 51.7  
6 1 2500.000 1 14.93 5.31 4.59 4.27 3.90 3.55 2.91 2.50 2.09 51.7  
6 1 2500.000 1 14.98 5.32 4.57 4.29 3.91 3.58 2.93 2.51 2.09 51.7  
6 1 2500.000 1 14.88 5.33 4.57 4.28 3.91 3.59 2.95 2.53 2.09 51.7

Drop Sequence Completed Time: 11:25 Air Temp (F): 52.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.630080 N Longitude = 97  
deg26.227571 W PDOP = 1.90

Note:

7 1 3002.000 1 15.10 5.51 4.40 4.05 3.71 3.42 2.78 2.31 1.84 51.4  
7 1 3002.000 1 14.96 5.51 4.36 4.02 3.68 3.37 2.74 2.29 1.83 51.4  
7 1 3002.000 1 14.93 5.45 4.33 3.95 3.64 3.36 2.72 2.27 1.82 51.4  
7 1 3002.000 1 14.83 5.42 4.30 3.92 3.63 3.34 2.72 2.24 1.85 51.4  
7 1 3002.000 1 15.03 5.44 4.34 3.97 3.64 3.38 2.71 2.27 1.82 51.4  
7 1 3002.000 1 14.98 5.46 4.36 3.98 3.65 3.36 2.73 2.27 1.81 51.4

Drop Sequence Completed Time: 11:27 Air Temp (F): 53.3

GPS: Quality : DGPS Fix Latitude = 35 deg6.695461 N Longitude = 97  
deg26.287902 W PDOP = 1.90

Note:

8 1 3248.000 1 15.28 4.65 3.89 3.58 3.29 3.05 2.46 2.11 1.73 51.7  
8 1 3248.000 1 15.01 4.56 3.85 3.51 3.23 3.00 2.45 2.09 1.71 51.7  
8 1 3248.000 1 14.93 4.52 3.78 3.49 3.20 2.97 2.42 2.09 1.68 51.7  
8 1 3248.000 1 14.98 4.50 3.79 3.49 3.21 2.96 2.44 2.08 1.68 51.7  
8 1 3248.000 1 15.03 4.51 3.78 3.50 3.20 2.95 2.41 2.06 1.70 51.7  
8 1 3248.000 1 14.91 4.51 3.79 3.49 3.20 2.95 2.43 2.03 1.69 51.7

Drop Sequence Completed Time: 11:28 Air Temp (F): 52.3

GPS: Quality : DGPS Fix Latitude = 35 deg6.727641 N Longitude = 97  
deg26.317700 W PDOP = 1.90

Note:

9 1 3503.000 1 15.23 5.30 4.52 4.16 3.80 3.55 2.98 2.36 1.93 51.7  
9 1 3503.000 1 15.03 5.23 4.48 4.12 3.76 3.49 2.96 2.36 1.96 51.7  
9 1 3503.000 1 14.88 5.16 4.40 4.05 3.69 3.48 2.90 2.35 1.91 51.7  
9 1 3503.000 1 14.98 5.15 4.40 4.05 3.68 3.44 2.90 2.28 1.83 51.7  
9 1 3503.000 1 14.96 5.14 4.42 4.08 3.72 3.48 2.92 2.35 1.91 51.7  
9 1 3503.000 1 15.05 5.20 4.44 4.08 3.74 3.50 2.91 2.32 1.89 51.7

Drop Sequence Completed Time: 11:29 Air Temp (F): 54.0

GPS: Quality : DGPS Fix Latitude = 35 deg6.760792 N Longitude = 97  
deg26.348358 W PDOP = 1.90

Note:

10 1 4005.000 1 15.13 5.34 3.91 3.45 3.10 2.85 2.45 2.12 1.81 51.4  
10 1 4005.000 1 14.83 5.16 3.82 3.38 3.02 2.81 2.36 2.08 1.75 51.4

10 1 4005.000 1 14.81 5.15 3.82 3.38 3.04 2.79 2.37 2.07 1.81 51.4  
10 1 4005.000 1 14.93 5.17 3.84 3.38 3.06 2.83 2.40 2.08 1.84 51.4  
10 1 4005.000 1 14.83 5.05 3.75 3.31 2.98 2.75 2.30 2.02 1.80 51.4  
10 1 4005.000 1 14.96 5.16 3.83 3.42 3.06 2.85 2.40 2.04 1.80 51.4

Drop Sequence Completed Time: 11:30 Air Temp (F): 53.5

GPS: Quality : DGPS Fix Latitude = 35 deg6.826261 N Longitude = 97  
deg26.408804 W PDOP = 1.90

Note:

11 1 4251.000 1 14.98 6.90 6.06 5.66 5.15 4.77 3.51 2.85 2.28 51.4  
11 1 4251.000 1 15.03 6.91 6.11 5.67 5.17 4.76 3.56 2.85 2.30 51.4  
11 1 4251.000 1 14.91 6.84 6.00 5.61 5.08 4.70 3.48 2.83 2.27 51.4  
11 1 4251.000 1 14.66 6.76 5.96 5.51 5.04 4.65 3.45 2.77 2.24 51.4  
11 1 4251.000 1 14.76 6.81 5.98 5.55 5.06 4.67 3.48 2.79 2.24 51.4  
11 1 4251.000 1 14.71 6.80 5.94 5.57 5.09 4.71 3.49 2.79 2.28 51.4

Drop Sequence Completed Time: 11:31 Air Temp (F): 52.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.858224 N Longitude = 97  
deg26.438395 W PDOP = 1.90

Note:

12 1 4503.000 1 15.23 3.73 2.79 2.49 2.20 1.98 1.51 1.14 0.83 51.4  
12 1 4503.000 1 14.83 3.64 2.72 2.43 2.16 1.93 1.47 1.12 0.82 51.4  
12 1 4503.000 1 14.93 3.63 2.73 2.42 2.16 1.93 1.46 1.13 0.82 51.4  
12 1 4503.000 1 14.76 3.58 2.70 2.43 2.15 1.90 1.45 1.10 0.81 51.4  
12 1 4503.000 1 14.91 3.59 2.71 2.43 2.17 1.95 1.48 1.12 0.80 51.4  
12 1 4503.000 1 14.81 3.56 2.70 2.40 2.14 1.94 1.46 1.11 0.84 51.4

Drop Sequence Completed Time: 11:31 Air Temp (F): 53.9

GPS: Quality : DGPS Fix Latitude = 35 deg6.890895 N Longitude = 97  
deg26.468554 W PDOP = 1.90

Note:

13 1 4999.000 1 15.13 4.16 3.49 3.27 2.98 2.78 2.31 1.94 1.60 51.4  
13 1 4999.000 1 15.03 4.09 3.44 3.20 2.95 2.74 2.26 1.93 1.56 51.4  
13 1 4999.000 1 14.91 4.06 3.40 3.20 2.94 2.73 2.28 1.91 1.56 51.4  
13 1 4999.000 1 14.86 4.04 3.40 3.17 2.91 2.72 2.25 1.89 1.55 51.4  
13 1 4999.000 1 14.76 4.02 3.41 3.19 2.91 2.70 2.21 1.89 1.51 51.4  
13 1 4999.000 1 14.91 4.09 3.41 3.21 2.94 2.73 2.27 1.91 1.52 51.4

Drop Sequence Completed Time: 11:33 Air Temp (F): 53.3

GPS: Quality : DGPS Fix Latitude = 35 deg6.955522 N Longitude = 97  
deg26.528336 W PDOP = 1.90

Note:

14 1 5258.000 1 14.93 3.71 3.19 2.99 2.71 2.51 2.00 1.65 1.29 52.1  
14 1 5258.000 1 15.20 3.72 3.19 2.99 2.75 2.51 2.00 1.68 1.30 52.1  
14 1 5258.000 1 14.88 3.67 3.14 2.92 2.68 2.43 1.96 1.61 1.27 52.1  
14 1 5258.000 1 14.88 3.67 3.16 2.93 2.67 2.47 1.99 1.61 1.27 52.1  
14 1 5258.000 1 14.71 3.64 3.09 2.93 2.64 2.40 1.96 1.61 1.26 52.1  
14 1 5258.000 1 14.76 3.64 3.13 2.93 2.67 2.45 1.96 1.63 1.24 52.1

Drop Sequence Completed Time: 11:33 Air Temp (F): 54.0

GPS: Quality : DGPS Fix Latitude = 35 deg6.989131 N Longitude = 97  
deg26.559688 W PDOP = 1.90

Note:

15 1 6006.000 1 15.03 5.10 4.32 4.01 3.68 3.38 2.80 2.46 2.07 52.7  
15 1 6006.000 1 14.61 4.90 4.16 3.89 3.56 3.27 2.69 2.39 2.01 52.7

15 1 6006.000 1 14.66 4.92 4.18 3.90 3.56 3.28 2.72 2.38 2.03 52.7  
15 1 6006.000 1 14.68 4.89 4.16 3.87 3.55 3.27 2.70 2.39 2.03 52.7  
15 1 6006.000 1 14.51 4.84 4.11 3.84 3.52 3.22 2.70 2.35 2.04 52.7  
15 1 6006.000 1 14.63 4.88 4.17 3.89 3.59 3.29 2.70 2.32 2.03 52.7

Drop Sequence Completed Time: 11:35 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.086523 N Longitude = 97  
deg26.650013 W PDOP = 1.90

Note:

16 1 6257.000 1 14.98 5.02 4.24 4.00 3.76 3.51 2.95 2.60 2.16 52.1  
16 1 6257.000 1 14.98 5.00 4.22 4.01 3.77 3.53 2.97 2.58 2.19 52.1  
16 1 6257.000 1 14.81 5.00 4.22 3.97 3.73 3.50 2.97 2.58 2.14 52.1  
16 1 6257.000 1 14.93 5.00 4.23 3.96 3.74 3.50 2.96 2.56 2.17 52.1  
16 1 6257.000 1 14.76 4.94 4.19 3.94 3.72 3.50 2.95 2.58 2.14 52.1  
16 1 6257.000 1 14.93 5.00 4.18 4.00 3.73 3.49 2.95 2.57 2.17 52.1

Drop Sequence Completed Time: 11:35 Air Temp (F): 53.3

GPS: Quality : DGPS Fix Latitude = 35 deg7.119272 N Longitude = 97  
deg26.679844 W PDOP = 1.90

Note:

17 1 6501.000 1 14.88 4.51 3.87 3.65 3.45 3.28 2.73 2.29 1.86 52.7  
17 1 6501.000 1 14.76 4.45 3.83 3.62 3.42 3.24 2.76 2.25 1.83 52.7  
17 1 6501.000 1 14.56 4.41 3.79 3.56 3.36 3.19 2.71 2.22 1.81 52.7  
17 1 6501.000 1 14.68 4.35 3.73 3.49 3.32 3.14 2.65 2.14 1.77 52.7  
17 1 6501.000 1 14.71 4.34 3.72 3.52 3.32 3.12 2.66 2.15 1.74 52.7  
17 1 6501.000 1 14.71 4.38 3.74 3.57 3.36 3.21 2.71 2.19 1.79 52.7

Drop Sequence Completed Time: 11:36 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.150988 N Longitude = 97  
deg26.709454 W PDOP = 1.90

Note:

18 1 7001.000 1 14.91 5.86 4.67 4.22 3.87 3.60 2.98 2.56 2.15 52.4  
18 1 7001.000 1 14.61 5.87 4.65 4.24 3.90 3.61 3.03 2.64 2.15 52.4  
18 1 7001.000 1 14.56 5.77 4.60 4.16 3.83 3.57 2.98 2.57 2.13 52.4  
18 1 7001.000 1 14.44 5.70 4.59 4.18 3.83 3.54 2.90 2.56 2.15 52.4  
18 1 7001.000 1 14.44 5.70 4.57 4.14 3.80 3.54 2.96 2.55 2.15 52.4  
18 1 7001.000 1 14.46 5.72 4.56 4.16 3.82 3.56 2.27 2.59 2.12 52.4

Drop Sequence Completed Time: 11:38 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.215881 N Longitude = 97  
deg26.769580 W PDOP = 1.90

Note:

19 1 7249.000 1 14.81 5.44 4.41 4.16 3.87 3.61 2.99 2.55 2.09 52.4  
19 1 7249.000 1 14.61 5.38 4.40 4.13 3.85 3.59 2.98 2.56 2.07 52.4  
19 1 7249.000 1 14.71 5.32 4.36 4.08 3.80 3.55 2.93 2.51 2.03 52.4  
19 1 7249.000 1 14.58 5.27 4.34 4.08 3.78 3.52 2.93 2.50 2.04 52.4  
19 1 7249.000 1 14.51 5.26 4.38 4.07 3.78 3.52 2.94 2.49 2.05 52.4  
19 1 7249.000 1 14.56 5.33 4.40 4.14 3.85 3.58 2.95 2.51 2.05 52.4

Drop Sequence Completed Time: 11:39 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.248320 N Longitude = 97  
deg26.799500 W PDOP = 1.90

Note:

20 1 7502.000 1 14.81 6.43 5.58 5.14 4.59 3.97 3.05 2.55 2.11 52.7  
20 1 7502.000 1 14.61 6.38 5.50 5.11 4.54 3.96 3.07 2.57 2.09 52.7

20 1 7502.000 1 14.51 6.31 5.47 5.09 4.50 3.90 3.01 2.52 2.07 52.7  
20 1 7502.000 1 14.44 6.25 5.40 5.02 4.49 3.90 2.99 2.51 2.05 52.7  
20 1 7502.000 1 14.56 6.28 5.47 5.03 4.49 3.88 3.01 2.52 2.06 52.7  
20 1 7502.000 1 14.58 6.30 5.47 5.05 4.49 3.91 3.03 2.56 2.08 52.7

Drop Sequence Completed Time: 11:39 Air Temp (F): 53.7

GPS: Quality : DGPS Fix Latitude = 35 deg7.281340 N Longitude = 97  
deg26.829867 W PDOP = 1.90

Note:

21 1 8002.000 1 14.81 4.66 3.89 3.58 3.37 3.13 2.62 2.25 1.80 53.1  
21 1 8002.000 1 14.63 4.63 3.82 3.60 3.36 3.16 2.62 2.24 1.82 53.1  
21 1 8002.000 1 14.61 4.61 3.84 3.55 3.31 3.10 2.59 2.21 1.82 53.1  
21 1 8002.000 1 14.51 4.59 3.84 3.51 3.30 3.12 2.60 2.23 1.87 53.1  
21 1 8002.000 1 14.44 4.58 3.83 3.52 3.31 3.09 2.61 2.24 1.86 53.1  
21 1 8002.000 1 14.41 4.49 3.73 3.46 3.28 3.06 2.54 2.15 1.82 53.1

Drop Sequence Completed Time: 11:41 Air Temp (F): 53.9

GPS: Quality : DGPS Fix Latitude = 35 deg7.346645 N Longitude = 97  
deg26.890239 W PDOP = 1.90

Note:

22 1 8271.000 1 14.91 3.83 2.94 2.64 2.28 2.02 1.52 1.17 0.87 52.7  
22 1 8271.000 1 14.51 3.74 2.84 2.56 2.22 1.99 1.49 1.14 0.85 52.7  
22 1 8271.000 1 14.51 3.70 2.79 2.53 2.23 1.98 1.49 1.12 0.84 52.7  
22 1 8271.000 1 14.36 3.69 2.82 2.51 2.22 1.98 1.47 1.10 0.84 52.7  
22 1 8271.000 1 14.58 3.70 2.86 2.60 2.25 1.98 1.48 1.16 0.87 52.7  
22 1 8271.000 1 14.41 3.72 2.83 2.55 2.24 1.98 1.48 1.16 0.86 52.7

Drop Sequence Completed Time: 11:41 Air Temp (F): 54.0

GPS: Quality : DGPS Fix Latitude = 35 deg7.381592 N Longitude = 97  
deg26.922515 W PDOP = 1.90

Note:

23 1 8499.000 1 14.66 3.79 3.08 2.88 2.62 2.37 1.84 1.46 1.13 51.7  
23 1 8499.000 1 14.49 3.75 3.04 2.81 2.57 2.32 1.83 1.47 1.12 51.7  
23 1 8499.000 1 14.39 3.73 3.04 2.81 2.56 2.32 1.77 1.45 1.11 51.7  
23 1 8499.000 1 14.39 3.68 2.99 2.71 2.49 2.25 1.75 1.39 1.08 51.7  
23 1 8499.000 1 14.31 3.72 3.01 2.81 2.53 2.29 1.79 1.43 1.12 51.7  
23 1 8499.000 1 14.39 3.69 3.05 2.80 2.53 2.28 1.81 1.43 1.10 51.7

Drop Sequence Completed Time: 11:42 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.411168 N Longitude = 97  
deg26.950006 W PDOP = 1.70

Note:

24 1 9000.000 1 14.66 4.95 4.15 3.83 3.51 3.21 2.54 2.14 1.70 52.4  
24 1 9000.000 1 14.36 4.84 4.06 3.77 3.42 3.15 2.52 2.08 1.63 52.4  
24 1 9000.000 1 14.44 4.86 4.11 3.84 3.47 3.16 2.54 2.12 1.68 52.4  
24 1 9000.000 1 14.31 4.84 4.05 3.80 3.45 3.15 2.54 2.09 1.68 52.4  
24 1 9000.000 1 14.44 4.85 4.08 3.79 3.50 3.19 2.54 2.08 1.60 52.4  
24 1 9000.000 1 14.34 4.81 4.06 3.80 3.42 3.16 2.52 2.08 1.67 52.4

Drop Sequence Completed Time: 11:43 Air Temp (F): 53.3

GPS: Quality : DGPS Fix Latitude = 35 deg7.476307 N Longitude = 97  
deg27.010350 W PDOP = 1.70

Note:

25 1 9252.000 1 14.66 4.00 3.35 3.14 2.94 2.72 2.29 2.02 1.69 53.7  
25 1 9252.000 1 14.49 3.92 3.30 3.11 2.89 2.69 2.22 1.97 1.66 53.7

25 1 9252.000 1 14.44 3.94 3.31 3.09 2.89 2.73 2.26 1.95 1.66 53.7  
25 1 9252.000 1 14.44 3.98 3.30 3.04 2.84 2.70 2.30 1.92 1.63 53.7  
25 1 9252.000 1 14.41 3.93 3.29 3.10 2.89 2.69 2.27 1.98 1.68 53.7  
25 1 9252.000 1 14.24 3.89 3.30 3.08 2.84 2.69 2.24 1.96 1.66 53.7

Drop Sequence Completed Time: 11:44 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg7.509248 N Longitude = 97  
deg27.040831 W PDOP = 1.90

Note:

26 1 9502.000 1 14.53 4.71 3.87 3.59 3.30 3.07 2.51 2.15 1.78 52.4  
26 1 9502.000 1 14.31 4.63 3.81 3.52 3.23 3.01 2.46 2.19 1.71 52.4  
26 1 9502.000 1 14.46 4.69 3.85 3.56 3.29 3.06 2.53 2.14 1.71 52.4  
26 1 9502.000 1 14.26 4.59 3.78 3.52 3.21 3.00 2.50 2.15 1.74 52.4  
26 1 9502.000 1 14.49 4.61 3.83 3.56 3.24 3.00 2.49 2.14 1.79 52.4  
26 1 9502.000 1 14.36 4.63 3.84 3.55 3.25 3.03 2.51 2.17 1.75 52.4

Drop Sequence Completed Time: 11:45 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg7.541818 N Longitude = 97  
deg27.070823 W PDOP = 2.00

Note:

27 1 9998.000 1 14.68 5.96 5.02 4.67 4.33 4.03 3.31 2.76 2.22 52.4  
27 1 9998.000 1 14.31 5.78 4.88 4.55 4.24 3.93 3.24 2.72 2.17 52.4  
27 1 9998.000 1 14.29 5.75 4.87 4.53 4.18 3.93 3.27 2.70 2.16 52.4  
27 1 9998.000 1 14.14 5.70 4.81 4.47 4.17 3.83 3.20 2.67 2.15 52.4  
27 1 9998.000 1 14.29 5.76 4.89 4.53 4.21 3.91 3.25 2.69 2.20 52.4  
27 1 9998.000 1 14.24 5.73 4.86 4.52 4.20 3.88 3.24 2.67 2.19 52.4

Drop Sequence Completed Time: 11:46 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.606361 N Longitude = 97  
deg27.130523 W PDOP = 2.00

Note:

28 1 10249.000 1 14.56 5.79 4.91 4.62 4.25 3.98 3.28 2.81 2.33 52.1  
28 1 10249.000 1 14.39 5.71 4.84 4.59 4.22 3.93 3.23 2.75 2.28 52.1  
28 1 10249.000 1 14.34 5.64 4.82 4.54 4.22 3.89 3.22 2.74 2.29 52.1  
28 1 10249.000 1 14.11 5.58 4.76 4.48 4.13 3.82 3.17 2.71 2.23 52.1  
28 1 10249.000 1 14.39 5.67 4.84 4.49 4.17 3.87 3.12 2.76 2.24 52.1  
28 1 10249.000 1 14.26 5.61 4.76 4.53 4.17 3.85 3.20 2.73 2.24 52.1

Drop Sequence Completed Time: 11:47 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.639117 N Longitude = 97  
deg27.160571 W PDOP = 2.00

Note:

29 1 10500.000 1 14.63 5.22 4.41 4.10 3.73 3.39 2.62 2.27 1.83 52.1  
29 1 10500.000 1 14.39 5.11 4.29 4.00 3.66 3.35 2.68 2.28 1.77 52.1  
29 1 10500.000 1 14.36 5.14 4.32 4.03 3.66 3.39 2.68 2.25 1.78 52.1  
29 1 10500.000 1 14.41 5.11 4.31 3.97 3.65 3.39 2.68 2.22 1.76 52.1  
29 1 10500.000 1 14.46 5.12 4.32 4.04 3.67 3.36 2.71 2.25 1.79 52.1  
29 1 10500.000 1 14.41 5.09 4.30 4.00 3.69 3.34 2.68 2.20 1.79 52.1

Drop Sequence Completed Time: 11:48 Air Temp (F): 54.2

GPS: Quality : DGPS Fix Latitude = 35 deg7.671849 N Longitude = 97  
deg27.190966 W PDOP = 2.00

Note:

30 1 11005.000 1 14.78 4.87 3.90 3.59 3.30 3.06 2.48 2.11 1.72 52.7  
30 1 11005.000 1 14.56 4.75 3.78 3.53 3.23 3.00 2.36 2.01 1.70 52.7

30 1 11005.000 1 14.46 4.71 3.78 3.50 3.21 2.97 2.32 2.02 1.68 52.7  
30 1 11005.000 1 14.26 4.60 3.69 3.43 3.16 2.93 2.35 2.07 1.62 52.7  
30 1 11005.000 1 14.39 4.66 3.75 3.46 3.18 2.93 2.38 2.01 1.67 52.7  
30 1 11005.000 1 14.49 4.69 3.78 3.53 3.19 2.94 2.35 2.03 1.70 52.7

Drop Sequence Completed Time: 11:50 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.737742 N Longitude = 97  
deg27.251901 W PDOP = 1.70

Note:

31 1 11256.000 1 14.63 4.74 3.89 3.66 3.43 3.22 2.69 2.23 1.26 53.1  
31 1 11256.000 1 14.41 4.64 3.84 3.64 3.41 3.17 2.66 2.29 1.91 53.1  
31 1 11256.000 1 14.36 4.63 3.78 3.58 3.36 3.16 2.66 2.29 1.89 53.1  
31 1 11256.000 1 14.34 4.58 3.74 3.56 3.31 3.09 2.61 2.29 1.89 53.1  
31 1 11256.000 1 14.41 4.59 3.76 3.59 3.34 3.12 2.64 2.29 1.88 53.1  
31 1 11256.000 1 14.51 4.64 3.79 3.60 3.38 3.16 2.60 2.28 1.90 53.1

Drop Sequence Completed Time: 11:50 Air Temp (F): 53.0

GPS: Quality : DGPS Fix Latitude = 35 deg7.770472 N Longitude = 97  
deg27.282247 W PDOP = 2.00

Note:

32 1 11505.000 1 14.63 5.39 4.64 4.33 3.95 3.64 2.93 2.47 1.97 52.7  
32 1 11505.000 1 14.56 5.34 4.61 4.29 3.92 3.57 2.90 2.44 1.98 52.7  
32 1 11505.000 1 14.68 5.39 4.62 4.30 3.95 3.63 2.94 2.44 1.98 52.7  
32 1 11505.000 1 14.39 5.26 4.54 4.25 3.85 3.55 2.86 2.38 1.94 52.7  
32 1 11505.000 1 14.49 5.32 4.57 4.27 3.88 3.58 2.87 2.41 1.97 52.7  
32 1 11505.000 1 14.34 5.28 4.56 4.23 3.87 3.54 2.88 2.43 1.94 52.7

Drop Sequence Completed Time: 11:51 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.802850 N Longitude = 97  
deg27.312307 W PDOP = 2.00

Note:

33 1 12000.000 1 14.76 5.19 4.25 3.99 3.59 3.29 2.59 2.14 1.75 52.4  
33 1 12000.000 1 14.53 5.11 4.24 3.91 3.55 3.24 2.56 2.11 1.71 52.4  
33 1 12000.000 1 14.58 5.10 4.21 3.91 3.53 3.22 2.57 2.11 1.70 52.4  
33 1 12000.000 1 14.61 5.11 4.21 3.89 3.55 3.24 2.58 2.11 1.68 52.4  
33 1 12000.000 1 14.51 5.08 4.16 3.89 3.56 3.25 2.58 2.11 1.65 52.4  
33 1 12000.000 1 14.44 5.04 4.15 3.89 3.52 3.20 2.53 2.07 1.67 52.4

Drop Sequence Completed Time: 11:52 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.867203 N Longitude = 97  
deg27.371976 W PDOP = 2.00

Note:

34 1 12250.000 1 14.58 4.25 3.47 3.25 3.04 2.87 2.44 2.10 1.80 52.7  
34 1 12250.000 1 14.58 4.24 3.46 3.21 3.03 2.85 2.41 2.17 1.77 52.7  
34 1 12250.000 1 14.53 4.28 3.53 3.30 3.08 2.91 2.47 2.17 1.75 52.7  
34 1 12250.000 1 14.41 4.16 3.43 3.22 2.99 2.83 2.48 2.18 1.75 52.7  
34 1 12250.000 1 14.56 4.24 3.47 3.21 3.04 2.86 2.41 2.12 1.82 52.7  
34 1 12250.000 1 14.58 4.22 3.47 3.25 3.04 2.83 2.49 2.17 1.75 52.7

Drop Sequence Completed Time: 11:53 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg7.899936 N Longitude = 97  
deg27.402426 W PDOP = 2.00

Note:

35 1 12502.000 1 14.73 4.49 3.86 3.64 3.29 3.06 2.46 2.09 1.74 52.1  
35 1 12502.000 1 14.63 4.44 3.82 3.57 3.25 3.00 2.46 2.08 1.71 52.1

35 1 12502.000 1 14.53 4.41 3.83 3.53 3.21 2.94 2.40 2.13 1.69 52.1  
35 1 12502.000 1 14.71 4.50 3.86 3.60 3.27 3.03 2.36 2.11 1.73 52.1  
35 1 12502.000 1 14.46 4.40 3.78 3.54 3.24 2.97 2.42 2.04 1.69 52.1  
35 1 12502.000 1 14.39 4.45 3.83 3.51 3.19 2.96 2.42 2.06 1.69 52.1

Drop Sequence Completed Time: 11:54 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg7.932663 N Longitude = 97  
deg27.432692 W PDOP = 2.00

Note:

36 1 13000.000 1 14.76 5.74 5.03 4.73 4.42 4.08 3.32 2.82 2.25 52.1  
36 1 13000.000 1 14.63 5.69 4.93 4.67 4.36 4.06 3.31 2.76 2.20 52.1  
36 1 13000.000 1 14.56 5.68 4.88 4.65 4.35 4.04 3.29 2.76 2.20 52.1  
36 1 13000.000 1 14.49 5.66 4.88 4.61 4.34 4.02 3.28 2.74 2.16 52.1  
36 1 13000.000 1 14.44 5.61 4.84 4.62 4.29 3.99 3.25 2.72 2.17 52.1  
36 1 13000.000 1 14.41 5.65 4.86 4.62 4.30 4.01 3.32 2.75 2.20 52.1

Drop Sequence Completed Time: 11:55 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg7.997329 N Longitude = 97  
deg27.492795 W PDOP = 2.00

Note:

37 1 13251.000 1 14.71 5.01 4.02 3.77 3.46 3.16 2.57 2.19 1.82 52.4  
37 1 13251.000 1 14.49 4.92 4.00 3.67 3.36 3.12 2.53 2.15 1.75 52.4  
37 1 13251.000 1 14.49 4.88 3.92 3.62 3.35 3.09 2.53 2.14 1.76 52.4  
37 1 13251.000 1 14.26 4.82 3.92 3.64 3.33 3.08 2.48 2.12 1.75 52.4  
37 1 13251.000 1 14.31 4.86 3.94 3.65 3.31 3.09 2.50 2.13 1.51 52.4  
37 1 13251.000 1 14.34 4.75 3.81 3.57 3.25 3.02 2.42 2.05 1.68 52.4

Drop Sequence Completed Time: 11:56 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg8.029924 N Longitude = 97  
deg27.522907 W PDOP = 2.00

Note:

38 1 13500.000 1 14.63 5.30 4.29 4.03 3.66 3.38 2.76 2.33 1.95 52.7  
38 1 13500.000 1 14.29 5.16 4.16 3.91 3.60 3.27 2.68 2.25 1.89 52.7  
38 1 13500.000 1 14.21 5.09 4.13 3.88 3.58 3.28 2.66 2.22 1.85 52.7  
38 1 13500.000 1 14.31 5.09 4.13 3.88 3.57 3.25 2.65 2.25 1.79 52.7  
38 1 13500.000 1 14.14 5.08 4.14 3.87 3.54 3.27 2.67 2.25 1.81 52.7  
38 1 13500.000 1 14.26 5.08 4.14 3.89 3.50 3.24 2.63 2.23 1.85 52.7

Drop Sequence Completed Time: 11:57 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg8.062418 N Longitude = 97  
deg27.552803 W PDOP = 2.20

Note:

39 1 13997.000 1 14.51 10.29 7.41 6.57 5.70 5.09 3.86 3.06 2.37 52.1  
39 1 13997.000 1 14.34 10.03 7.36 6.47 5.63 5.02 3.84 3.07 2.35 52.1  
39 1 13997.000 1 14.39 9.90 7.35 6.45 5.60 4.97 3.77 3.02 2.33 52.1  
39 1 13997.000 1 14.21 9.84 7.33 6.42 5.60 4.96 3.81 3.02 2.33 52.1  
39 1 13997.000 1 14.11 9.75 7.25 6.41 5.57 4.91 3.81 3.07 2.37 52.1  
39 1 13997.000 1 14.39 9.83 7.30 6.46 5.61 4.97 3.81 3.02 2.35 52.1

Drop Sequence Completed Time: 11:58 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.127060 N Longitude = 97  
deg27.612759 W PDOP = 2.00

Note:

40 1 14250.000 1 14.44 6.06 5.18 4.93 4.58 4.26 3.44 2.68 2.09 52.7  
40 1 14250.000 1 14.31 5.90 4.99 4.77 4.45 4.07 3.26 2.52 1.95 52.7

40 1 14250.000 1 14.29 6.00 5.14 4.88 4.54 4.20 3.39 2.67 2.08 52.7  
40 1 14250.000 1 14.39 6.01 5.17 4.89 4.57 4.23 3.39 2.66 2.07 52.7  
40 1 14250.000 1 14.29 6.05 5.21 4.94 4.66 4.30 3.46 2.73 2.17 52.7  
40 1 14250.000 1 14.29 6.02 5.20 4.92 4.60 4.24 3.41 2.66 2.09 52.7

Drop Sequence Completed Time: 11:59 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg8.159858 N Longitude = 97  
deg27.642958 W PDOP = 1.80

Note:

41 1 14502.000 1 14.21 9.31 8.05 7.55 6.76 5.85 4.29 3.40 2.60 52.7  
41 1 14502.000 1 13.64 8.97 7.80 7.33 6.54 5.70 4.21 3.38 2.60 52.7  
41 1 14502.000 1 13.74 9.02 7.88 7.37 6.60 5.73 4.23 3.37 2.64 52.7  
41 1 14502.000 1 14.44 9.45 8.29 7.74 6.93 6.01 4.43 3.55 2.75 52.7  
41 1 14502.000 1 13.94 9.12 8.02 7.49 6.71 5.84 4.27 3.41 2.69 52.7  
41 1 14502.000 1 14.68 9.53 8.37 7.81 6.99 6.10 4.48 3.62 2.77 52.7

Drop Sequence Completed Time: 12:00 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.192908 N Longitude = 97  
deg27.673448 W PDOP = 2.10

Note:

42 1 15005.000 1 16.69 10.28 7.59 6.87 6.10 5.43 4.12 3.31 2.56 52.7  
42 1 15005.000 1 15.08 9.19 6.80 6.16 5.46 4.88 3.72 3.00 2.32 52.7  
42 1 15005.000 1 14.76 8.99 6.71 6.11 5.39 4.81 3.69 2.95 2.28 52.7  
42 1 15005.000 1 14.88 8.99 6.76 6.13 5.46 4.83 3.70 2.94 2.29 52.7  
42 1 15005.000 1 14.86 8.93 6.74 6.10 5.43 4.83 3.75 2.96 2.31 52.7  
42 1 15005.000 1 14.83 8.90 6.75 6.11 5.42 4.84 3.69 2.93 2.31 52.7

Drop Sequence Completed Time: 12:01 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.258495 N Longitude = 97  
deg27.734208 W PDOP = 2.10

Note:

43 1 15255.000 1 15.18 9.25 7.29 6.58 5.77 5.11 3.84 3.07 2.42 52.7  
43 1 15255.000 1 15.03 9.05 7.21 6.51 5.72 5.05 3.81 3.05 2.38 52.7  
43 1 15255.000 1 14.98 8.97 7.20 6.49 5.69 5.03 3.84 3.08 2.43 52.7  
43 1 15255.000 1 14.93 8.92 7.13 6.46 5.67 5.00 3.83 3.04 2.38 52.7  
43 1 15255.000 1 14.91 8.86 7.08 6.44 5.67 5.00 3.78 3.03 2.38 52.7  
43 1 15255.000 1 14.88 8.81 7.08 6.41 5.62 4.96 3.78 3.02 2.37 52.7

Drop Sequence Completed Time: 12:02 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg8.291059 N Longitude = 97  
deg27.764288 W PDOP = 2.10

Note:

44 1 15502.000 1 15.48 6.99 6.07 5.75 5.29 4.88 3.92 3.27 2.64 53.7  
44 1 15502.000 1 14.86 6.72 5.80 5.53 5.10 4.71 3.81 3.14 2.52 53.7  
44 1 15502.000 1 14.93 6.72 5.86 5.55 5.12 4.72 3.78 3.18 2.58 53.7  
44 1 15502.000 1 15.01 6.73 5.87 5.58 5.16 4.71 3.80 3.15 2.53 53.7  
44 1 15502.000 1 14.83 6.71 5.86 5.52 5.09 4.70 3.79 3.16 2.55 53.7  
44 1 15502.000 1 14.83 6.60 5.79 5.46 5.06 4.65 3.72 3.09 2.52 53.7

Drop Sequence Completed Time: 12:03 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.322920 N Longitude = 97  
deg27.793978 W PDOP = 2.10

Note:

45 1 16004.000 1 15.43 7.18 6.11 5.71 5.21 4.69 3.65 2.88 2.28 52.4  
45 1 16004.000 1 14.96 6.95 5.91 5.53 5.03 4.58 3.54 2.82 2.16 52.4

45 1 16004.000 1 14.96 6.91 5.93 5.52 4.98 4.51 3.51 2.79 2.19 52.4  
45 1 16004.000 1 14.91 6.88 5.89 5.50 4.98 4.50 3.50 2.76 2.19 52.4  
45 1 16004.000 1 14.83 6.84 5.90 5.49 4.98 4.51 3.52 2.76 2.20 52.4  
45 1 16004.000 1 14.81 6.85 5.92 5.50 5.00 4.52 3.48 2.77 2.19 52.4

Drop Sequence Completed Time: 12:04 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg8.388370 N Longitude = 97  
deg27.854613 W PDOP = 2.10

Note:

46 1 16255.000 1 15.55 7.86 6.67 6.23 5.58 4.99 3.81 3.10 2.41 53.4  
46 1 16255.000 1 15.05 7.64 6.49 6.04 5.43 4.91 3.79 3.03 2.38 53.4  
46 1 16255.000 1 15.03 7.55 6.39 5.99 5.35 4.82 3.68 2.94 2.31 53.4  
46 1 16255.000 1 14.98 7.53 6.44 5.99 5.37 4.78 3.69 2.96 2.33 53.4  
46 1 16255.000 1 14.86 7.50 6.41 5.97 5.34 4.81 3.69 2.98 2.35 53.4  
46 1 16255.000 1 15.15 7.59 6.49 6.05 5.43 4.88 3.77 3.02 2.36 53.4

Drop Sequence Completed Time: 12:05 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.420910 N Longitude = 97  
deg27.884820 W PDOP = 2.40

Note:

47 1 16514.000 1 15.38 9.43 8.03 7.46 6.66 5.96 4.59 3.65 2.79 52.4  
47 1 16514.000 1 15.15 9.26 7.87 7.34 6.57 5.88 4.50 3.58 2.75 52.4  
47 1 16514.000 1 14.91 9.06 7.75 7.22 6.45 5.79 4.45 3.52 2.70 52.4  
47 1 16514.000 1 14.93 9.03 7.78 7.28 6.47 5.80 4.47 3.56 2.75 52.4  
47 1 16514.000 1 15.08 8.97 7.72 7.19 6.41 5.72 4.40 3.46 2.68 52.4  
47 1 16514.000 1 14.91 9.04 7.78 7.23 6.47 5.80 4.44 3.56 2.75 52.4

Drop Sequence Completed Time: 12:06 Air Temp (F): 55.9

GPS: Quality : DGPS Fix Latitude = 35 deg8.454599 N Longitude = 97  
deg27.915888 W PDOP = 2.10

Note:

48 1 17008.000 1 15.60 9.37 7.18 6.51 5.64 4.87 3.46 2.60 1.98 52.7  
48 1 17008.000 1 15.18 9.00 6.94 6.27 5.45 4.68 3.35 2.48 1.92 52.7  
48 1 17008.000 1 15.10 8.88 6.91 6.26 5.42 4.66 3.32 2.52 1.92 52.7  
48 1 17008.000 1 15.25 8.91 6.97 6.29 5.47 4.71 3.36 2.55 1.93 52.7  
48 1 17008.000 1 15.10 8.85 6.92 6.27 5.48 4.71 3.36 2.51 1.94 52.7  
48 1 17008.000 1 15.05 8.73 6.85 6.18 5.40 4.62 3.30 2.50 1.90 52.7

Drop Sequence Completed Time: 12:07 Air Temp (F): 56.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.518159 N Longitude = 97  
deg27.974944 W PDOP = 2.10

Note:

49 1 17250.000 1 15.45 12.99 10.28 8.93 7.56 6.39 4.38 3.32 2.49 52.7  
49 1 17250.000 1 14.91 12.41 9.93 8.71 7.41 6.26 4.24 3.21 2.47 52.7  
49 1 17250.000 1 14.88 12.31 9.88 8.67 7.33 6.21 4.22 3.22 2.44 52.7  
49 1 17250.000 1 14.96 12.25 9.91 8.67 7.36 6.24 4.24 3.22 2.44 52.7  
49 1 17250.000 1 14.91 12.20 9.85 8.66 7.35 6.24 4.23 3.17 2.41 52.7  
49 1 17250.000 1 14.81 12.14 9.82 8.60 7.31 6.17 4.22 3.20 2.43 52.7

Drop Sequence Completed Time: 12:08 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.550194 N Longitude = 97  
deg28.004615 W PDOP = 2.10

Note:

50 1 17501.000 1 15.18 7.84 6.11 5.60 5.11 4.59 3.60 2.90 2.28 50.4  
50 1 17501.000 1 15.13 7.62 5.97 5.51 5.01 4.52 3.52 2.81 2.19 50.4

50 1 17501.000 1 15.18 7.62 6.01 5.52 5.03 4.56 3.51 2.83 2.21 50.4  
50 1 17501.000 1 14.93 7.52 5.94 5.45 4.97 4.51 3.52 2.85 2.20 50.4  
50 1 17501.000 1 15.05 7.56 6.01 5.49 5.03 4.57 3.57 2.87 2.25 50.4  
50 1 17501.000 1 15.15 7.61 6.03 5.55 5.06 4.58 3.54 2.86 2.23 50.4

Drop Sequence Completed Time: 12:08 Air Temp (F): 55.9

GPS: Quality : DGPS Fix Latitude = 35 deg8.583093 N Longitude = 97  
deg28.035089 W PDOP = 2.10

Note:

51 1 18003.000 1 15.55 6.54 5.56 5.25 4.83 4.45 3.59 2.99 2.40 53.1  
51 1 18003.000 1 15.15 6.48 5.41 5.16 4.72 4.37 3.55 2.99 2.37 53.1  
51 1 18003.000 1 15.08 6.32 5.39 5.04 4.65 4.27 3.45 2.88 2.30 53.1  
51 1 18003.000 1 15.43 6.51 5.56 5.21 4.77 4.43 3.59 3.03 2.44 53.1  
51 1 18003.000 1 15.15 6.35 5.43 5.10 4.65 4.32 3.50 2.93 2.39 53.1  
51 1 18003.000 1 15.08 6.38 5.47 5.10 4.68 4.31 3.48 2.95 2.41 53.1

Drop Sequence Completed Time: 12:09 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg8.648218 N Longitude = 97  
deg28.095827 W PDOP = 2.50

Note:

52 1 18504.000 1 15.55 7.13 6.15 5.78 5.25 4.75 3.77 3.08 2.46 53.7  
52 1 18504.000 1 15.20 6.96 6.04 5.66 5.12 4.65 3.66 3.03 2.46 53.7  
52 1 18504.000 1 15.23 6.96 6.05 5.68 5.17 4.66 3.69 3.04 2.43 53.7  
52 1 18504.000 1 14.88 6.81 5.87 5.54 5.01 4.55 3.60 2.93 2.38 53.7  
52 1 18504.000 1 14.98 6.92 5.99 5.58 5.08 4.64 3.72 3.04 2.44 53.7  
52 1 18504.000 1 15.10 6.94 6.01 5.65 5.14 4.67 3.70 3.04 2.43 53.7

Drop Sequence Completed Time: 12:10 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg8.713203 N Longitude = 97  
deg28.156507 W PDOP = 2.10

Note:

53 1 18751.000 1 15.30 7.86 6.59 6.16 5.58 5.05 4.01 3.26 2.56 53.1  
53 1 18751.000 1 15.25 7.74 6.53 6.06 5.51 5.02 3.96 3.23 2.58 53.1  
53 1 18751.000 1 14.86 7.65 6.42 5.97 5.40 4.93 3.90 3.16 2.53 53.1  
53 1 18751.000 1 15.05 7.67 6.48 6.09 5.52 4.99 3.94 3.22 2.54 53.1  
53 1 18751.000 1 14.88 7.54 6.35 5.91 5.35 4.87 3.83 3.11 2.46 53.1  
53 1 18751.000 1 14.96 7.58 6.39 5.99 5.42 4.93 3.87 3.17 2.51 53.1

Drop Sequence Completed Time: 12:11 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.745263 N Longitude = 97  
deg28.186537 W PDOP = 1.80

Note:

54 1 19008.000 1 15.38 8.84 7.84 7.38 6.57 5.72 4.14 3.16 2.41 54.7  
54 1 19008.000 1 15.03 8.66 7.66 7.19 6.44 5.63 4.08 3.10 2.34 54.7  
54 1 19008.000 1 15.08 8.64 7.65 7.22 6.42 5.64 4.08 3.12 2.37 54.7  
54 1 19008.000 1 14.81 8.51 7.53 7.10 6.32 5.51 3.98 3.05 2.32 54.7  
54 1 19008.000 1 14.93 8.50 7.54 7.12 6.34 5.53 4.02 3.05 2.34 54.7  
54 1 19008.000 1 14.96 8.54 7.60 7.09 6.34 5.57 4.03 3.10 2.33 54.7

Drop Sequence Completed Time: 12:12 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg8.778665 N Longitude = 97  
deg28.217624 W PDOP = 2.10

Note:

55 1 19498.000 1 15.57 9.84 8.66 8.09 7.23 6.39 4.69 3.59 2.69 52.4  
55 1 19498.000 1 15.01 9.51 8.42 7.84 6.99 6.18 4.58 3.49 2.62 52.4

55 1 19498.000 1 15.13 9.44 8.35 7.81 6.95 6.16 4.54 3.45 2.62 52.4  
55 1 19498.000 1 15.18 9.50 8.41 7.88 7.01 6.19 4.57 3.49 2.63 52.4  
55 1 19498.000 1 15.01 9.40 8.36 7.81 6.96 6.15 4.53 3.45 2.60 52.4  
55 1 19498.000 1 14.96 9.29 8.24 7.68 6.88 6.09 4.49 3.39 2.53 52.4

Drop Sequence Completed Time: 12:13 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg8.842514 N Longitude = 97  
deg28.276916 W PDOP = 2.50

Note:

56 1 19999.000 1 15.38 10.93 9.58 8.89 7.78 6.67 4.68 3.47 2.60 52.4  
56 1 19999.000 1 15.01 10.53 9.24 8.55 7.49 6.47 4.54 3.37 2.50 52.4  
56 1 19999.000 1 14.91 10.53 9.26 8.58 7.49 6.47 4.58 3.41 2.55 52.4  
56 1 19999.000 1 14.86 10.43 9.16 8.46 7.39 6.38 4.49 3.33 2.47 52.4  
56 1 19999.000 1 14.78 10.40 9.13 8.48 7.41 6.39 4.50 3.36 2.50 52.4  
56 1 19999.000 1 14.71 10.38 9.11 8.41 7.38 6.40 4.50 3.33 2.47 52.4

Drop Sequence Completed Time: 12:14 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.907609 N Longitude = 97  
deg28.337174 W PDOP = 2.10

Note:

57 1 20499.000 1 15.38 12.04 9.81 8.80 7.50 6.31 4.30 3.11 2.35 52.4  
57 1 20499.000 1 14.91 11.65 9.53 8.58 7.27 6.13 4.16 3.05 2.33 52.4  
57 1 20499.000 1 14.88 11.54 9.40 8.44 7.19 6.07 4.11 2.98 2.25 52.4  
57 1 20499.000 1 14.78 11.38 9.33 8.39 7.16 6.05 4.10 3.00 2.25 52.4  
57 1 20499.000 1 14.63 11.35 9.35 8.40 7.14 6.02 4.13 3.01 2.27 52.4  
57 1 20499.000 1 14.68 11.32 9.30 8.37 7.11 6.01 4.13 2.98 2.28 52.4

Drop Sequence Completed Time: 12:15 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg8.972686 N Longitude = 97  
deg28.397452 W PDOP = 2.50

Note:

58 1 21003.000 1 15.13 10.60 9.15 8.14 6.87 5.87 4.12 3.11 2.38 52.4  
58 1 21003.000 1 14.96 10.32 8.87 7.90 6.73 5.72 4.01 2.97 2.25 52.4  
58 1 21003.000 1 14.81 10.24 8.80 7.85 6.64 5.65 3.94 2.95 2.23 52.4  
58 1 21003.000 1 14.91 10.13 8.75 7.80 6.59 5.63 3.96 2.97 2.28 52.4  
58 1 21003.000 1 14.68 10.04 8.70 7.75 6.55 5.58 3.91 2.94 2.26 52.4  
58 1 21003.000 1 14.73 10.09 8.70 7.78 6.59 5.65 3.94 2.96 2.26 52.4

Drop Sequence Completed Time: 12:16 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg9.038211 N Longitude = 97  
deg28.458301 W PDOP = 2.20

Note:

59 1 21505.000 1 15.28 9.87 8.65 7.90 6.86 5.90 4.18 3.12 2.36 52.1  
59 1 21505.000 1 14.81 9.51 8.34 7.69 6.67 5.73 4.06 3.03 2.30 52.1  
59 1 21505.000 1 14.71 9.46 8.30 7.62 6.64 5.70 4.01 2.99 2.28 52.1  
59 1 21505.000 1 14.68 9.40 8.23 7.58 6.57 5.68 4.02 2.98 2.29 52.1  
59 1 21505.000 1 14.68 9.37 8.21 7.55 6.54 5.61 3.97 2.97 2.25 52.1  
59 1 21505.000 1 14.63 9.34 8.21 7.55 6.56 5.63 3.97 2.98 2.22 52.1

Drop Sequence Completed Time: 12:17 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg9.103477 N Longitude = 97  
deg28.518876 W PDOP = 2.20

Note:

60 1 22002.000 1 15.20 8.68 7.54 6.96 6.15 5.40 3.96 3.07 2.35 50.4  
60 1 22002.000 1 14.96 8.49 7.38 6.83 6.04 5.30 3.88 3.04 2.32 50.4

60 1 22002.000 1 14.86 8.41 7.33 6.76 6.00 5.27 3.85 3.00 2.30 50.4  
60 1 22002.000 1 14.68 8.39 7.28 6.77 6.01 5.27 3.88 3.02 2.36 50.4  
60 1 22002.000 1 14.78 8.34 7.26 6.72 5.95 5.21 3.84 2.98 2.30 50.4  
60 1 22002.000 1 14.76 8.32 7.21 6.70 5.93 5.18 3.81 2.93 2.26 50.4

Drop Sequence Completed Time: 12:18 Air Temp (F): 53.9

GPS: Quality : DGPS Fix Latitude = 35 deg9.168359 N Longitude = 97  
deg28.578950 W PDOP = 2.20

Note:

61 1 22492.000 1 15.05 11.15 9.76 8.91 7.60 6.40 4.31 3.07 2.33 51.7  
61 1 22492.000 1 14.76 10.89 9.56 8.71 7.44 6.28 4.25 3.06 2.32 51.7  
61 1 22492.000 1 14.83 10.84 9.49 8.64 7.38 6.23 4.24 3.03 2.31 51.7  
61 1 22492.000 1 14.76 10.81 9.51 8.66 7.41 6.25 4.21 3.06 2.32 51.7  
61 1 22492.000 1 14.83 10.74 9.40 8.56 7.34 6.18 4.21 3.04 2.27 51.7  
61 1 22492.000 1 14.68 10.73 9.37 8.56 7.31 6.17 4.21 3.04 2.28 51.7

Drop Sequence Completed Time: 12:20 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg9.232115 N Longitude = 97  
deg28.638254 W PDOP = 2.60

Note:

62 1 23008.000 1 15.28 14.22 11.41 10.15 8.63 7.25 5.04 3.80 2.92 51.7  
62 1 23008.000 1 15.01 13.81 11.18 9.93 8.43 7.10 4.94 3.73 2.86 51.7  
62 1 23008.000 1 14.91 13.64 11.08 9.88 8.39 7.09 4.97 3.73 2.83 51.7  
62 1 23008.000 1 14.81 13.57 11.05 9.85 8.37 7.10 4.96 3.76 2.84 51.7  
62 1 23008.000 1 14.83 13.41 10.93 9.73 8.29 6.99 4.86 3.70 2.81 51.7  
62 1 23008.000 1 14.73 13.32 10.90 9.72 8.28 6.96 4.84 3.63 2.80 51.7

Drop Sequence Completed Time: 12:21 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg9.299042 N Longitude = 97  
deg28.700537 W PDOP = 2.60

Note:

63 1 23251.000 1 15.30 13.86 10.15 8.72 7.46 6.29 4.30 3.17 2.45 50.1  
63 1 23251.000 1 15.10 13.38 9.91 8.53 7.29 6.14 4.19 3.10 2.39 50.1  
63 1 23251.000 1 14.93 13.21 9.81 8.45 7.22 6.08 4.18 3.07 2.38 50.1  
63 1 23251.000 1 14.91 13.12 9.76 8.44 7.22 6.09 4.19 3.10 2.39 50.1  
63 1 23251.000 1 14.76 12.94 9.55 8.37 7.14 6.00 4.14 3.09 2.38 50.1  
63 1 23251.000 1 14.91 12.95 9.69 8.42 7.20 6.07 4.15 3.09 2.36 50.1

Drop Sequence Completed Time: 12:22 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg9.330709 N Longitude = 97  
deg28.729828 W PDOP = 2.20

Note:

64 1 24005.000 1 15.43 11.84 9.70 8.73 7.55 6.49 4.71 3.67 2.85 51.4  
64 1 24005.000 1 15.15 11.49 9.49 8.53 7.36 6.34 4.57 3.54 2.77 51.4  
64 1 24005.000 1 15.15 11.38 9.39 8.47 7.31 6.32 4.59 3.60 2.85 51.4  
64 1 24005.000 1 14.96 11.15 9.25 8.40 7.28 6.23 4.50 3.50 2.75 51.4  
64 1 24005.000 1 15.03 11.24 9.29 8.37 7.24 6.26 4.52 3.54 2.75 51.4  
64 1 24005.000 1 14.96 11.17 9.24 8.34 7.22 6.24 4.54 3.55 2.78 51.4

Drop Sequence Completed Time: 12:27 Air Temp (F): 55.4

GPS: Quality : GPS Fi Latitude = 35 deg9.428994 N Longitude = 97 deg28.821065  
W PDOP = 2.10

Note:

1 1 24502.000 1 15.52 11.53 10.01 8.94 8.07 6.98 5.02 3.83 2.92 52.1  
1 1 24502.000 1 15.33 11.35 9.86 8.99 7.91 6.88 4.97 3.82 2.90 52.1

1 1 24502.000 1 15.33 11.36 9.85 8.99 7.95 6.91 4.98 3.83 2.93 52.1  
1 1 24502.000 1 15.25 11.26 9.77 8.99 7.89 6.87 4.95 3.75 2.88 52.1  
1 1 24502.000 1 15.01 11.01 9.55 8.82 7.70 6.68 4.77 3.69 2.86 52.1  
1 1 24502.000 1 15.23 11.19 9.69 8.92 7.83 6.80 4.88 3.72 2.82 52.1

Drop Sequence Completed Time: 12:31 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg9.494173 N Longitude = 97  
deg28.881085 W PDOP = 2.10

Note:

2 1 24752.000 1 15.38 12.86 11.00 10.11 8.82 7.62 5.48 4.19 3.22 52.1  
2 1 24752.000 1 14.98 12.45 10.72 9.85 8.56 7.43 5.33 4.09 3.10 52.1  
2 1 24752.000 1 15.03 12.49 10.71 9.81 8.54 7.44 5.42 4.15 3.17 52.1  
2 1 24752.000 1 14.78 12.23 10.53 9.65 8.40 7.29 5.27 4.05 3.08 52.1  
2 1 24752.000 1 14.81 12.21 10.53 9.66 8.45 7.33 5.29 4.08 3.08 52.1  
2 1 24752.000 1 14.76 12.14 10.46 9.61 8.39 7.27 5.28 4.05 3.09 52.1

Drop Sequence Completed Time: 12:32 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg9.526453 N Longitude = 97  
deg28.911228 W PDOP = 2.10

Note:

3 1 25005.000 1 15.38 11.19 9.70 8.97 7.94 6.96 5.16 3.99 3.08 52.1  
3 1 25005.000 1 15.25 10.99 9.55 8.84 7.81 6.87 5.08 3.96 3.01 52.1  
3 1 25005.000 1 14.86 10.75 9.35 8.67 7.68 6.74 5.00 3.87 2.95 52.1  
3 1 25005.000 1 14.81 10.62 9.22 8.56 7.56 6.67 4.94 3.82 2.91 52.1  
3 1 25005.000 1 15.01 10.69 9.30 8.63 7.64 6.71 4.97 3.84 2.91 52.1  
3 1 25005.000 1 14.86 10.62 9.27 8.58 7.60 6.68 4.97 3.85 2.93 52.1

Drop Sequence Completed Time: 12:33 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg9.558571 N Longitude = 97  
deg28.941084 W PDOP = 2.50

Note:

## **SOUTHBOUND (SB) DATA**

M5

Date-Time: 12/ 6/2022 8:37: 6

Sensors: chop chop chop chop chop chop chop chop

Weight/spring: 3

Location: remote

Temp: 54.38

Operator: Ryan

Comments:

25	1	0.000	1	15.13	8.45	7.38	6.57	6.08	5.39	4.05	3.24	2.54	46.1
25	1	0.000	1	15.01	8.34	7.32	6.58	6.01	5.33	3.98	3.16	2.45	46.1
25	1	0.000	1	15.01	8.31	7.27	6.71	6.01	5.30	4.02	3.20	2.49	46.1
25	1	0.000	1	14.96	8.29	7.24	6.70	5.99	5.29	4.02	3.19	2.48	46.1
25	1	0.000	1	14.88	8.27	7.23	6.69	5.99	5.31	3.97	3.18	2.50	46.1
25	1	0.000	1	14.98	8.28	7.22	6.71	5.96	5.29	3.98	3.18	2.47	46.1

Drop Sequence Completed Time: 08:30 Air Temp (F): 53.3

GPS: Quality : DGPS Fix Latitude = 35 deg9.590275 N Longitude = 97 deg28.989477 W PDOP = 1.60

Note:

26	1	50.000	1	15.13	9.98	8.71	8.06	7.12	6.17	4.50	3.36	2.57	50.1
26	1	50.000	1	14.91	9.84	8.59	7.95	7.00	6.11	4.44	3.32	2.55	50.1
26	1	50.000	1	14.96	9.83	8.60	7.96	7.02	6.11	4.42	3.34	2.58	50.1
26	1	50.000	1	14.91	9.81	8.57	7.97	7.00	6.10	4.39	3.30	2.54	50.1
26	1	50.000	1	14.96	9.81	8.59	7.98	7.05	6.12	4.46	3.35	2.58	50.1
26	1	50.000	1	15.01	9.84	8.65	8.03	7.09	6.18	4.50	3.40	2.63	50.1

Drop Sequence Completed Time: 08:31 Air Temp (F): 53.7

GPS: Quality : DGPS Fix Latitude = 35 deg9.525330 N Longitude = 97 deg28.929397 W PDOP = 2.00

Note:

27	1	100.000	1	15.23	10.63	9.24	8.46	7.38	6.35	4.56	3.38	2.58	44.8
27	1	100.000	1	14.91	10.39	9.04	8.29	7.19	6.19	4.44	3.29	2.50	44.8
27	1	100.000	1	14.91	10.40	9.07	8.32	7.20	6.23	4.48	3.37	2.57	44.8
27	1	100.000	1	14.83	10.27	8.97	8.24	7.15	6.16	4.40	3.26	2.49	44.8
27	1	100.000	1	14.83	10.30	8.97	8.24	7.18	6.20	4.44	3.31	2.50	44.8
27	1	100.000	1	14.86	10.22	8.90	8.19	7.11	6.13	4.39	3.29	2.48	44.8

Drop Sequence Completed Time: 08:33 Air Temp (F): 53.7

GPS: Quality : DGPS Fix Latitude = 35 deg9.460030 N Longitude = 97 deg28.868747 W PDOP = 1.60

Note:

1	1	250.000	1	15.55	10.71	9.39	8.64	7.50	6.50	4.66	3.48	2.64	48.8
1	1	250.000	1	15.25	10.59	9.28	8.55	7.44	6.41	4.60	3.43	2.65	48.8
1	1	250.000	1	15.05	10.39	9.09	8.37	7.28	6.28	4.49	3.38	2.58	48.8
1	1	250.000	1	15.10	10.37	9.09	8.40	7.31	6.31	4.53	3.39	2.57	48.8
1	1	250.000	1	15.03	10.28	9.05	8.34	7.28	6.30	4.51	3.38	2.59	48.8
1	1	250.000	1	15.05	10.39	9.09	8.38	7.32	6.29	4.52	3.36	2.56	48.8

Drop Sequence Completed Time: 08:37 Air Temp (F): 54.2

GPS: Quality : DGPS Fix Latitude = 35 deg9.460183 N Longitude = 97 deg28.868742 W PDOP = 2.10

Note:

2	1	503.000	1	15.38	10.36	8.44	7.65	6.70	5.80	4.14	3.10	2.42	49.4
2	1	503.000	1	15.18	10.14	8.35	7.58	6.63	5.72	4.11	3.09	2.43	49.4

2 1 503.000 1 15.05 10.00 8.27 7.52 6.56 5.68 4.10 3.06 2.39 49.4  
2 1 503.000 1 15.35 10.15 8.41 7.64 6.69 5.79 4.16 3.12 2.42 49.4  
2 1 503.000 1 15.23 10.03 8.30 7.56 6.59 5.70 4.11 3.09 2.41 49.4  
2 1 503.000 1 15.10 9.93 8.26 7.52 6.56 5.69 4.06 3.06 2.38 49.4

Drop Sequence Completed Time: 08:39 Air Temp (F): 52.0

GPS: Quality : DGPS Fix Latitude = 35 deg9.394937 N Longitude = 97  
deg28.807926 W PDOP = 2.10

Note:

3 1 1503.000 1 15.55 8.72 7.70 6.82 6.38 5.64 4.19 3.27 2.52 50.8  
3 1 1503.000 1 15.10 8.51 7.51 6.82 6.26 5.52 4.09 3.20 2.50 50.8  
3 1 1503.000 1 15.20 8.50 7.54 6.88 6.25 5.56 4.13 3.24 2.53 50.8  
3 1 1503.000 1 15.08 8.45 7.45 6.73 6.18 5.46 4.07 3.17 2.45 50.8  
3 1 1503.000 1 14.93 8.39 7.42 6.82 6.17 5.46 4.06 3.21 2.47 50.8  
3 1 1503.000 1 15.23 8.49 7.49 6.86 6.21 5.51 4.08 3.19 2.48 50.8

Drop Sequence Completed Time: 08:41 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg9.264794 N Longitude = 97  
deg28.687089 W PDOP = 2.10

Note:

4 1 2001.000 1 15.33 17.06 14.06 12.13 9.87 7.94 5.07 3.44 2.65 54.1  
4 1 2001.000 1 15.01 16.39 13.62 11.78 9.59 7.73 4.91 3.39 2.56 54.1  
4 1 2001.000 1 14.83 16.17 13.54 11.70 9.54 7.70 4.91 3.38 2.66 54.1  
4 1 2001.000 1 14.88 16.11 13.49 11.73 9.51 7.67 4.89 3.37 2.53 54.1  
4 1 2001.000 1 14.73 16.00 13.39 11.65 9.47 7.65 4.87 3.36 2.58 54.1  
4 1 2001.000 1 14.96 16.17 13.58 11.80 9.63 7.75 4.95 3.41 2.61 54.1

Drop Sequence Completed Time: 08:43 Air Temp (F): 54.0

GPS: Quality : DGPS Fix Latitude = 35 deg9.199906 N Longitude = 97  
deg28.627088 W PDOP = 2.20

Note:

5 1 3007.000 1 15.33 11.10 8.89 7.67 6.87 5.93 4.18 3.16 2.42 55.4  
5 1 3007.000 1 15.01 10.73 8.65 7.67 6.73 5.77 4.08 3.09 2.35 55.4  
5 1 3007.000 1 15.05 10.71 8.66 7.60 6.71 5.77 4.12 3.09 2.35 55.4  
5 1 3007.000 1 15.10 10.65 8.63 7.75 6.74 5.77 4.11 3.11 2.36 55.4  
5 1 3007.000 1 15.01 10.56 8.54 7.70 6.65 5.71 4.04 3.08 2.36 55.4  
5 1 3007.000 1 14.91 10.45 8.49 7.64 6.61 5.67 4.06 3.03 2.34 55.4

Drop Sequence Completed Time: 08:45 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg9.068795 N Longitude = 97  
deg28.505911 W PDOP = 2.70

Note:

6 1 3505.000 1 15.28 7.42 6.41 5.87 5.26 4.72 3.61 2.85 2.22 56.0  
6 1 3505.000 1 15.03 7.27 6.32 5.82 5.18 4.61 3.53 2.82 2.23 56.0  
6 1 3505.000 1 15.05 7.25 6.27 5.79 5.18 4.60 3.49 2.81 2.20 56.0  
6 1 3505.000 1 14.91 7.20 6.23 5.76 5.14 4.58 3.49 2.80 2.20 56.0  
6 1 3505.000 1 14.93 7.22 6.26 5.76 5.14 4.58 3.51 2.80 2.23 56.0  
6 1 3505.000 1 14.86 7.18 6.23 5.74 5.14 4.59 3.50 2.80 2.21 56.0

Drop Sequence Completed Time: 08:46 Air Temp (F): 53.2

GPS: Quality : DGPS Fix Latitude = 35 deg9.004444 N Longitude = 97  
deg28.445549 W PDOP = 2.20

Note:

7 1 4000.000 1 15.15 13.24 10.64 8.63 7.53 6.24 4.19 3.14 2.41 54.4  
7 1 4000.000 1 15.23 13.10 10.60 7.96 7.52 6.22 4.21 3.15 2.39 54.4

7 1 4000.000 1 15.01 12.81 10.40 8.76 7.42 6.13 4.13 3.10 2.39 54.4  
7 1 4000.000 1 14.88 12.69 10.31 8.78 7.36 6.08 4.11 3.05 2.34 54.4  
7 1 4000.000 1 14.83 12.62 10.26 8.72 7.34 6.05 4.11 3.07 2.38 54.4  
7 1 4000.000 1 14.86 12.61 10.28 8.83 7.33 6.08 4.12 3.07 2.36 54.4

Drop Sequence Completed Time: 08:47 Air Temp (F): 54.4

GPS: Quality : DGPS Fix Latitude = 35 deg8.939827 N Longitude = 97  
deg28.385953 W PDOP = 2.30

Note:

8 1 4503.000 1 15.40 11.92 9.83 8.92 7.71 6.64 4.72 3.54 2.67 54.7  
8 1 4503.000 1 14.93 11.53 9.56 8.70 7.50 6.46 4.60 3.47 2.60 54.7  
8 1 4503.000 1 14.91 11.47 9.52 8.64 7.47 6.40 4.57 3.42 2.57 54.7  
8 1 4503.000 1 15.01 11.43 9.48 8.65 7.51 6.46 4.57 3.46 2.58 54.7  
8 1 4503.000 1 14.81 11.31 9.44 8.58 7.42 6.42 4.58 3.44 2.60 54.7  
8 1 4503.000 1 15.01 11.41 9.52 8.62 7.47 6.46 4.60 3.45 2.62 54.7

Drop Sequence Completed Time: 08:48 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.874495 N Longitude = 97  
deg28.325394 W PDOP = 2.30

Note:

9 1 5001.000 1 15.23 12.17 9.60 8.60 7.41 6.27 4.38 3.27 2.48 53.1  
9 1 5001.000 1 15.05 11.84 9.41 8.42 7.26 6.14 4.30 3.17 2.38 53.1  
9 1 5001.000 1 14.93 11.72 9.32 8.39 7.21 6.11 4.28 3.19 2.39 53.1  
9 1 5001.000 1 14.96 11.69 9.36 8.42 7.24 6.14 4.29 3.23 2.42 53.1  
9 1 5001.000 1 14.98 11.67 9.37 8.42 7.25 6.13 4.29 3.22 2.42 53.1  
9 1 5001.000 1 15.18 11.63 9.31 8.38 7.21 6.12 4.28 3.20 2.42 53.1

Drop Sequence Completed Time: 08:49 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.809461 N Longitude = 97  
deg28.265272 W PDOP = 2.30

Note:

10 1 5501.000 1 15.33 7.16 6.21 5.83 5.29 4.79 3.81 3.16 2.55 52.4  
10 1 5501.000 1 15.05 6.99 6.12 5.72 5.19 4.74 3.74 3.11 2.52 52.4  
10 1 5501.000 1 15.08 6.93 6.09 5.68 5.17 4.69 3.74 3.12 2.51 52.4  
10 1 5501.000 1 15.01 6.89 6.07 5.71 5.16 4.70 3.73 3.12 2.51 52.4  
10 1 5501.000 1 15.03 6.86 6.03 5.65 5.14 4.67 3.71 3.07 2.47 52.4  
10 1 5501.000 1 14.88 6.81 6.02 5.63 5.13 4.66 3.71 3.10 2.50 52.4

Drop Sequence Completed Time: 08:50 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.744281 N Longitude = 97  
deg28.205130 W PDOP = 2.90

Note:

11 1 6004.000 1 15.20 9.11 8.02 7.40 6.48 5.31 3.78 3.06 2.43 52.4  
11 1 6004.000 1 15.05 8.94 7.85 7.27 6.33 5.18 3.70 3.01 2.40 52.4  
11 1 6004.000 1 15.03 8.90 7.81 7.24 6.30 5.16 3.72 2.99 2.38 52.4  
11 1 6004.000 1 14.98 8.87 7.81 7.23 6.30 5.18 3.70 2.98 2.40 52.4  
11 1 6004.000 1 14.98 8.84 7.79 7.22 6.29 5.16 3.70 3.00 2.39 52.4  
11 1 6004.000 1 14.93 8.84 7.82 7.23 6.29 5.17 3.69 2.99 2.37 52.4

Drop Sequence Completed Time: 08:51 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg8.678521 N Longitude = 97  
deg28.144785 W PDOP = 2.40

Note:

12 1 6501.000 1 15.25 7.54 6.67 6.34 5.90 5.48 4.44 3.61 2.93 52.4  
12 1 6501.000 1 15.08 7.50 6.63 6.27 5.85 5.43 4.41 3.58 2.89 52.4

12 1 6501.000 1 15.10 7.45 6.60 6.26 5.82 5.42 4.39 3.56 2.90 52.4  
12 1 6501.000 1 14.93 7.38 6.58 6.24 5.79 5.37 4.38 3.56 2.87 52.4  
12 1 6501.000 1 15.01 7.39 6.53 6.21 5.78 5.36 4.39 3.56 2.87 52.4  
12 1 6501.000 1 15.03 7.38 6.55 6.24 5.77 5.38 4.36 3.53 2.87 52.4

Drop Sequence Completed Time: 08:52 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg8.613449 N Longitude = 97  
deg28.084926 W PDOP = 2.40

Note:

13 1 7017.000 1 15.03 18.84 14.86 10.53 9.43 7.50 4.94 3.68 2.84 52.1  
13 1 7017.000 1 14.88 18.16 14.48 11.25 9.20 7.30 4.80 3.59 2.76 52.1  
13 1 7017.000 1 14.88 18.12 14.51 11.73 9.23 7.34 4.82 3.59 2.77 52.1  
13 1 7017.000 1 14.76 17.96 14.37 11.62 9.17 7.25 4.78 3.60 2.72 52.1  
13 1 7017.000 1 14.96 17.90 14.36 11.59 9.17 7.27 4.76 3.57 2.70 52.1  
13 1 7017.000 1 14.73 17.85 14.30 11.60 9.13 7.26 4.77 3.59 2.73 52.1

Drop Sequence Completed Time: 08:53 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg8.546229 N Longitude = 97  
deg28.022700 W PDOP = 2.40

Note:

14 1 7497.000 1 15.20 8.24 7.28 6.83 6.22 5.61 4.36 3.44 2.60 52.7  
14 1 7497.000 1 15.15 8.18 7.25 6.79 6.16 5.57 4.31 3.46 2.60 52.7  
14 1 7497.000 1 14.96 8.05 7.10 6.66 6.07 5.47 4.21 3.36 2.52 52.7  
14 1 7497.000 1 15.10 8.14 7.18 6.75 6.13 5.51 4.28 3.39 2.55 52.7  
14 1 7497.000 1 14.88 8.06 7.18 6.72 6.13 5.54 4.26 3.42 2.59 52.7  
14 1 7497.000 1 14.91 8.03 7.14 6.66 6.09 5.48 4.23 3.33 2.53 52.7

Drop Sequence Completed Time: 08:55 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg8.483675 N Longitude = 97  
deg27.964822 W PDOP = 3.00

Note:

15 1 7999.000 1 15.43 7.69 6.72 5.89 5.61 5.00 3.90 3.15 2.53 52.1  
15 1 7999.000 1 15.08 7.39 6.45 5.88 5.39 4.82 3.69 2.97 2.40 52.1  
15 1 7999.000 1 15.03 7.48 6.55 5.98 5.45 4.90 3.82 3.12 2.48 52.1  
15 1 7999.000 1 14.86 7.43 6.50 5.97 5.45 4.86 3.78 3.09 2.47 52.1  
15 1 7999.000 1 15.15 7.52 6.56 6.03 5.49 4.93 3.82 3.14 2.53 52.1  
15 1 7999.000 1 14.93 7.44 6.53 5.93 5.46 4.90 3.76 3.12 2.51 52.1

Drop Sequence Completed Time: 08:56 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.418443 N Longitude = 97  
deg27.904309 W PDOP = 2.40

Note:

16 1 8501.000 1 15.33 9.44 7.63 6.97 6.25 5.34 3.69 2.98 2.39 53.1  
16 1 8501.000 1 15.08 9.24 7.52 6.86 6.14 5.25 3.61 2.95 2.37 53.1  
16 1 8501.000 1 14.98 9.14 7.44 6.83 6.11 5.21 3.60 2.97 2.37 53.1  
16 1 8501.000 1 15.08 9.14 7.48 6.86 6.13 5.26 3.61 2.97 2.39 53.1  
16 1 8501.000 1 14.98 9.06 7.44 6.81 6.08 5.22 3.58 2.92 2.34 53.1  
16 1 8501.000 1 15.08 9.10 7.45 6.83 6.11 5.23 3.58 2.94 2.37 53.1

Drop Sequence Completed Time: 08:57 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg8.353066 N Longitude = 97  
deg27.843680 W PDOP = 3.10

Note:

17 1 9000.000 1 15.25 11.35 9.17 8.29 7.23 6.23 4.36 3.12 2.34 53.4  
17 1 9000.000 1 15.10 11.08 9.01 8.16 7.15 6.18 4.28 3.09 2.31 53.4

17 1 9000.000 1 14.86 10.90 8.91 8.06 7.03 6.09 4.20 3.05 2.30 53.4  
17 1 9000.000 1 14.93 10.89 8.89 8.05 7.01 6.10 4.25 3.05 2.29 53.4  
17 1 9000.000 1 14.86 10.78 8.82 7.97 6.99 6.04 4.21 3.02 2.30 53.4  
17 1 9000.000 1 14.86 10.83 8.87 8.03 7.04 6.07 4.22 3.05 2.27 53.4

Drop Sequence Completed Time: 08:58 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg8.288092 N Longitude = 97  
deg27.783532 W PDOP = 2.50

Note:

18 1 9501.000 1 15.25 12.52 11.18 9.75 8.25 6.59 4.45 3.27 2.45 53.1  
18 1 9501.000 1 15.01 12.16 10.83 9.80 8.04 6.43 4.38 3.19 2.39 53.1  
18 1 9501.000 1 14.96 12.07 10.79 9.80 8.01 6.43 4.37 3.19 2.41 53.1  
18 1 9501.000 1 14.91 12.02 10.76 9.75 7.97 6.40 4.37 3.19 2.40 53.1  
18 1 9501.000 1 14.91 11.93 10.72 9.73 7.96 6.37 4.34 3.20 2.40 53.1  
18 1 9501.000 1 14.88 11.94 10.69 9.72 7.95 6.39 4.34 3.20 2.37 53.1

Drop Sequence Completed Time: 08:59 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg8.222790 N Longitude = 97  
deg27.723277 W PDOP = 3.20

Note:

19 1 10002.000 1 15.25 8.00 6.76 6.18 5.49 4.85 3.67 2.88 2.21 51.7  
19 1 10002.000 1 15.01 7.87 6.64 6.07 5.42 4.78 3.60 2.85 2.20 51.7  
19 1 10002.000 1 15.03 7.76 6.58 6.04 5.36 4.72 3.59 2.83 2.19 51.7  
19 1 10002.000 1 14.96 7.78 6.57 6.05 5.34 4.73 3.57 2.84 2.18 51.7  
19 1 10002.000 1 14.93 7.76 6.58 6.07 5.38 4.73 3.57 2.83 2.18 51.7  
19 1 10002.000 1 14.98 7.74 6.55 6.03 5.36 4.73 3.58 2.85 2.18 51.7

Drop Sequence Completed Time: 09:00 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg8.157616 N Longitude = 97  
deg27.662789 W PDOP = 2.50

Note:

20 1 10502.000 1 15.33 7.55 6.16 5.68 5.10 4.57 3.58 2.92 2.32 50.4  
20 1 10502.000 1 15.10 7.43 6.07 5.61 5.02 4.54 3.49 2.87 2.28 50.4  
20 1 10502.000 1 15.01 7.37 5.98 5.56 4.97 4.48 3.47 2.86 2.30 50.4  
20 1 10502.000 1 15.05 7.34 6.02 5.55 4.99 4.47 3.47 2.86 2.23 50.4  
20 1 10502.000 1 15.03 7.33 6.04 5.54 4.97 4.48 3.47 2.85 2.28 50.4  
20 1 10502.000 1 15.01 7.34 6.02 5.54 5.07 4.47 3.48 2.85 2.26 50.4

Drop Sequence Completed Time: 09:01 Air Temp (F): 55.1

GPS: Quality : DGPS Fix Latitude = 35 deg8.092568 N Longitude = 97  
deg27.602372 W PDOP = 2.50

Note:

21 1 11000.000 1 15.48 5.88 5.15 4.56 3.77 3.30 2.59 2.17 1.84 53.7  
21 1 11000.000 1 15.03 5.71 5.02 4.44 3.69 3.18 2.52 2.14 1.82 53.7  
21 1 11000.000 1 15.05 5.70 4.99 4.42 3.68 3.18 2.51 2.16 1.84 53.7  
21 1 11000.000 1 15.05 5.65 4.95 4.36 3.65 3.18 2.49 2.11 1.80 53.7  
21 1 11000.000 1 15.08 5.64 4.96 4.39 3.65 3.14 2.49 2.14 1.83 53.7  
21 1 11000.000 1 15.05 5.65 4.98 4.41 3.69 3.21 2.53 2.17 1.89 53.7

Drop Sequence Completed Time: 09:02 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg8.027824 N Longitude = 97  
deg27.542280 W PDOP = 2.50

Note:

22 1 11501.000 1 15.52 5.42 4.60 4.25 3.88 3.54 2.89 2.44 1.99 54.1  
22 1 11501.000 1 15.08 5.25 4.46 4.11 3.75 3.44 2.79 2.35 1.92 54.1

22 1 11501.000 1 15.10 5.26 4.45 4.14 3.75 3.44 2.81 2.36 1.93 54.1  
22 1 11501.000 1 14.93 5.19 4.40 4.07 3.69 3.39 2.79 2.32 1.89 54.1  
22 1 11501.000 1 15.08 5.22 4.43 4.10 3.77 3.44 2.80 2.38 1.94 54.1  
22 1 11501.000 1 14.98 5.17 4.37 4.05 3.71 3.40 2.74 2.29 1.89 54.1

Drop Sequence Completed Time: 09:03 Air Temp (F): 55.9

GPS: Quality : DGPS Fix Latitude = 35 deg7.962627 N Longitude = 97  
deg27.481622 W PDOP = 3.30

Note:

23 1 12001.000 1 15.43 4.34 3.85 3.63 3.42 3.23 2.76 2.45 2.06 52.1  
23 1 12001.000 1 15.18 4.30 3.80 3.56 3.39 3.19 2.73 2.42 2.01 52.1  
23 1 12001.000 1 15.08 4.30 3.80 3.56 3.37 3.17 2.73 2.42 2.01 52.1  
23 1 12001.000 1 15.01 4.30 3.79 3.57 3.36 3.16 2.69 2.40 2.04 52.1  
23 1 12001.000 1 15.01 4.26 3.78 3.54 3.34 3.17 2.72 2.35 2.04 52.1  
23 1 12001.000 1 15.01 4.25 3.78 3.57 3.34 3.14 2.71 2.39 2.05 52.1

Drop Sequence Completed Time: 09:05 Air Temp (F): 54.9

GPS: Quality : DGPS Fix Latitude = 35 deg7.897484 N Longitude = 97  
deg27.421273 W PDOP = 2.50

Note:

24 1 12499.000 1 15.13 9.00 7.04 6.06 5.20 4.56 3.55 2.97 2.38 50.8  
24 1 12499.000 1 15.20 8.93 7.02 6.08 5.22 4.59 3.57 2.98 2.39 50.8  
24 1 12499.000 1 15.13 8.80 6.95 6.00 5.16 4.53 3.52 2.90 2.37 50.8  
24 1 12499.000 1 15.10 8.72 6.91 6.00 5.14 4.53 3.52 2.92 2.35 50.8  
24 1 12499.000 1 15.05 8.73 6.89 6.01 5.16 4.55 3.53 2.92 2.35 50.8  
24 1 12499.000 1 15.08 8.70 6.87 6.00 5.14 4.53 3.53 2.91 2.36 50.8

Drop Sequence Completed Time: 09:06 Air Temp (F): 54.0

GPS: Quality : DGPS Fix Latitude = 35 deg7.832770 N Longitude = 97  
deg27.361356 W PDOP = 2.50

Note:

25 1 13002.000 1 15.55 5.88 5.06 4.77 4.33 4.00 3.31 2.77 2.28 51.4  
25 1 13002.000 1 15.18 5.75 4.96 4.63 4.26 3.94 3.23 2.73 2.25 51.4  
25 1 13002.000 1 15.18 5.73 4.91 4.63 4.21 3.93 3.22 2.73 2.23 51.4  
25 1 13002.000 1 15.05 5.69 4.93 4.59 4.20 3.93 3.19 2.71 2.21 51.4  
25 1 13002.000 1 15.10 5.69 4.89 4.59 4.20 3.88 3.19 2.69 2.25 51.4  
25 1 13002.000 1 15.08 5.64 4.84 4.53 4.16 3.84 3.14 2.64 2.17 51.4

Drop Sequence Completed Time: 09:07 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg7.767322 N Longitude = 97  
deg27.300622 W PDOP = 2.50

Note:

26 1 13499.000 1 15.40 7.22 6.52 5.95 5.20 4.18 3.34 2.60 2.15 52.1  
26 1 13499.000 1 15.05 7.02 6.30 5.81 5.07 4.10 3.26 2.52 2.10 52.1  
26 1 13499.000 1 14.98 6.96 6.26 5.77 5.01 4.05 3.27 2.53 2.06 52.1  
26 1 13499.000 1 15.10 6.95 6.26 5.78 5.08 4.08 3.35 2.54 2.06 52.1  
26 1 13499.000 1 14.83 6.89 6.18 5.72 5.00 4.02 3.31 2.51 2.03 52.1  
26 1 13499.000 1 14.91 6.86 6.22 5.72 5.01 4.04 3.28 2.51 2.07 52.1

Drop Sequence Completed Time: 09:08 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg7.702340 N Longitude = 97  
deg27.240703 W PDOP = 3.40

Note:

27 1 14000.000 1 15.52 5.25 4.35 3.94 3.54 3.22 2.99 2.27 1.98 55.0  
27 1 14000.000 1 15.38 5.13 4.25 3.88 3.47 3.16 2.92 2.28 1.93 55.0

27 1 14000.000 1 15.15 5.11 4.23 3.88 3.47 3.15 2.94 2.28 1.91 55.0  
27 1 14000.000 1 15.01 5.04 4.22 3.84 3.45 3.14 2.97 2.25 1.92 55.0  
27 1 14000.000 1 15.05 5.07 4.19 3.83 3.44 3.09 2.99 2.23 1.91 55.0  
27 1 14000.000 1 15.05 5.08 4.22 3.89 3.44 3.15 2.94 2.27 1.95 55.0

Drop Sequence Completed Time: 09:09 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.637246 N Longitude = 97  
deg27.180339 W PDOP = 2.50

Note:

28 1 14501.000 1 15.43 6.28 5.20 4.82 4.43 4.10 3.45 2.96 2.46 52.4  
28 1 14501.000 1 15.01 6.08 5.09 4.65 4.27 3.99 3.35 2.88 2.40 52.4  
28 1 14501.000 1 15.08 6.07 5.05 4.64 4.27 4.00 3.35 2.87 2.36 52.4  
28 1 14501.000 1 15.01 6.05 5.00 4.62 4.25 3.96 3.31 2.85 2.35 52.4  
28 1 14501.000 1 15.03 6.06 5.04 4.64 4.26 3.98 3.31 2.85 2.37 52.4  
28 1 14501.000 1 14.98 6.04 5.04 4.64 4.25 3.98 3.34 2.84 2.38 52.4

Drop Sequence Completed Time: 09:10 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg7.572204 N Longitude = 97  
deg27.119987 W PDOP = 2.50

Note:

29 1 15000.000 1 15.25 4.51 3.42 3.07 2.83 2.69 2.31 1.64 1.46 53.1  
29 1 15000.000 1 15.30 4.51 3.48 3.10 2.84 2.69 2.32 1.64 1.47 53.1  
29 1 15000.000 1 15.13 4.46 3.44 3.09 2.82 2.69 2.29 1.65 1.40 53.1  
29 1 15000.000 1 15.03 4.38 3.36 3.05 2.78 2.65 2.28 1.65 1.45 53.1  
29 1 15000.000 1 15.08 4.38 3.37 3.03 2.82 2.67 2.26 1.62 1.48 53.1  
29 1 15000.000 1 15.15 4.39 3.40 3.08 2.81 2.64 2.29 1.62 1.46 53.1

Drop Sequence Completed Time: 09:11 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg7.507095 N Longitude = 97  
deg27.059862 W PDOP = 2.50

Note:

30 1 15501.000 1 15.28 4.86 3.65 3.32 3.00 2.75 2.22 1.90 1.56 51.7  
30 1 15501.000 1 15.10 4.73 3.59 3.25 2.94 2.71 2.25 1.90 1.55 51.7  
30 1 15501.000 1 15.23 4.74 3.58 3.26 2.94 2.71 2.24 1.92 1.54 51.7  
30 1 15501.000 1 15.18 4.72 3.59 3.26 2.95 2.72 2.22 1.87 1.53 51.7  
30 1 15501.000 1 15.15 4.72 3.60 3.30 2.93 2.71 2.23 1.88 1.55 51.7  
30 1 15501.000 1 14.98 4.67 3.54 3.22 2.91 2.71 2.20 1.87 1.50 51.7

Drop Sequence Completed Time: 09:13 Air Temp (F): 53.7

GPS: Quality : DGPS Fix Latitude = 35 deg7.441917 N Longitude = 97  
deg26.999568 W PDOP = 2.50

Note:

31 1 16000.000 1 15.13 7.23 5.10 4.37 3.66 3.19 2.34 1.76 1.27 52.7  
31 1 16000.000 1 15.03 7.08 5.03 4.30 3.63 3.15 2.32 1.76 1.26 52.7  
31 1 16000.000 1 14.93 6.95 4.97 4.25 3.59 3.12 2.28 1.72 1.25 52.7  
31 1 16000.000 1 14.98 6.89 4.94 4.27 3.61 3.12 2.31 1.77 1.27 52.7  
31 1 16000.000 1 15.01 6.90 4.94 4.23 3.58 3.10 2.30 1.75 1.24 52.7  
31 1 16000.000 1 14.96 6.89 4.97 4.28 3.58 3.13 2.30 1.74 1.25 52.7

Drop Sequence Completed Time: 09:14 Air Temp (F): 54.6

GPS: Quality : DGPS Fix Latitude = 35 deg7.376993 N Longitude = 97  
deg26.939615 W PDOP = 2.50

Note:

32 1 16500.000 1 15.35 6.20 5.10 4.69 4.27 3.91 3.11 2.61 2.09 53.1  
32 1 16500.000 1 14.96 6.05 4.99 4.58 4.16 3.81 3.11 2.54 2.06 53.1

32 1 16500.000 1 14.86 6.01 4.96 4.58 4.16 3.79 3.05 2.55 2.01 53.1  
32 1 16500.000 1 14.88 5.98 4.97 4.57 4.13 3.81 3.05 2.53 2.03 53.1  
32 1 16500.000 1 14.93 6.02 4.98 4.59 4.18 3.82 3.07 2.55 2.06 53.1  
32 1 16500.000 1 14.83 5.97 4.96 4.59 4.14 3.78 3.02 2.54 2.05 53.1

Drop Sequence Completed Time: 09:15 Air Temp (F): 54.7

GPS: Quality : DGPS Fix Latitude = 35 deg7.311912 N Longitude = 97  
deg26.879378 W PDOP = 3.50

Note:

33 1 16853.000 1 15.30 5.38 4.52 4.12 3.75 3.44 2.79 2.36 1.94 53.1  
33 1 16853.000 1 14.93 5.25 4.42 4.03 3.65 3.37 2.73 2.31 1.89 53.1  
33 1 16853.000 1 15.01 5.20 4.35 4.00 3.66 3.34 2.66 2.24 1.89 53.1  
33 1 16853.000 1 14.83 5.14 4.30 3.92 3.58 3.29 2.67 2.23 1.81 53.1  
33 1 16853.000 1 14.91 5.18 4.31 3.93 3.59 3.26 2.62 2.18 1.83 53.1  
33 1 16853.000 1 14.96 5.15 4.35 3.97 3.61 3.32 2.67 2.27 1.82 53.1

Drop Sequence Completed Time: 09:16 Air Temp (F): 53.5

GPS: Quality : DGPS Fix Latitude = 35 deg7.265977 N Longitude = 97  
deg26.836842 W PDOP = 3.40

Note:

34 1 17906.000 1 15.48 6.29 4.86 4.32 3.99 3.74 3.13 2.67 2.23 54.1  
34 1 17906.000 1 15.10 6.14 4.77 4.23 3.95 3.69 3.07 2.61 2.19 54.1  
34 1 17906.000 1 14.93 6.01 4.70 4.22 3.88 3.67 3.05 2.60 2.15 54.1  
34 1 17906.000 1 15.01 6.06 4.76 4.24 3.92 3.70 3.05 2.60 2.17 54.1  
34 1 17906.000 1 15.01 6.04 4.71 4.23 3.90 3.68 3.03 2.61 2.18 54.1  
34 1 17906.000 1 14.98 5.97 4.69 4.21 3.91 3.66 3.05 2.60 2.14 54.1

Drop Sequence Completed Time: 09:18 Air Temp (F): 55.4

GPS: Quality : DGPS Fix Latitude = 35 deg7.128915 N Longitude = 97  
deg26.709851 W PDOP = 2.40

Note:

35 1 18006.000 1 15.25 6.24 5.09 4.63 4.21 3.91 3.24 2.76 2.29 53.1  
35 1 18006.000 1 14.93 6.07 4.99 4.55 4.13 3.86 3.29 2.71 2.28 53.1  
35 1 18006.000 1 14.93 6.06 4.99 4.52 4.13 3.81 3.16 2.71 2.26 53.1  
35 1 18006.000 1 14.91 5.99 4.90 4.47 4.08 3.74 3.29 2.66 2.21 53.1  
35 1 18006.000 1 14.86 6.01 4.98 4.48 4.11 3.80 3.12 2.69 2.24 53.1  
35 1 18006.000 1 14.78 6.02 4.93 4.45 4.10 3.80 3.24 2.65 2.21 53.1

Drop Sequence Completed Time: 09:19 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg7.115865 N Longitude = 97  
deg26.697852 W PDOP = 2.40

Note:

36 1 18505.000 1 15.30 5.92 5.25 4.88 4.47 4.07 3.19 2.65 2.18 54.4  
36 1 18505.000 1 15.01 5.83 5.17 4.78 4.38 4.00 3.11 2.60 2.15 54.4  
36 1 18505.000 1 14.96 5.74 5.08 4.73 4.33 3.97 3.09 2.58 2.13 54.4  
36 1 18505.000 1 14.78 5.72 5.08 4.72 4.34 3.96 3.09 2.59 2.12 54.4  
36 1 18505.000 1 14.93 5.71 5.08 4.71 4.34 3.96 3.08 2.56 2.11 54.4  
36 1 18505.000 1 14.78 5.70 5.07 4.72 4.30 3.95 3.07 2.56 2.11 54.4

Drop Sequence Completed Time: 09:20 Air Temp (F): 55.9

GPS: Quality : DGPS Fix Latitude = 35 deg7.051036 N Longitude = 97  
deg26.637687 W PDOP = 1.90

Note:

37 1 19000.000 1 15.30 5.66 4.42 3.97 3.53 3.17 2.46 1.94 1.47 55.4  
37 1 19000.000 1 14.93 5.50 4.32 3.86 3.44 3.11 2.40 1.91 1.45 55.4

37 1 19000.000 1 14.81 5.45 4.27 3.83 3.40 3.08 2.37 1.88 1.45 55.4  
37 1 19000.000 1 14.81 5.44 4.27 3.83 3.41 3.07 2.39 1.89 1.44 55.4  
37 1 19000.000 1 14.73 5.37 4.22 3.80 3.40 3.04 2.35 1.87 1.45 55.4  
37 1 19000.000 1 14.76 5.41 4.26 3.80 3.40 3.05 2.38 1.89 1.45 55.4

Drop Sequence Completed Time: 09:21 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.986402 N Longitude = 97  
deg26.577083 W PDOP = 3.40

Note:

38 1 19507.000 1 15.38 5.55 4.37 3.95 3.52 3.16 2.37 1.81 1.36 55.4  
38 1 19507.000 1 14.98 5.35 4.26 3.82 3.40 3.04 2.29 1.76 1.28 55.4  
38 1 19507.000 1 15.01 5.33 4.22 3.80 3.39 3.01 2.27 1.75 1.30 55.4  
38 1 19507.000 1 14.93 5.30 4.23 3.79 3.39 3.03 2.29 1.75 1.29 55.4  
38 1 19507.000 1 14.98 5.34 4.21 3.81 3.38 3.02 2.29 1.77 1.27 55.4  
38 1 19507.000 1 14.98 5.32 4.22 3.81 3.39 3.04 2.29 1.79 1.29 55.4

Drop Sequence Completed Time: 09:22 Air Temp (F): 54.2

GPS: Quality : DGPS Fix Latitude = 35 deg6.920487 N Longitude = 97  
deg26.516872 W PDOP = 1.90

Note:

39 1 20008.000 1 15.28 6.80 5.56 4.91 4.26 3.87 3.04 2.44 1.87 50.1  
39 1 20008.000 1 15.08 6.65 5.42 4.84 4.17 3.75 2.98 2.39 1.82 50.1  
39 1 20008.000 1 14.98 6.62 5.38 4.79 4.16 3.75 2.97 2.39 1.82 50.1  
39 1 20008.000 1 14.98 6.60 5.39 4.81 4.16 3.74 2.98 2.38 1.80 50.1  
39 1 20008.000 1 14.93 6.59 5.37 4.81 4.16 3.73 2.98 2.39 1.80 50.1  
39 1 20008.000 1 15.08 6.53 5.36 4.79 4.11 3.71 2.96 2.36 1.81 50.1

Drop Sequence Completed Time: 09:23 Air Temp (F): 55.9

GPS: Quality : DGPS Fix Latitude = 35 deg6.855201 N Longitude = 97  
deg26.456701 W PDOP = 1.80

Note:

40 1 20500.000 1 15.25 4.86 3.98 3.72 3.41 3.18 2.68 2.27 1.89 56.4  
40 1 20500.000 1 14.96 4.77 3.95 3.62 3.37 3.17 2.63 2.27 1.83 56.4  
40 1 20500.000 1 15.13 4.77 3.96 3.64 3.35 3.16 2.60 2.23 1.85 56.4  
40 1 20500.000 1 15.13 4.73 3.92 3.63 3.36 3.16 2.63 2.23 1.84 56.4  
40 1 20500.000 1 15.05 4.71 3.91 3.61 3.33 3.12 2.60 2.21 1.82 56.4  
40 1 20500.000 1 15.08 4.74 3.90 3.63 3.34 3.16 2.59 2.23 1.83 56.4

Drop Sequence Completed Time: 09:24 Air Temp (F): 56.1

GPS: Quality : DGPS Fix Latitude = 35 deg6.791231 N Longitude = 97  
deg26.397289 W PDOP = 1.90

Note:

41 1 21001.000 1 15.40 3.94 3.23 2.97 2.74 2.59 2.12 1.97 1.31 54.7  
41 1 21001.000 1 15.43 3.95 3.27 3.00 2.78 2.64 2.16 1.94 1.35 54.7  
41 1 21001.000 1 15.20 3.88 3.19 2.96 2.75 2.55 2.11 1.94 1.26 54.7  
41 1 21001.000 1 15.03 3.85 3.20 2.93 2.72 2.56 2.19 1.90 1.30 54.7  
41 1 21001.000 1 15.03 3.87 3.20 2.93 2.72 2.58 2.15 1.91 1.20 54.7  
41 1 21001.000 1 15.08 3.89 3.19 2.93 2.74 2.59 2.19 1.97 1.27 54.7

Drop Sequence Completed Time: 09:25 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.726007 N Longitude = 97  
deg26.337015 W PDOP = 2.30

Note:

42 1 21499.000 1 15.25 7.93 6.20 5.45 4.76 4.30 3.48 2.96 2.45 53.1  
42 1 21499.000 1 15.28 7.80 6.09 5.39 4.74 4.26 3.46 2.95 2.43 53.1

42 1 21499.000 1 15.20 7.77 6.11 5.39 4.73 4.30 3.47 2.94 2.42 53.1  
42 1 21499.000 1 15.23 7.79 6.11 5.43 4.76 4.28 3.49 2.96 2.41 53.1  
42 1 21499.000 1 15.13 7.71 6.06 5.37 4.70 4.25 3.45 2.96 2.42 53.1  
42 1 21499.000 1 15.23 7.74 6.09 5.38 4.73 4.30 3.48 2.92 2.43 53.1

Drop Sequence Completed Time: 09:26 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg6.661171 N Longitude = 97  
deg26.276937 W PDOP = 1.80

Note:

43 1 22003.000 1 15.40 5.85 5.01 4.66 4.34 4.01 3.22 2.85 2.33 56.0  
43 1 22003.000 1 15.18 5.71 4.90 4.62 4.25 3.94 3.23 2.80 2.28 56.0  
43 1 22003.000 1 15.25 5.69 4.88 4.58 4.22 3.94 3.27 2.80 2.29 56.0  
43 1 22003.000 1 15.13 5.69 4.86 4.59 4.22 3.92 3.23 2.80 2.30 56.0  
43 1 22003.000 1 15.20 5.69 4.87 4.57 4.22 3.92 3.25 2.76 2.27 56.0  
43 1 22003.000 1 15.05 5.68 4.86 4.58 4.23 3.91 3.55 2.80 2.30 56.0

Drop Sequence Completed Time: 09:28 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.595575 N Longitude = 97  
deg26.216169 W PDOP = 1.90

Note:

44 1 22499.000 1 15.23 5.41 4.18 3.69 3.46 3.20 2.64 2.28 1.85 54.1  
44 1 22499.000 1 15.13 5.31 4.13 3.68 3.40 3.17 2.63 2.21 1.87 54.1  
44 1 22499.000 1 14.96 5.17 4.04 3.62 3.36 3.10 2.59 2.18 1.83 54.1  
44 1 22499.000 1 15.01 5.22 4.08 3.64 3.37 3.12 2.61 2.18 1.84 54.1  
44 1 22499.000 1 15.01 5.15 4.04 3.61 3.34 3.11 2.56 2.16 1.81 54.1  
44 1 22499.000 1 14.88 5.16 4.05 3.62 3.34 3.10 2.59 2.14 1.84 54.1

Drop Sequence Completed Time: 09:29 Air Temp (F): 55.6

GPS: Quality : DGPS Fix Latitude = 35 deg6.531091 N Longitude = 97  
deg26.156422 W PDOP = 3.10

Note:

45 1 23001.000 1 15.23 6.01 5.03 4.56 4.19 3.88 3.19 2.44 2.21 54.4  
45 1 23001.000 1 14.96 5.90 4.96 4.45 4.14 3.82 3.16 2.44 2.19 54.4  
45 1 23001.000 1 14.98 5.89 4.94 4.45 4.13 3.84 3.16 2.49 2.19 54.4  
45 1 23001.000 1 14.98 6.00 5.03 4.55 4.25 3.92 3.15 2.42 2.32 54.4  
45 1 23001.000 1 15.03 5.88 4.92 4.49 4.13 3.83 3.17 2.40 2.20 54.4  
45 1 23001.000 1 14.83 5.71 4.77 4.33 3.96 3.68 3.00 2.44 2.70 54.4

Drop Sequence Completed Time: 09:30 Air Temp (F): 56.3

GPS: Quality : DGPS Fix Latitude = 35 deg6.465650 N Longitude = 97  
deg26.095894 W PDOP = 1.80

Note:

46 1 23499.000 1 15.52 4.72 4.17 3.94 3.70 3.53 2.97 2.56 2.16 50.1  
46 1 23499.000 1 15.08 4.57 4.04 3.84 3.60 3.41 2.87 2.47 2.08 50.1  
46 1 23499.000 1 15.10 4.61 4.09 3.87 3.64 3.44 2.88 2.53 2.09 50.1  
46 1 23499.000 1 15.05 4.60 4.05 3.84 3.61 3.41 2.90 2.50 2.09 50.1  
46 1 23499.000 1 15.10 4.62 4.07 3.87 3.63 3.45 2.88 2.52 2.09 50.1  
46 1 23499.000 1 15.05 4.59 4.03 3.82 3.58 3.41 2.88 2.50 2.07 50.1

Drop Sequence Completed Time: 09:39 Air Temp (F): 55.2

GPS: Quality : DGPS Fix Latitude = 35 deg6.400696 N Longitude = 97  
deg26.035781 W PDOP = 1.70

Note:

47 1 24000.000 1 15.45 4.92 4.36 4.12 3.83 3.54 2.95 2.48 2.05 47.1  
47 1 24000.000 1 15.05 4.79 4.29 4.04 3.73 3.46 2.85 2.44 1.98 47.1

47	1	24000.000	1	15.03	4.76	4.23	3.99	3.70	3.42	2.83	2.41	2.00	47.1
47	1	24000.000	1	14.98	4.75	4.25	4.02	3.72	3.44	2.84	2.41	1.99	47.1
47	1	24000.000	1	15.01	4.76	4.26	4.02	3.72	3.45	2.84	2.42	2.00	47.1
47	1	24000.000	1	15.03	4.75	4.26	4.02	3.71	3.46	2.85	2.43	2.01	47.1

Drop Sequence Completed Time: 09:42 Air Temp (F): 55.8

GPS: Quality : DGPS Fix Latitude = 35 deg6.335522 N Longitude = 97  
deg25.975515 W PDOP = 2.10

Note:

## **APPENDIX E**

CLIENT Olsson Associates

PROJECT NAME I-35 Pavement & Subgrade Survey 35589(04)

PROJECT NUMBER 22118

PROJECT LOCATION McClain County, Oklahoma

Borehole	Depth (in)	% Moist.	Liquid Limit	Plastic Limit	Plasticity Index	-3" Sieve	- 3/4" Sieve	-1/2" Sieve	-4 Sieve	-10 Sieve	-40 Sieve	-200 Sieve
C-01	22-46	18.5	22	17	5	100	100	100	99	98	89	53.9
C-01	46-58	15.5										
C-02	24-42	13.0										
C-02	42-60	10.8	21	14	7	100	100	100	99	99	88	60.2
C-03	23-41	14.2										
C-03	41-59	11.9	20	13	7	100	100	100	98	97	89	58.8
C-04	21-51	11.7	19	14	5	100	100	100	100	99	91	47.1
C-05	22-40	14.1	20	16	4	100	100	100	99	97	83	44.2
C-05	40-52	15.8										
C-06	22-40	13.6										
C-06	40-58	18.4	29	14	15	100	100	100	99	99	96	77.4
C-07	19-55	13.0	21	11	10	100	100	100	97	95	81	45.9
C-08	24-48	14.2	NV	NP	NP	100	100	100	96	92	81	39.0
C-08	48-60	14.7										
C-09	23-53	11.7										
C-09	53-59	12.0	21	11	10	100	100	100	98	97	88	56.8
C-10	23-41	11.0	16	13	3	100	100	100	100	99	85	34.7
C-10	41-59	12.4										
C-11	24-48	14.2										
C-11	48-60	17.3	32	12	20	100	100	100	100	100	94	74.9
C-12	26-50	13.2										
C-12	50-62	15.6	24	14	10	100	100	100	98	97	92	69.8
C-13	25-49	11.5	19	14	5	100	100	100	100	99	84	36.3
C-13	49-61	12.6										
C-14	19-52	11.0	NV	NP	NP	100	100	100	98	96	82	31.9
C-14	52-55	15.6										
C-15	21-45	11.8										
C-15	45-57	16.2	27	15	12	100	100	100	100	100	96	79.4
C-16	17-35	15.3	19	16	3	100	100	100	99	95	82	39.7
C-16	35-53	14.6										
C-17	21-39	12.7										
C-17	39-57	18.3	26	16	10	100	100	100	100	99	97	81.8
C-18	22-46	13.9	19	16	3	100	100	100	100	99	88	52.6
C-18	46-58	14.2										
C-19	22-46	12.4										
C-19	46-58	12.1	23	15	8	100	100	100	97	95	91	76.5
C-20	16-40	8.4	NV	NP	NP	100	100	100	97	93	81	32.7
C-20	40-52	14.2										
C-21	17-41	10.3										
C-21	41-47	10.8	21	13	8	100	100	100	94	91	80	48.1
C-22	19-31	17.4	19	13	6	100	100	100	93	83	62	30.2
C-23	20-32	15.0	17	13	4	100	100	100	78	69	50	21.3
C-24	19-43	4.9										

CLIENT Olsson Associates

PROJECT NAME I-35 Pavement & Subgrade Survey 35589(04)

PROJECT NUMBER 22118

PROJECT LOCATION McClain County, Oklahoma

Borehole	Depth (in)	% Moist.	Liquid Limit	Plastic Limit	Plasticity Index	-3" Sieve	- 3/4" Sieve	-1/2" Sieve	-4 Sieve	-10 Sieve	-40 Sieve	-200 Sieve
C-24	43-55	9.5	23	17	6	100	100	100	98	96	93	79.6
C-25	19-43	5.1										
C-25	43-55	11.1	22	15	7	100	100	100	100	99	95	78.6
C-26	17-29	7.6	NV	NP	NP	100	100	100	83	74	57	28.7
C-26	29-53	10.7										
C-27	20-32	6.2										
C-27	32-56	10.2	NV	NP	NP	100	100	100	100	99	92	51.3
C-28	17-41	5.8	NV	NP	NP	100	100	100	94	90	75	30.4
C-28	41-53	12.4										
C-29	19-43	12.8										
C-29	43-55	14.1	24	15	9	100	100	100	100	100	96	78.1
C-30	19-31	11.8										
C-30	31-43	8.9	19	15	4	100	100	100	99	99	90	46.3
C-30	43-55	14.8										
C-31	19-43	11.7										
C-31	43-55	12.9	21	16	5	100	100	100	100	99	93	67.6
C-32	18-30	16.0										
C-32	30-54	14.9	25	14	11	100	100	100	100	99	95	74.7
C-33	18-42	12.9										
C-33	42-54	14.4	20	14	6	100	100	100	100	99	92	63.5
C-34	20-44	9.4										
C-34	44-56	12.7	20	14	6	100	100	100	99	98	86	47.6
C-35	21-39	14.4	NV	NP	NP	100	100	100	98	96	81	31.4
C-35	39-50	17.2										
C-36	23-47	11.9										
C-36	47-59	14.4	24	14	10	100	100	100	100	99	93	68.3
C-37	22-46	10.6	NV	NP	NP	100	100	100	100	98	85	38.2
C-37	46-52	11.4										
C-38	22-52	12.6										
C-38	52-58	13.2	23	14	9	100	100	100	100	99	90	57.3
C-39	22-40	12.7	NV	NP	NP	100	100	100	100	99	86	35.8
C-39	40-58	14.9										
C-41	18-42	14.7	24	15	9	100	100	100	97	96	89	61.1
C-42	22-46	12.7	20	16	4	100	100	100	99	97	85	46.2
C-42	46-58	14.6										
C-43	24-48	16.0										
C-43	48-60	13.7	24	15	9	100	100	100	100	100	94	64.7
C-44	24-42	16.1	21	16	5	100	100	100	100	99	89	55.9
C-44	42-60	16.3										
C-45	23-53	12.8	19	14	5	100	100	100	99	98	82	42.8
C-45	53-59	10.4										
C-46	24-54	14.3										
C-46	54-60	15.9	25	15	10	100	100	100	100	99	95	76.1

## **APPENDIX F**

## GENERAL NOTES

### SOIL PROPERTY ABBREVIATIONS

N	Uncorrected SPT Penetration, blows per foot
N <sub>60</sub>	Corrected SPT Penetration, blows per foot
Q <sub>u</sub>	Unconfined Compressive Strength, psf
Mc	Moisture Content, %
LL	Liquid Limit, %
PL	Plastic Limit, %
PI	Plasticity Index, %

### DRILLING & SAMPLING ABBREVIATIONS

BS	Bag Sample
SPT	Split Spoon Sample
ST	Shelby Tube Sample
AU	Auger Sample
TC	Texas Cone Penetrometer
DCP	Dynamic Cone Penetrometer

### UNIFIED SOIL CLASSIFICATION SYSTEM (ASTM D 2487)

-- used to classify all soils unless otherwise noted --

Major Divisions			Group Symbol	Typical Names
<b>Course-Grained Soils</b> >50% retained on #200 sieve	<b>Gravels</b> 50% + of course fraction retained on #4 sieve	Clean Gravels	GW	Well-graded gravels and gravel-sand mixtures, little or no fines
			GP	Poorly graded gravels and gravel-sand mixtures, little or no fines
		Gravels with Fines	GM	Silty gravels, gravel-sand-silt mixtures
			GC	Clayey gravels, gravel-sand-clay mixtures
	<b>Sands</b> 50% + of course fraction passes #4 sieve	Clean Sands	SW	Well-graded sands and gravelly sands, little or no fines
			SP	Poorly graded sands and gravelly sands, little or no fines
		Sands with Fines	SM	Silty sands, sand-silt mixtures
			SC	Clayey sands, sand-clay mixtures
<b>Fine-Grained Soils</b> <50% passes #200 sieve	<b>Silts and Clays</b> Liquid Limit ≤ 50%	ML	Inorganic silts, very fine sands, rock four, silty or clayey fine sands	
		CL	Inorganic clays of low to medium plasticity, gravelly/sandy/silty/lean clays	
		OL	Organic silts and organic silty clays of low plasticity	
	<b>Silts and Clays</b> Liquid Limit > 50%	MH	Inorganic silts, micaceous or diatomaceous fine sands or silts, elastic silts	
		CH	Inorganic clays or high plasticity, fat clays	
		OH	Organic clays of medium to high plasticity	
<b>Highly Organic Soils</b>			PT	Peat, muck, and other highly organic soils

**Prefix:** G = Gravel, S = Sand, M = Silt, C = Clay, O = Organic    **Suffix:** W = Well Graded, P = Poorly Graded, M = Silty, L = Clay, LL < 50%, H = Clay, LL > 50%

#### PLASTICITY OF COHESIVE SOIL

Degree of Plasticity	Plasticity Index	Swell Potential
None	0 to 4	Very Low
Slight	5 to 9	Low
Medium	10 to 19	Low to Medium
High	20 to 39	Medium to High
Very High	40+	Very High

#### CONSISTENCY - COHESIVE SOILS

Consistency	SPT
Very Soft	<2
Soft	2 to 4
Medium Stiff	5 to 8
Stiff	9 to 14
Very Stiff	15 to 30
Hard	31+

#### ROCK HARDNESS

SPT (in/50)	TCP (in/100)	Rock Description
6+	6+	Very Soft / Very Poorly Cemented
5 - 6	3 - 6	Soft / Poorly Cemented
4 - 5	2 - 3	Moderately Hard / Cemented
3 - 4	1 - 2	Hard / Well Cemented
<3	<1	Very Hard / Very Well Cemented

#### MOISTURE OF COHESIVE SOIL

Description	Condition	Moisture Content
Dry, Dusty	Dry	0 to 10%
Damp	Moist	10 to 30%
Free Water	Wet	30 to 70%

#### DENSITY - COHESIONLESS SOILS

Relative Density	SPT
Very Loose	<4
Loose	4 to 10
Medium Dense	11 to 30
Dense	31 to 50
Very Dense	51+

#### ROCK CORE QUALITY

Core Quality	RQD
Excellent Quality	90 – 100%
Good Quality	75 – 90%
Fair Quality	50 – 75%
Poor Quality	25 – 50%
Very Poor Quality	<25%